

## Vehicle Specifications for DOFAW Hilo:

- A. 1/4 -1/2 ton pick-up truck with 4-door, standard bed, diesel powered, 4-wheel drive.  
Chevy Colorado, Toyota Tacoma or equivalent, delivered to 19 E. Kawili St. Hilo, HI

<u>Category</u>	<u>Minimum Specifications</u>
1. Year of Manufacture:	2023 or newer
2. Model:	Chevy Colorado, Toyota Tacoma, or equal
3. Type:	4-wheel drive
4. GVW Rating:	6,000 lbs., Minimum Capacity
5. Wheel Base:	128 inches.
6. Engine:	2.8 L Minimum 181 hp 4-cylinder minimum Heavy duty cooling system, External Engine oil Cooler, Non-California Emissions.
7. Transmission:	Automatic transmission automatic w/overdrive External Oil cooler
8. Transfer Case:	2 speed minimum Part time 4 wheel drive Locking Rear Differentials
9. Cab:	<b>4 door</b> , double cab, 5-foot bed minimum Front seat w/ center console Upholstery of vinyl material or equivalent Full length vinyl flooring or equivalent front Heater/Defroster Factory installed premium AM/FM radio Blue tooth capable Full instrument, Gauge Type package Factory installed air conditioning-CFC free Overhead Map lamps Sliding rear window
10. Body:	4 door, 5.0 ft cargo box 60" pickup box with composite inner shell or spray-on bedliner.  Skid plate (Transmission, Engine, Fuel tank, Oil pan and Transfer case) Complete after factory rust proofing, with min. five (5) Year unlimited mileage requirement warranty. Factory standard dual trailer tow "swing away type" Exterior mirrors.
11. Bumpers:	Heavy duty front end with two tow hooks. Heavy duty rear step bumper 7,500 lb. towing capacity.

<u>Category</u>	<u>Minimum Specifications</u>
12. Electrical System:	Heavy duty 12 volt system Heavy duty 12 volt, minimum 600 CCA battery Courtesy lamp package with map lamps Factory 7-wire trailer brake light package
13. Steering:	Power assist, power steering Factory installed front stabilizer bar Steering damper
14. Brakes:	Power assisted Anti-lock, front and rear disc
15. Tires/Wheels:	All terrain tires Tires and wheels must meet manufactures and federal GAWR Requirements for GVW submitted. Full size spare tire mounted under truck bed Five (5) 18x8 steel rims minimum Jack and wheel wrench
16. Axle:	Front axle shall include automatic locking hubs Rear axle shall include Limited Slip Differential Minimum 3:42 gear ratio
17. Suspension:	Heavy duty maximum front and rear suspension
18. Color:	Exterior White High gloss urethane with base clear coat Interior Camel, Medium Beige or equal
19. Miscellaneous:	2-1/2 lbs. ABC Dry chemical Fire Extinguisher mounted Inside the vehicle Fuel tank, 21-gallon Capacity minimum Locking gas cap Receiver type tow hitch with ball combo Owner-Operator Manual (1 copy) All repair and electric shop manuals (1 copy) 4 FOB key sets

**Delivery date no later than 3/15/2024**

**Specifications Contact:**

Nick Agorastos  
nicholas.r.agorastos@hawaii.gov  
(808) 974-4226