

**DEPARTMENT OF HEALTH
KONA HEALTH CENTER
REQUEST FOR QUOTES
Single ADA Water Cooler with Bottle Filling Station**

PURPOSE

The purpose for this Request for Quotes (RFQ) is to procure one (1) Single ADA Water Cooler with Bottle Filling Station and three (3) replacement filtration filters for the State of Hawaii, Department of Health facility located at:

Kona Health Center
75-1015 Haukapila Street
Kealahou, HI 96750

Product to be Elkay Enhanced EZH2O Bottle Filling Station & Single ADA Cooler Filtered Refrigerated Light Gray or similar and 3 replacement filtration filters.

SCOPE OF WORK

The VENDOR shall cover all steps:

- A. Review Exhibit 'A', Specifications for the Elkay Enhanced EZH2O Bottle Filling Station as reference to the warranted product or similar.
- B. Complete and Submit Offer Form attached to the RFQ. The price quote shall be the all-inclusive cost to the STATE, consisting of all related costs and applicable taxes for providing the specified product.
- C. Submit Company Quote with product specifications.
- D. Attach a Copy of their Certificate of Vendor Compliance and W-9.

OTHER

- A. Invoicing for product from the VENDOR shall be submitted via mail to:

DEPARTMENT OF HEALTH
HAWAII DISTRICT HEALTH OFFICE
P.O. Box 916
Hilo, Hawaii 96721-0916

- B. Delivery of Product shall be addressed to:

Kona Health Center
75-1015 Haukapila Street
Kealahou, HI 96750

**DEPARTMENT OF HEALTH
KONA HEALTH CENTER
REQUEST FOR QUOTES
Single ADA Water Cooler with Bottle Filling Station**

EXHIBIT 'A'

Elkay Enhanced EZH2O Bottle Filling Station & Single ADA Cooler Filtered Refrigerated Light Gray Model LZS8WSLP or Similar

Chilling Capacity of 8.0 GPH (gallons per hour) of 50 F drinking water, based on 80 F inlet water and 90 F ambient, per ASHRAE 18 testing. Features shall include Antimicrobial*, Automatic Filter Status Reset, Energy Savings, Filtered, Green Ticker™, Hands Free, Laminar Flow, Real Drain, Visual Filter Monitor. Furnished with Flexi-Guard® Safety Bubbler. Electronic Bottle Filler Sensor with Electronic Front and Side Bubbler Pushbar activation. Product shall be Wall Mount (On Wall), for Indoor applications, serving 1 station(s). Unit shall be certified to UL 399 and CAN/CSA C22.2 No. 120.

Special Features:	Antimicrobial, Automatic Filter Status Reset, Energy Savings, Filtered, Green Ticker™, Hands Free, Laminar Flow, Real Drain, Visual Filter Monitor
Finish:	Light Gray Granite
Power:	115V/60Hz
Bubbler Style:	Flexi-Guard® Safety Bubbler
Activation by:	Electronic Bottle Filler Sensor with Electronic Front and Side Bubbler Pushbar
Mounting Type:	Wall Mount (On Wall)
Chilling Capacity*:	8.0 GPH
Full Load Amps	5
Rated Watts:	370
Dimensions (L x W x H):	18-3/8" x 19" x 39-7/16"
Approx. Shipping Weight:	85 lbs.
Installation Location:	Indoor
No. of Stations Served:	1



*Based on 80° F inlet water & 90° F ambient air temp for 50° F chilled drinking water.

- Visual Filter Monitor: LED Filter Status Indicator for when filter change is necessary.
- Filter is certified to NSF 42 and 53 for lead, cyst, particulate, chlorine, taste and odor reduction. 3,000 gal. capacity.
- Energy-savings mode reduces energy consumption.
- Green Ticker: Informs user of number of 20 oz. plastic water bottles saved from waste.
- Laminar flow provides clean fill with minimal splash.

**DEPARTMENT OF HEALTH
KONA HEALTH CENTER
REQUEST FOR QUOTES
Single ADA Water Cooler with Bottle Filling Station**

- Key plastic components are manufactured with silver ion antimicrobial agent helping to provide clean, stain- and odor-free surfaces.
- Real Drain System eliminates standing water.

COOLING SYSTEM

- Compressor: Hermetically-sealed, reciprocating type, single phase. Sealed-in lifetime lubrication.
- Condenser: Fan cooled, copper tube with aluminum fins. Fan motor is permanently lubricated.
- Cooling Unit: Combination tube-tank type. Continuous copper tubing with is fully insulated with EPS foam that meets UL requirements for self-extinguishing material.
- Refrigerant Control: Refrigerant R-134a is controlled by accurately calibrated capillary tube.
- Temperature Control: Easily accessible enclosed adjustable thermostat is factory preset. Requires no adjustment other than for altitude requirements