

SCOPE OF WORK

SIDEWALK REPAIR AT KALAU PLACE, WAIMANALO

TMK: 4-1-030:053

RFQ-25-HHL-005

1.0 Existing Conditions:

- A. TMK: 4-1-030:053 located on Kalau Place, Waimanalo. This lot is part of the Waimanalo Residence Lots, Series 5.

- B. Tree roots have lifted and damaged portions of the sidewalk, curb, and gutter area adjacent to the TMK reference above. The C & C requested that the sidewalk be repaired. The tree roots remain under the sidewalk and will need to be removed. The tree that caused the damage has since been removed.

2.0 Scope of Work:

The Contractor shall provide labor, materials, and equipment to remove, repair, and replace the sidewalk, curb and gutter areas damaged by the tree roots at 41-217 Kalau Place, Waimanalo. All replaced sections shall match the existing dimensions, profiles, finishes and materials.

- A. **Compliance with Standards:** All construction activities shall adhere to the “Standard Specifications for Public Works Construction” (September 1986) and “Standard Details for Public Works Construction” (September 1984), as amended. This includes subgrade and base preparation, minimum slab thickness and slope, concrete strength, forms, placement, joints, finish, and curing.

- B. **Demolition and Removal:**
 - 1. Demolish and remove damaged sidewalk sections as indicated in the provided pictures.
 - 2. Carefully remove damaged sections of curb and gutter to prevent further damage to surrounding infrastructure.
 - 3. Preserve adjacent structure and utilities during demolition.

- C. **Subgrade Preparation:**
 - 1. Eliminate all tree roots and excavate the subgrade to a depth of one foot below the current ground level.
 - 2. Re-compact the existing base course.
 - 3. Supply and install additional base course beneath the sidewalk to achieve the intended final elevation.

4. Ensure all fill and base materials for over-excavated areas are placed in accordance with the standards.

D. **Storm Drain Rehabilitation**

1. Please verify the state and condition of the existing storm drain vault connected to the curb & gutter.
2. If necessary and appropriate, please make all appropriate rehab and reconstruction to meet City and County Standards (attached).

E. **Concrete Installation:**

1. Supply and install new sidewalk to match existing dimensions, profiles, and materials.
2. Verify the adequacy of the subgrade and make necessary adjustments for stability.
3. Excavate the base to the required depth, ensuring proper compaction and alignment to match existing grades.
4. Supply and install new curb and gutter sections to match existing dimensions, profiles, and materials.

F. **Utility Box Management:**

1. Identify and protect utility boxes within the construction area.
2. Monitor utility boxes throughout the project to prevent damage.
3. Ensure the functionality of utility boxes is maintained during and after construction.
4. If the utility box condition requires, please rehab and reconstruct utility boxes to City and County Standards (attached).

G. **Site Management:**

1. Haul out and dispose of removed and generated spoil materials off-site.
2. Erect and maintain barriers to prevent access to the project area for seven days after the concrete sidewalk has been poured.
3. Provide and maintain alternative passageways for pedestrian traffic during the construction period.

4. Repair and restore all disturbed landscaping and hardscape to their original condition as soon as practicable.

3.0 **General Conditions:**

A. **Licenses and Experience:**

Bidders and subcontractors must possess all required valid State of Hawaii licenses and specialty licenses and be in good standing. Contractors shall have at least five years of work experience in Hawaii within their specialty.

B. **Work Hours and Impact:**

Minimize impact to surrounding residential houses. Work hours are from 7:30am to 3:30pm.

C. **Environmental Compliance:**

Cover all costs associated with best management practices for water pollution control as required by local, state, and federal regulations.

D. **Safety and Cleanliness:**

Maintain a clean and safe construction area at all times. If construction activities pose a hazard, rope off the area and post warning signs.

E. **Damage and Repairs:**

Repair any damage caused by construction activities at no additional cost to DHHL. Document the existing condition of the area before beginning work to verify any damage claims.

F. **Material Specificaitons:**

Submit material specifications and MSDS/SDS datasheets for all proposed products and chemicals to the DHHL Project Manager for approval before delivery to the job site.

G. **Regulatory Compliance:**

1. Ensure compliance with all applicable OSHA and HIOSH requirements.
2. Adhere to HRS, Chapter 104 Prevailing Wages Laws for this project.

H. **Project Completion and Warranty:**

1. The time of performance for this project will be to complete all work within 45 calendar days from the date of the Notice to Proceed.
2. Contractor to provide a one-year warranty for materials and workmanship upon project completion.

I. **Additional Work:**

Any additional work not covered by this scope of work must be approved by the DHHL Project Manager prior to commencement. Additional work will be compensated at actual cost plus a 20 percent markup, inclusive of all taxes, overhead, profit, and incidental expenses.


PHOTOS FROM SITE AT 41-217 KALAU PL, WAIMANALO TMK 4-1-030:053












Class "A" Concrete quantity = 0.0584 cu. yd./lin. ft.

CAST IN PLACE INTEGRAL CURB AND GUTTER

Scale: 1 1/2" = 1'-0"



Class "A" Concrete quantity = 0.0506 cu. yd./lin. ft.

CAST IN PLACE INTEGRAL DRIVEWAY CURB AND GUTTER

Scale: 1 1/2" = 1'-0"

TABLE

DIST. CURB LINE TO R	SLOPE	HEIGHT
12'	1 1/16" to 12"	7 3/8"
10'	3/4" to 12"	7 7/16"
8'	7/8" to 12"	7 1/2"
7'	15/16" to 12"	7 9/16"
6'	1 1/16" to 12"	7 5/8"
3'	1 15/16" to 12"	8 1/8"

R-4
REVISED

STANDARD
DETAILS

INTEGRAL CURB AND GUTTER
INTEGRAL DRIVEWAY CURB AND GUTTER

JANUARY 1995

SCALE: 1-1/2" = 1'-0"

COUNTY OF KAUAI
CITY & COUNTY OF HONOLULU
COUNTY OF MAUI
COUNTY OF HAWAII

SECTION 41 - CONCRETE CURB AND GUTTER

41.1 DESCRIPTION

This work shall consist of constructing concrete curb and gutter to the established line and grade. The gutter shall be cast in place on a prepared subgrade, and the curb shall be of precast units or cast in place as an integral structure with the gutter.

41.2 MATERIALS

All curbs and gutters shall be constructed with Class "B" concrete containing an admixture conforming to ASTM C 494, Type D, unless designated otherwise on the plans or in the special provisions.

A. Precast Curb Blocks. The dimension of the curb blocks shall conform to the dimensions shown in the Standard Details. The front and top exposed faces and the top 2 inches of the back face of the curb block shall be smoothly finished. No air pockets or exposed rock shall appear on any surface.

Any precast curb block which does not conform to the standard dimensions or surface finish shall not be used.

B. Cast-in-Place Gutter or Cast-in-Place Curb and Gutter. Concrete gutter or integral curb and gutter shall be formed on a prepared subgrade or subbase and shall be true to the established line and grade. The dimensions and slope shall conform to the Standard Details and as shown on the construction plans.

All through gutters across street intersections and wherever specified on the plans shall be reinforced with galvanized welded wire fabric with a minimum cover of 2 inches. Unless specified otherwise in the Standard Details for the County, the wire fabric shall be 6"x6"-6/6.

C. Forms. Form materials shall be free from warps, bends, twists, or other defects which will impair the appearance of the completed work.

Wood forms shall be surfaced on the upper edges and on the sides against which the concrete is to be placed.

Form sections when set in place shall possess adequate strength and rigidity to remain true to the established line and grade.

41.3 DETAILS

A. Subgrade. Before erecting the forms, the subgrade or subbase shall be graded and compacted. Wherever unsuitable material is encountered, it shall be removed and replaced with select borrow and compacted to the required elevation in accordance with the requirements under Section 12, "Roadway Excavation."

B. Erecting Forms. All forms, wood or metal, shall be clean and oiled prior to setting in place. The erected forms shall be adequately secure to prevent movement in any direction during placement of the concrete.

C. Placing Precast Curb Blocks. All curb blocks shall be placed on a prepared subgrade, well bedded and true to the established line and grade. The joints between blocks shall be 1/2 inch wide. The joints shall be filled with mortar for the full depth and height of the blocks. After the mortar has gained sufficient strength, the backfill shall be thoroughly and carefully tamped into place.

D. Placing Concrete. Prior to pouring concrete, the prepared subgrade or subbase shall be dampened. The concrete shall be poured, spaded, and tamped thoroughly into the forms.

E. Finishing. Within a few hours after placing of concrete, the gutter or the integral curb and gutter forms shall be removed and the exposed faces shall be hand finished with a steel trowel and all irregularities corrected. All exposed edges shall be rounded with an edging tool.

On grades exceeding 6%, the gutter surface shall be lightly broomed in the direction parallel to the curb face.

F. Joints. Transverse weakened plane joints shall be formed on the gutter or on the integral curb and gutter spaced as shown on the plans. The joints shall not exceed 12-foot intervals. The joints may be formed with a removable metal strip or by sawing. Construction joints shall be keyed with a minimum of one #3 tie bar 15 inches long.

G. Curing and Protecting. The newly formed concrete curb and gutter shall be cured as specified under Section 39, "Portland Cement Concrete."

Barriers shall be erected and maintained for at least 5 days to prevent accidental damage to the curb and gutter.

H. Maintenance. The Contractor shall repair and clean, at his own expense, all curb and gutter damaged, discolored, or splashed with asphalt or concrete during construction. Damaged section shall be removed entirely and reconstructed. No patching or refinishing shall be permitted.

41.4 MEASUREMENT AND PAYMENT

Measurement for payment shall be by the lineal foot based on the actual work completed in place.

Payment for curb and gutter shall be made at the unit price bid per lineal foot and shall be full compensation for furnishing all material, tools, equipment, and labor necessary to construct the work including the subgrade preparation.

SECTION 42 - CONCRETE SIDEWALK

42.1 DESCRIPTION

This work shall consist of constructing concrete sidewalks and other walkways to the established line and grade.

42.2 MATERIALS

Unless specified otherwise on the plans, Class "B" concrete containing an admixture conforming to ASTM C 494, Type D, and/or ASTM C 260, shall be used in constructing the sidewalks. Premolded expansion joint filler shall conform to the requirements under ASTM D 1751.

42.3 DETAILS

A. Subgrade. The sidewalk area shall be graded to the required cross section, watered and thoroughly compacted to the established subgrade. Whenever unsuitable material is encountered, it shall be removed to a depth of 6 inches below the subgrade surface and replaced with select borrow and thoroughly compacted.

B. Forms. Metal or wood forms shall be free from warp, and shall be clean and oiled before setting in place. The forms shall be true to established line, grade and cross slope. The forms shall be sturdy and rigidly held in place by stakes, clamps, spreaders or braces to insure against movement during and after placement of concrete.

C. Placing and Finishing. Prior to pouring of concrete, the subgrade shall be dampened. Concrete shall be poured continuously and shall be thoroughly tamped and floated to a smooth and even surface. The pouring and constructing of alternating blocks shall not be permitted.

The finished surface shall be scored into squares with sides equal to the sidewalk width, in 4-foot squares, or as shown on the plans.

D. Joints. Expansion joints shall be constructed at every 96- to 100-foot spacing and at the beginning and at the end of curb returns. The joints shall be constructed with premolded expansion type filler. Contraction joints shall be spaced no farther than 30 feet apart. Construction shall be as specified under Section 37, "Portland Cement Concrete Pavement."

E. Curing and Protecting. The finished concrete sidewalk shall be cured as specified under Section 39, "Portland Cement Concrete," and shall be protected against damage or defacement of any kind. Sidewalk which is not acceptable by the Engineer because of damage or defacement shall be removed and replaced by the Contractor at his own expense.

42.4 MEASUREMENT AND PAYMENT


Concrete sidewalk shall be measured for payment by the square foot. Payment shall be made at the unit price bid and shall be full compensation for furnishing the material, tools and labor necessary to complete the work, including the preparation of the subgrade.

STANDARD SIDEWALK WIDTHS

Sidewalk widths for sidewalks in districts described in the Comprehensive Zoning Code for the City and County of Honolulu shall conform to the following:

District	Paved Sidewalk Width
All Residential	4 feet minimum
A-1, A-2, and A-3 Apartment	4 feet minimum
A-4 and A-5 Apartment	6 feet minimum
H-1 Resort Hotel	4 feet minimum; required width for each location shall be determined by the Chief Engineer.
H-2 Hotel	Full width unless determined otherwise by the Chief Engineer.
B-1 Business	4 feet minimum
B-2, B-3, and B-5 Business	6 feet minimum
B-4 Business	Full width
All Industrial	4 feet minimum
All Planned Development (For streets to be dedicated to the City)	4 feet minimum


SIDEWALK WITH STANDARD CURB & GUTTER



NOTE A:

- Full-width concrete sidewalks may be permitted when constructed for the entire block.
- Lawn grass or vegetative ground cover of a type with a maximum growth height of 4" or of a type that will grow at a trimmed height of 4" except vines or other planting which may be a tripping hazard. 4" topsoil required.
- In lieu of lawn grass the Chief Engineer may authorize:
 - Acceptable artificial turf, with proper bases,
 - Precast masonry units laid closely in a uniform pattern (bricks, tile caps, etc.) with proper base,
 - Asphalt concrete on proper base,
 - Concrete-poured separately from the concrete sidewalk, and of similar thickness, and
 - Loose aggregates, such as basaltic, coral or limestone chips.
- Street trees including existing trees may be permitted in sidewalk areas subject to the approval of the Department of Parks and Recreation.
- Sprinklers, set flush with the surface, may be permitted by the Chief Engineer.
- In areas where curbs exist with unpaved sidewalks, temporary asphalt concrete walkways may be installed, if authorized by the Chief Engineer.
- Deviation from this standard and other sidewalk standards may be permitted upon written approval of the Chief Engineer.

SIDEWALK AREA WITHOUT CURB OR GUTTER



GENERAL NOTE:

Mailbox support shall be of a type which causes minimal obstruction to traffic.

R-28
REVISED

STANDARD
DETAILS

SIDEWALK DETAILS


CITY & COUNTY OF HONOLULU

SEPTEMBER 1984


Storm Drains

PART

2



PLAN




ELEVATION

TYPE "A" CATCH BASIN

SCALE: 1/4" = 1'-0"

NOTES:

1. Provide 2 cu. ft. of crushed rock, ASTM size #9 Rock Sand, at weep hole.
2. C.B. wing shall be installed to favor upstream of gutter flow.
3. See sheet D-2 for reinforcement details.
4. Rungs shall not be installed over a pipe connection and the lowest rung shall be not more than 2'-0" above the invert.



SECTION A-A

D-2

STANDARD
DETAILS

SEPTEMBER 1984


TYPE "A" CATCH BASIN
REINFORCEMENT DETAILS

SCALE: 1/4" = 1'-0"

COUNTY OF KAUAI
CITY & COUNTY OF HONOLULU
COUNTY OF MAUI
COUNTY OF HAWAII

TYPE "A" CATCH BASIN REINFORCEMENT DETAILS


SCALE: 1/4" = 1'-0"




PLAN

NOTES:

1. See sheet D-13 for reinforcement at pipes and corners.
2. Spliced reinforcing bars shall be lapped at least 30 diameters.




SECTION C-C




SECTION B-B

SECTION A-A



ELEVATION



TYPE "E" CATCH BASIN

SCALE: 1/4" = 1'0"

NOTES:

1. Provide 2 cu. ft. of crushed rock (Rock Sand), ASTM size #9, at weep holes.
2. See sheet D-4 for reinforcement details.
3. Rungs shall not be installed over a pipe connection and the lowest rung shall be not more than 2'-0" above the invert.
4. This catch basin shall be used with drain pipes 60 inches or less in diameter.

D-4

STANDARD
DETAILS


SEPTEMBER 1984

TYPE "E" CATCH BASIN
REINFORCEMENT DETAILS

COUNTY OF KAUAI
CITY & COUNTY OF HONOLULU
COUNTY OF MAUI
COUNTY OF HAWAII

TYPE "E" CATCH BASIN REINFORCEMENT DETAILS


SCALE: 1/4" = 1'-0"




PLAN

NOTES:

1. See sheet D-13 for reinforcement at pipes and corners.
2. Spliced reinforcing bars shall be lapped at least 30 diameters.




SECTION C-C




DETAIL

SECTION B-B

SECTION A-A



PLAN




ELEVATION

TYPE "B" CATCH BASIN

SCALE: 1/4" = 1'-0"

NOTES:

1. Provide 2 cu. ft. of crushed rock, ASTM size #9 Rock Sand, at weep hole.
2. C.B. wing shall be installed to favor upstream of gutter flow.
3. See sheet D-6 for reinforcement details.
4. Rungs shall not be installed over a pipe connection and the lowest rung shall be not more than 2'-0" above the invert.



SECTION A - A

D-6


STANDARD
DETAILS

SEPTEMBER 1984

TYPE "B" CATCH BASIN
REINFORCEMENT DETAILS

SCALE: 1/4" = 1'-0"


COUNTY OF KAUAI
& COUNTY OF HONOLULU
COUNTY OF MAUI
COUNTY OF HAWAII



PLAN

TYPE "B" CATCH BASIN REINFORCEMENT DETAILS


SCALE: 1/4" = 1'-0"




SECTION C-C

NOTES:


- 1 See sheet D-13 for reinforcement at pipes and corners.
2. Spliced reinforcing bars shall be lopped at least 30 diameters.



SECTION B-B



SECTION A-A





TYPE "F" CATCH BASIN

SCALE: 1/4" = 1'-0"

NOTES:

1. Provide 2 cu. ft. of crushed rock (Rock Sand) ASTM size #9, at weep holes.
2. See sheet D-8 for reinforcement details.
3. Rungs shall not be installed over a pipe connection and the lowest rung shall be not more than 2'-0" above the invert.



D-8


STANDARD
DETAILS

SEPTEMBER 1984

TYPE "F" CATCH BASIN
REINFORCEMENT DETAILS

SCALE: 1/4" = 1'-0"

COUNTY OF KAUAI
CITY & COUNTY OF HONOLULU
COUNTY OF MAUI
COUNTY OF HAWAII



2 - #4 at 6" o.c. at bottom
 5 - #6 at 8" o.c. bottom
 #5 at 8" o.c. bottom
 #6 at each corner

Type "DA" frame & cover


PLAN

NOTES:


1. See sheet D-13 for reinforcement at pipes and corners.
2. Spliced reinforcing bars shall be lapped at least 30 diameters.

TYPE "F" CATCH BASIN REINFORCEMENT DETAILS


SCALE: 1/4" = 1'-0"



SECTION C-C



SECTION B-B



SECTION A-A

COUNTY OF KAUAI
CITY & COUNTY OF HONOLULU
COUNTY OF MAUI
COUNTY OF HAWAII


SCALE: 3/8" = 1'-0"

TYPE "C" CATCH BASIN

SEPTEMBER 1984

STANDARD
DETAILS

D-9




PLAN

TYPE "C" CATCH BASIN


SCALE: 3/8" = 1'-0"

NOTES:

1. Provide 2 cu. ft. of crushed rock, ASTM size #9 Rock Sand, at weep hole.
2. See sheet D-10 for reinforcement details.
3. Rungs shall not be installed over a pipe connection and the lowest rung shall be not more than 2'-0" above the invert.



ELEVATION



SECTION A-A

D-10

STANDARD
DETAILS

SEPTEMBER 1984

TYPE "C" CATCH BASIN
REINFORCEMENT DETAILS

SCALE: 3/8" = 1'-0"


COUNTY OF KAUAI
CITY & COUNTY OF HONOLULU
COUNTY OF MAUI
COUNTY OF HAWAII

TYPE "C" CATCH BASIN REINFORCEMENT DETAILS


SCALE: 3/8" = 1'-0"

NOTES:


1. See sheet D-13 for reinforcement at pipes and corners.
2. Spliced reinforcing bars shall be lapped at least 30 diameters.




PLAN




SECTION B-B



SECTION A-A



PLAN




ELEVATION

TYPE "D" CATCH BASIN

SCALE: 3/8" = 1'-0"

NOTES:

1. Provide 2 cu. ft. of crushed rock, ASTM size #9 Rock Sand, at weep hole.
2. See sheet D-12 for reinforcement details.
3. Rungs shall not be installed over a pipe connection and the lowest rung shall be not more than 2'-0" above the invert.



SECTION A-A

D-12


STANDARD
DETAILS

SEPTEMBER 1984


TYPE "D" CATCH BASIN
REINFORCEMENT DETAILS

SCALE: 3/8" = 1'-0"


COUNTY OF KAUAI
CITY & COUNTY OF HONOLULU
COUNTY OF MAUI
COUNTY OF HAWAII



PLAN



SECTION B-B




SECTION A-A

TYPE "D" CATCH BASIN REINFORCEMENT DETAILS

SCALE: 3/8" = 1'-0"


NOTES:

1. See sheet D-13 for reinforcement at pipes and corners.
2. Spliced reinforcing bars shall be lapped at least 30 diameters.




TYPICAL REINFORCEMENT AT PIPES

SCALE: 1" = 1'-0"




TYPICAL CORNER REINFORCEMENT LAPPING

SCALE: 1" = 1'-0"



DETAIL "A"

SCALE: 1 1/2" = 1'-0"




DETAIL "B"

SCALE: 1" = 1'-0"


CATCH BASIN DETAILS

COUNTY OF KAUAI CITY & COUNTY OF HONOLULU COUNTY OF MAUI COUNTY OF HAWAII	CATCH BASIN DETAILS SCALE: AS NOTED	STANDARD DETAILS	D-13
--	--	---------------------	------

SEPTEMBER 1984



DETAIL "A₁"
 SCALE: 1 1/2" = 1'-0"



REINFORCEMENT FOR DETAIL "A₁"
 SCALE: 1 1/2" = 1'-0"

DETAILS FOR CATCH BASIN WITH 5" CURB

COUNTY OF KAUAI
 CITY & COUNTY OF HONOLULU
 COUNTY OF MAUI
 COUNTY OF HAWAII


SCALE: AS NOTED

DEFLECTOR INLET
 FOR CATCH BASIN


SEPTEMBER 1984

STANDARD
 DETAILS


D-15




PLAN



SECTION A-A



SECTION B-B



SECTION C-C

SCALE: 2" = 1'-0"

NOTE:

For 3' - 6" C.B. throat construct
 3 deflector units at 8 1/2" o.c.

DEFLECTOR INLET FOR CATCH BASIN

SCALE: 1/2" = 1' - 0"

D-16


STANDARD
DETAILS

SEPTEMBER 1984

MONOLITHIC CONSTRUCTION OF CATCH
BASIN TOP SLAB AND SIDEWALK

SCALE: 3/16" = 1'-0"

COUNTY OF KAUAI
CITY & COUNTY OF HONOLULU
COUNTY OF MAUI
COUNTY OF HAWAII




TYPE "A" CATCH BASIN

TYPE "B" CATCH BASIN

NOTES

1. A four foot section of sidewalk, on both sides of the catch basin, shall be poured monolithically with the top deck of the catch basin.
2. Pour top deck of catch basin after the curb and gutter are installed.
3. Scoring shall be done according to the drawing.
4. Monolithic construction of types "C" and "D" catch basins and sidewalk shall be similar to detail for type "B" catch basin.


MONOLITHIC CONSTRUCTION OF CATCH BASIN
TOP SLAB AND SIDEWALK



PLAN

NOTES:

1. See sheet D-26 for channelizing detail.
2. See sheet D-13 for reinforcement at pipes and or corners.
3. Rungs shall not be installed over a pipe connection and the lowest rung shall be not more than 2' - 0" above the invert.



SECTION A-A

**SHALLOW DRAIN MANHOLE
FOR SIDEWALK AREA**

COUNTY OF KAUAI
CITY & COUNTY OF HONOLULU
COUNTY OF MAUI
COUNTY OF HAWAII


SHALLOW DRAIN MANHOLE
FOR SIDEWALK AREA

STANDARD
DETAILS

D-17

SCALE: 3/8" = 1'-0"


SEPTEMBER 1984



PLAN

NOTES:

1. See sheet D-26 for channelizing detail.
2. See sheet D-13 for reinforcement at pipes and corners.
3. Rungs shall not be installed over a pipe connection and the lowest rung shall be not more than 2'-0" above the invert.



SECTION A-A

**SHALLOW DRAIN MANHOLE
FOR PAVEMENT AREA**

D-18




STANDARD
DETAILS

SHALLOW DRAIN MANHOLE
FOR PAVEMENT AREA


SEPTEMBER 1984

SCALE: 3/8" = 1'-0"

COUNTY OF KAUAI
CITY & COUNTY OF HONOLULU
COUNTY OF MAUI
COUNTY OF HAWAII




SECTION A-A



SECTION A-A

FOR SIDEWALK AREA
 SCALE: 3/8" = 1'-0"


FOR PAVEMENT AREA
 SCALE: 3/8" = 1'-0"



DETAIL
 SCALE: 1 1/2" = 1'-0"

PRE-CAST TOP SLAB
FOR SHALLOW DRAIN MANHOLE

COUNTY OF KAUAI CITY & COUNTY OF HONOLULU COUNTY OF MAUI COUNTY OF HAWAII	PRE-CAST TOP SLAB FOR SHALLOW DRAIN MANHOLE SCALE: AS NOTED	STANDARD DETAILS	D-19 SEPTEMBER 1984
--	---	---------------------	------------------------



- NOTES:**
1. Manholes deeper than 10'-0" require special design and other detailing
 2. See sheet D-26 for "Channelizing Details for Drain Manhole"

CONCRETE WALL DRAIN MANHOLE
SCALE: 1/2" = 1'-0"

D-20


STANDARD
DETAILS

CONCRETE WALL DRAIN MANHOLE

SEPTEMBER 1984

SCALE: 1/2" = 1'-0"

COUNTY OF KAUAI
 CITY & COUNTY OF HONOLULU
 COUNTY OF MAUI
 COUNTY OF HAWAII



Type "A" Rungs 16" o.c.
Rungs shall not be installed over a pipe connection and the lowest rung shall be not more than 2'-0" above the invert

1" Cement Plaster

Pay line for excavation

2 #4 Horizontal Hoops

#4 Vertical Bars spaced 1/8 of circle

#4 Horizontal Hoops at 8" o.c. (Lap ends 12")

#4 Bars at 12" o.c. bothways

Round opening of outlet pipe. Min. radius = 0.15 pipe diameter

Diam. of Pipe

Diam. of pipe 30" max.

Variable Reint. Conc. Base


- NOTES:**
1. Manholes deeper than 10'-0" require special design and other detailing
 2. See sheet D-26 for "Channelizing Details for Drain Manhole"

BRICK WALL DRAIN MANHOLE

SCALE: 1/2" = 1'-0"

COUNTY OF KAUAI CITY & COUNTY OF HONOLULU COUNTY OF MAUI COUNTY OF HAWAII	BRICK WALL DRAIN MANHOLE SCALE: 1/2" = 1'-0"	STANDARD DETAILS	D-21
--	---	---------------------	------

SEPTEMBER 1984



Adjustment up to 3" permitted with brick or mortar

Type "B" Rungs 16" o.c. (max.) Rungs shall not be installed over a pipe connection and the lowest rung shall be not more than 2'-0" above the invert.

See Detail "A" of detail sheet D-23 Details of Cone Section, Riser Section and joint shall be approved by the Engineer

Pay line for excavation

Mortar around base See Detail "B" of detail sheet D-23

2 #4 Bars

#4 Vertical Bars spaced 1/8" of circle

#4 Horizontal Hoops at 8" o.c. (Lap ends 12")

Reinforced concrete base shall be cast in place


#4 Bars at 12" o.c. bothways

- NOTES:**
1. Manholes deeper than 10'-0" require special design and other detailing.
 2. See sheet D-26 for "Channelizing Details for Drain Manhole"


PRE-CAST CONCRETE DRAIN MANHOLE

SCALE: 1/2" = 1'-0"

D-22	STANDARD DETAILS	PRE-CAST CONCRETE DRAIN MANHOLE SEPTEMBER 1984	COUNTY OF KAUAI CITY & COUNTY OF HONOLULU COUNTY OF MAUI COUNTY OF HAWAII
------	------------------	---	--




CONE SECTION




RISER SECTION

DETAIL "A"




DETAIL "B"

**PRE-CAST CONCRETE DRAIN
MANHOLE DETAILS**



CONE SECTION



RISER SECTION

ALTERNATE DETAIL "A"

PRE-CAST CONCRETE DRAIN
MANHOLE DETAILS

SCALE: 4 1/2" = 1' - 0"

D-24


STANDARD
DETAILS

PRE-CAST CONCRETE DRAIN
MANHOLE DETAILS

SEPTEMBER 1984


SCALE: 4-1/2" = 1'-0"

COUNTY OF KAUAI
CITY & COUNTY OF HONOLULU
COUNTY OF MAUI
COUNTY OF HAWAII




36" CONE

SCALE: 1/2" = 1'-0"




GRADE RING

SCALE: 1/2" = 1"



RISER

SCALE: 1/2" = 1' - 0"



RISER

SCALE: 1/2" = 1' - 0"

SECTION	A _s /L.F.	TOTAL WT., LB.
48" x 48" Riser	0.15	2,752
48" x 45" Riser	0.15	2,580
48" x 36" Riser	0.15	2,064
48" x 30" Riser	0.15	1,720
48" x 24" Riser	0.15	1,376
48" x 15" Riser	0.15	860
48" x 12" Riser	0.15	688
48" x 24" x 36" Cone	0.16	2,100
22" x 4" Grade Ring	0.12	200
22" x 2 1/2" Grade Ring	0.12	95
48" x 32" Riser	0.15	2,691
48" x 16" Riser	0.15	1,345

NOTES

1. Pre-cast sections shall conform to ASTM C 478 - 61T.
2. Manufacturers may submit to the Engineer for approval, prior to manufacturing, designs other than those shown on this sheet.

COUNTY OF KAUAI
CITY & COUNTY OF HONOLULU
COUNTY OF MAUI
COUNTY OF HAWAII


PRE-CAST CONCRETE DRAIN
MANHOLE DETAILS

STANDARD
DETAILS


D-25

SCALE: 1/2" = 1'-0"

SEPTEMBER 1984




PLAN



SECTION A - A

CHANNELIZING DETAILS FOR DRAIN MANHOLE

SCALE: 1/2" = 1'-0"




NOTES:

1. Rungs shall be 3/4" diameter wrought iron or ASTM A36 steel rods and shall be hot-dipped galvanized or cadmium plated after bending.

SECTION


2. Any deviation from these details must be approved by the Chief Engineer.

TYPE	WALLS	L ₁	L ₂
Type A	Brick	13 1/8"	7 5/8"
Type B	Concrete	9"	4 1/4"
Type C	Precast	7 3/4"	3"



* 3" for one rung at top of opening.


SECTION A-A



PLAN

NOTE:

This frame is the same as sewer manhole frame Type "SA".



SECTION A-A

TYPE "DA" FRAME
FOR CATCH BASIN AND MANHOLE

D-28


STANDARD
 DETAILS

TYPE "DA" FRAME
 FOR CATCH BASIN AND MANHOLE

SEPTEMBER 1984

SCALE: 1-1/2" = 1'-0"


COUNTY OF KAUAI
 CITY & COUNTY OF HONOLULU
 COUNTY OF MAUI
 COUNTY OF HAWAII



PLAN

NOTE:

This frame is the same as sewer manhole frame Type "SD".




SECTION A - A

TYPE "DB" FRAME
FOR CATCH BASIN AND MANHOLE


COUNTY OF KAUAI CITY & COUNTY OF HONOLULU COUNTY OF MAUI COUNTY OF HAWAII	TYPE "DB" FRAME FOR CATCH BASIN AND MANHOLE SCALE: 1-1/2" = 1'-0" SEPTEMBER 1984	STANDARD DETAILS	D-29
--	---	---------------------	------

1" Diameter hole


Cast Iron



PLAN



SECTION A - A



BOTTOM VIEW OF COVER

CATCH BASIN AND MANHOLE COVER

D-30


STANDARD
DETAILS

CATCH BASIN AND MANHOLE COVER

SEPTEMBER 1984

SCALE: 1-1/2" = 1'-0"

COUNTY OF KAUAI
CITY & COUNTY OF HONOLULU
COUNTY OF MAUI
COUNTY OF HAWAII



NOTES:

1. Restore pavement to match existing pavement.
2. Minimum thickness of pavement:
A.C. Pavement = 2"
Base Course = 6"
3. Excavation for extra 6" width of repaving to be included with trench excavation.

ELEVATION

SCALE: 3/4" = 1'-0"

DRAIN PIPE SIZE	PAYMENT WIDTH OF TRENCHING	WIDTH OF REPAVING
18"	36"	48"
24"	48"	60"
30"	56"	68"
36"	64"	76"
42"	72"	84"
48"	80"	92"
54"	88"	100"
60"	96"	108"

PAYMENT TRENCH WIDTH AND REPAVING FOR DRAIN PIPES

D-32


STANDARD
DETAILS

SEPTEMBER 1984

SIDEWALK CULVERT

SCALE: AS NOTED





COUNTY OF KAUAI
CITY & COUNTY OF HONOLULU
COUNTY OF MAUI
COUNTY OF HAWAII




NOTE:

All steel parts to be galvanized.

Drill and tap for 3/8" F.H. brass screw at 2'-0" o.c.





SIDEWALK CULVERT



NOTE:
 Culvert size to be determined by Engineer. Box culvert minimum inside dimensions 16" deep x 24" wide. All form material to be removed upon completion of construction.

SECTION




SECTION A-A

A	B
2'	4"
3'	5"
4'	6"
5'	6"


* 4 BAR = 1/2" DIA.
 * 5 BAR = 5/8" DIA.

DETAIL




SEE DETAIL ABOVE FOR
 CULVERT REINFORCEMENT
 REQUIREMENTS.

PLAN



CULVERT SIZE TO BE DETERMINED BY ENGINEER. IS" MIN. INSIDE DIA. FOR CIRCULAR CORRUGATED IRON OR CONCRETE CULVERT.

SECTION



PLAN

D-34


STANDARD
DETAILS

DRIVEWAY DRAINAGE - PIPE CULVERT


COUNTY OF HAWAII

SEPTEMBER 1984

NOT TO SCALE




SECTION




PLAN

COUNTY OF HAWAII	DRIVEWAY DRAINAGE - SWALE NOT TO SCALE	STANDARD DETAILS	D-35 SEPTEMBER 1984
------------------	---	---------------------	------------------------




SECTION B-B
(SHOWING SMALL PIPE)




JOINT DETAIL


H	T
0'-0" OR LESS	6"
0'-1" TO 20'-0"	8"




TYPE G2




ALTERNATIVE REINFORCED BOTTOM




ALTERNATIVE HALF ROUND BOTTOM



STEP DETAIL



SECTION A-A
BOTTOMS NOT REINFORCED



TYPE G1

GENERAL NOTES


- "H" IS THE DIFF. IN ELEV. BETWEEN THE OUTLET PIPE FLOW LINE AND THE NORMAL GUTTER GRADE LINE UNDERPRESSED AT THE CURB FACE.
- FOR "T" WALL THICKNESS, SEE TABLE.
- REINFORCING STEEL IN WALLS SHALL BE #4 BARS @ 18" CENTERS, PLACED 1/2" CLEAR TO INSIDE OF BOX UNLESS OTHERWISE SHOWN.
- STEPS - NONE REQUIRED WHERE "H" IS 3'-6" OR LESS. INSTALL ONE STEP 16"± ABOVE FLOOR WHEN "H" IS MORE THAN 3'-6" AND LESS THAN 5'-0". WHERE "H" IS MORE THAN 5'-0", STEPS SHALL BE EVENLY SPACED @ 12"± INTERVALS FROM 16"± ABOVE FLOOR TO WITHIN 12" OF THE TOP OF THE BOX. PLACE STEPS IN WALL WITHOUT PIPE OPENING.
- DETAILS SHOWN APPLY TO BOTH METAL AND CONCRETE PIPE.
- PIPE(S) CAN BE PLACED IN ANY WALL.
- CURB SECTIONS SHALL MATCH ADJACENT CURB.
- BASIN FLOORS SHALL HAVE WOOD TROWEL FINISH AND A MINIMUM SLOPE OF 12:3 FROM ALL DIRECTIONS TOWARD OUTLET PIPE.
- GALVANIZING - SEE STANDARD SPECIFICATIONS OR SPECIAL PROVISIONS.
- CAST-IN-PLACE OR PRECAST ALTERNATIVE IS OPTIONAL WITH CONTRACTOR.
- SET INLET SO THAT GRATE BARS ARE PARALLEL TO DIRECTION OF PRINCIPAL SURFACE FLOW.
- SEE "STANDARD GRATE DETAIL" FOR GRATE AND FRAME DETAILS.
- USE G1 WHEN H ≤ 4'-0".

TABLE A


H	T
8' - 0" OR LESS	6"
8' - 1" TO 20' - 0"	8"

GENERAL NOTES


- "H" IS THE DIFF. IN ELEV. BETWEEN THE OUTLET PIPE FLOW LINE AND THE NORMAL GUTTER GRADE LINE UNDEPRESSED.
- FOR "T" WALL THICKNESS, SEE TABLE A.
- REINFORCING STEEL IN WALLS SHALL BE #4 BARS @ 18"± CENTERS PLACED 1½" CLEAR TO INSIDE OF BOX UNLESS OTHERWISE SHOWN.
- STEPS - NONE REQUIRED WHERE "H" IS 3'-6" OR LESS. INSTALL ONE STEP "H" ABOVE FLOOR WHEN 16"± IS MORE THAN 3'-6" AND LESS THAN 5'-0". WHERE "H" IS MORE THAN 5'-0", STEPS SHALL BE EVENLY SPACED @ 12"± INTERVALS FROM 16"± ABOVE FLOOR TO WITHIN 12"± OF THE TOP OF THE BOX. PLACE STEPS IN WALL WITHOUT PIPE OPENINGS.
- WHEN SHOWN ON THE PROJECT PLANS, PLACE A #6 PROTECTION BAR HORIZONTALLY ACROSS THE LENGTH OF THE OPENING AND BEND BACK 4" INTO THE INLET WALL ON EACH SIDE.
- PIPE(S) CAN BE PLACED IN ANY WALL.
- BASIN FLOORS SHALL HAVE WOOD TROWEL FINISH AND A MINIMUM SLOPE OF 12:1 FROM ALL DIRECTIONS TOWARDS OUTLET PIPE.
- GALVANIZING - SEE STANDARD SPECIFICATIONS OR SPECIAL PROVISIONS.
- W=2'-11 3/8" FOR ONE GRATE, ADD 3'-5 3/8" FOR ADDITIONAL GRATES IN TANDEM.
- FULL PENETRATION BUTT WELDS MAY BE SUBSTITUTED FOR THE FILLET WELDS ON ALL ANCHORS.
- STANDARD SQUARE, HEXAGON, ROUND OR EQUIVALENT HEADED ANCHORS MAY BE SUBSTITUTED FOR THE RIGHT ANGLE HOOKS ON THE ANCHORS SHOWN ON THIS PLAN.




SECTION C-C




PLAN




SECTION A-A




SECTION B-B




REFER TO TYPES G1, G2 & G3 DRAINAGE INLET NOTES, TABLES, SECTIONS & DETAILS



D-38	STANDARD DETAILS	TYPE G4 DRAINAGE INLET	COUNTY OF KAUAI
	<small>SEPTEMBER 1984</small>	<small>SCALE: 5/8" = 1'-0"</small>	




ON FRAMES FOR TYPES 24-18 GRATES PROVIDE 3-3" X 1" X 3/4" BLOCKS. PLACE ON ROADWAY SIDE OR HIGH SIDE OF GRATE OPENING.




TYPICAL FRAME

WELDED GRATE




SECTION A-A



SECTION B-B


GENERAL NOTES

1. CONTRACTOR HAS THE OPTION OF USING CAST NODULAR IRON, CAST STEEL, WELDED, BOLTED, OR CAST END BLOCK GRATE.
2. GRATES AND FRAMES SHALL BE GALVANIZED.
3. ROUNDED TOP OF BARS OPTIONAL ON ALL GRATES.
4. PIPE DROP INLETS WITH A GRATE SHALL BE PLACED SO THAT BARS PARALLEL DIRECTION OF PRINCIPLE SURFACE FLOW.




1. W = WIDTH OF CATCH BASIN
 2. L = LENGTH OF CATCH BASIN
 3. K = 6'-0" MIN. UNLESS OTHERWISE SPECIFIED
 4. X = 3'-0" MIN. UNLESS OTHERWISE SPECIFIED
 5. IN SUMP CONDITIONS K = X = 6'-0" MIN.
- } NORMAL SECTION

PLAN



SECTION A



SECTION B

D-40


STANDARD
DETAILS

LOCAL DEPRESSION WITHOUT
CURB AND GUTTER


COUNTY OF KAUAI

SEPTEMBER 1984


SCALE: 1/4" = 1'-0"



PLAN



**SECTION Z'-Z''-Z'''
PROJECTED ON Y-Y-Z**



SECTION M-M

TABLE OF VALUES FOR T	
B	T
12"	4"
15"	4 1/4"
18"	4 1/2"
21"	5"
24"	5 1/4"
27"	5 1/2"
30"	6"
33"	6 1/4"
36"	6 1/2"
39"	7"

MINIMUM DEPTH OF TOP AND BOTTOM SLABS SHALL BE $\frac{D}{12} + 2"$

NOTES

- H: VALUES FOR A, B, C, D, E, F, G, L, ELEV. R AND ELEV. S SHOWN ON IMPROVEMENT PLAN. PIPE SHALL BE CRADLED IN CLASS A CONCRETE EXTENDING LONGITUDINALLY TO POINT 1 FT. BEYOND THE LIMITS OF L. H = 1/2 OUTSIDE DIA. OF PIPE + 3" AS A MIN. CRADLE MAY BE OMITTED ON SIDE OPPOSITE LATERAL INLET WHEN CONSTRUCTED IN CONNECTION WITH EXISTING PIPE STORM DRAIN.
- J: A AND B BARS SHALL BE CARRIED TO POINT NOT LESS THAN J DIST. FROM $e = 7D/12 + 6"$.
- L: RECTANGULAR OPENING IN MAIN LINE PIPE SHALL BE CUT IN WITHIN THESE LIMITS NORMAL TO PIPE SURFACE WITHOUT DAMAGING STEEL. VALUES FOR F, G, AND L ON IMPROVEMENT PLAN.
- P: TRANSVERSE REINFORCEMENT IN PIPE SHALL BE CUT IN CENTER OF OPENING AND BENT TO UNIFORM DISTANCE FROM TOP AND BOTTOM OF JUNCTION STRUCTURE.
- T: TABLE OF VALUES FOR T SHOWN ON THIS PLAN.
- 1. OPTIONAL CONSTRUCTION: WHEN JUNCTION STRUCTURE B IS SPECIFIED ON IMPROVEMENT PLAN, THE CONTRACTOR SHALL HAVE THE OPTION OF CONSTRUCTING JUNCTION C, IN WHICH CASE CONSTRUCTION DATA WILL BE FURNISHED BY THE ENGINEER.
- 2. CONCRETE SHALL BE CLASS A.
- 3. REINFORCING STEEL SHALL BE ROUND, DEFORMED, STRAIGHT BARS 1 1/2" CLEAR FROM FACE OF CONCRETE UNLESS OTHERWISE SHOWN.
- 4. STEEL SCHEDULE: A & B BARS - #5 @ 3" O.C.
F BARS - #4 @ 6" O.C.
- 5. MONOLITHIC ARCH: WHEN JUNCTION STRUCTURE B IS SPECIFIED WITH REINFORCED MONOLITHIC ARCH STORM DRAIN, VALUE D SHALL REFER TO THE CLEAR SPAN OF ARCH, REINFORCING STEEL SHALL BE CUT AND BENT INTO JUNCTION STRUCTURE THE SAME AS FOR PIPE. CONCRETE CRADLE UNDER REINFORCED MONOLITHIC ARCH IS NOT REQUIRED.
- 6. FLOOR OF STRUCTURE SHALL BE STEEL-TROWELED TO SPRING LINE.
- 7. ELEVATION S APPLIES AT CENTER OF MAIN LINE ON PROLOGATION OF INVERT OF SPUR.

COUNTY OF KAUAI
COUNTY OF MAUI
COUNTY OF HAWAII

JUNCTION STRUCTURE B


STANDARD
DETAILS

D-41


SCALE: 1/4" = 1'-0"

SEPTEMBER 1984

DIAM. B OR D2	A OR B-BARS	C OR F-BARS
12" TO 39"	#5 @ 3"	#4 @ 6"
42" TO 84"	#6 @ 3"	#5 @ 6"




PLAN



SECTION G-G

TABLE OF VALUES FOR F AND T

D2	F	B	T
12"	4"	12"	4"
15"	4 1/4"	15"	4 1/4"
18"	4 1/2"	18"	4 1/2"
21"	5"	21"	5"
24"	5 1/4"	24"	5 1/4"
27"	5 1/2"	27"	5 1/2"
30"	6"	30"	6"
33"	6 1/4"	33"	6 1/4"
36"	6 1/2"	36"	6 1/2"
39"	7"	39"	7"
42"	7 1/2"	42"	7 1/2"
45"	7 3/4"	45"	7 3/4"
48"	8"	48"	8"
51"	8 1/2"	51"	8 1/2"
54"	9"	54"	9"
57"	9 1/4"	57"	9 1/4"
60"	9 1/2"	60"	9 1/2"
63"	10"	63"	10"
66"	10 1/4"	66"	10 1/4"
69"	10 3/4"	69"	10 3/4"
72"	11"	72"	11"
78"	11 3/4"		
84"	12 1/2"		
90"	13 1/4"		
96"	14"		



**SECTION N'-N''-N'''
PROJECTED ON M-M-N**

NOTES

- VALUES FOR A, B, C, D₁, D₂, E, L, ELEV. R AND ELEV. S ARE SHOWN ON IMPROVEMENT PLAN TABLE OF VALUES FOR F AND T SHOWN ON THIS PLAN.
- OPTIONAL CONSTRUCTION: WHEN JUNCTION STRUCTURE B IS SPECIFIED ON IMPROVEMENT PLAN, THE CONTRACTOR SHALL HAVE THE OPTION OF CONSTRUCTING JUNCTION STRUCTURE C, IN WHICH CASE CONSTRUCTION DATA WILL BE FURNISHED BY THE ENGINEER.
- CONCRETE SHALL BE CLASS A.
- FLOOR OF STRUCTURE SHALL BE STEEL-TROWELED TO SPRING LINE.
- REINFORCING STEEL SHALL BE ROUND, DEFORMED, STRAIGHT BARS, 1/2" CLEAR FROM FACE OF CONCRETE UNLESS OTHERWISE SHOWN. TIE BARS SHALL BE 3/8" ϕ AND SPACED 18" O.C. OR CLOSER. A AND B BARS NEED NOT BE LONGER THAN THE OUTSIDE DIAGONAL WIDTH OF LATERAL SPUR.
- STEEL SCHEDULE DETAILED ON IMPROVEMENT PLAN.
- ELEVATION S APPLIES AT CENTER OF MAIN LINE ON PROLONGATION OF INVERT OF SPUR.
- JUNCTION STRUCTURE SHALL BE POURED IN ONE CONTINUOUS OPERATION, EXCEPT THAT THE CONTRACTOR SHALL HAVE THE OPTION OF PLACING AT THE SPRING LINE A CONSTRUCTION JOINT WITH A LONGITUDINAL KEYWAY.
- LENGTH L SHOWN ON IMPROVEMENT PLAN.
- STATIONS OF MANHOLES SHOWN ON IMPROVEMENT PLAN APPLY AT INTERSECTION OF MAIN LINE AND SPUR. ELEV. SHOWN AT THIS POINT REFER TO PROLONGED INVERT GRADE LINES, EXCEPT THAT WHEN INTERSECTION OF CENTER LINES FALLS OUTSIDE OF STRUCTURE, THE ELEV. ARE SHOWN AND APPLY AT EXTREME LOWER END OF THE STRUCTURE.
- LATERALS - WHERE LATERALS ENTER ON BOTH SIDES OF STRUCTURE, THEY SHALL BE DESIGNATED ON THE IMPROVEMENT PLAN AS RIGHT OR LEFT, FACING IN THE DIRECTION OF STATIONING.






TABLE OF VALUES FOR T

B	T
12"	4"
15"	4 1/4"
18"	4 1/2"
21"	5"
24"	5 1/4"
27"	5 1/2"
30"	6"
33"	6 1/4"
36"	6 1/2"
39"	7"
42"	7 1/2"
45"	7 3/4"
48"	8"
51"	8 1/2"
54"	9"
57"	9 1/4"
60"	9 1/2"
63"	10"
66"	10 1/4"
69"	10 3/4"
72"	11"



SECTION N-M-P'-O
PROJECTED ON P-P'-O

NOTES

- VALUES FOR A, B, L, L₁, ELEVATION R AND ELEVATION S ARE SHOWN ON IMPROVEMENT PLAN. TABLE OF VALUES FOR T SHOWN ON THIS PLAN.
- STATIONS SPECIFIED ON IMPROVEMENT PLAN APPLY AT INTERSECTION OF CENTER LINES OF MAIN LINE AND LATERAL, EXCEPT THAT STATIONS FOR CATCH BASIN CONNECTIONS APPLY AT INSIDE WALL OF STRUCTURE.
- CONCRETE SHALL BE CLASS A EXCEPT AS OTHERWISE NOTED.
- REINFORCING STEEL SHALL BE ROUND, DEFORMED, STRAIGHT BARS 1/2" CLEAR FROM FACE OF CONCRETE UNLESS OTHERWISE SHOWN.
W BARS ARE OF SIZE AND SPACING SPECIFIED FOR WALL STEEL ON IMPROVEMENT PLAN, AND SHALL BE CUT IN CENTER OF OPENING AND BENT INTO TOP AND BOTTOM OF JUNCTION STRUCTURE.
OMIT H BARS WHEN SOFFIT OF SPUR IS 1 FT. OR LESS BELOW SOFFIT OF MAIN LINE, AND OMIT G BARS WHEN INVERT OF SPUR IS 1 FT. OR LESS ABOVE FLOOR OF MAIN LINE.
OMIT ALL STEEL EXCEPT F BARS AND TIE BARS WHEN JUNCTION STRUCTURE IS SPECIFIED WITH MANHOLE, UNLESS OTHERWISE SHOWN ON IMPROVEMENT PLAN.
STEEL SCHEDULE DETAILED ON IMPROVEMENT PLAN.
- JUNCTION STRUCTURE SHALL BE POURED MONOLITHIC WITH MAIN LINE STORM DRAIN OR MANHOLE.
- FLOOR OF STRUCTURE SHALL BE STEEL-TROWELED TO SPRING LINE.

COUNTY OF KAUAI
COUNTY OF MAUI
COUNTY OF HAWAII

JUNCTION STRUCTURE D

STANDARD
DETAILS

D-43

NOT TO SCALE

SEPTEMBER 1984

"C" BARS-2 ABOVE AND 2 BELOW OPENING

VARIABLE TO MEET END OF PIPE

12" MIN.

ROUND PER NOTE 2


12" MIN.

"C" BARS-2 ABOVE AND 2 BELOW OPENING

MINIMUM OF 4-#4 TIES ABOVE AND 4-#4 TIES BELOW OPENING AND ON SIDES. MAXIMUM SPACING 18."

#4 @ 12"
"A" BARS

PLAN OF CORNER CONNECTION



SECTION A-A

D	T	"A"	"B"- "C"
12"	4-1/2"	#4 @ 12"	#5
15"	4-1/2"		
18"	5"		
21"	5-1/2"		
24"	6"		
27"	6-1/2"		
30"	7"		
33"	7"		
36"	7-1/2"		
39"	8"		
42"	8"		
45"	8"		
48"	8"		
51"	8"		
54"	8"		
57"	10"		
60"	10"		
63"	10"		
66"	11"		
69"	11"		
72"	11"		

12" MIN. 12" MIN.

VARIABLE TO MEET END OF PIPE

"B" BARS-2 ABOVE AND 2 BELOW OPENING

ROUND PER NOTE 2

#4 @ 12"

MINIMUM OF 4-#4 TIES ABOVE AND 4-#4 TIES BELOW OPENING AND ON SIDES. MAXIMUM SPACING 18."

PLAN OF SIDE CONNECTION

NOTES

1. ROUND EDGE OF OUTLET 3" RADIUS.
2. REINFORCEMENT SHALL BE 1 1/2" INCHES CLEAR FROM THE FACE OF CONCRETE.
3. IN CONNECTING TO AN EXISTING STRUCTURE BREAK OUT PORTIONS OF THE EXISTING STRUCTURE 6 INCHES OUTSIDE ITS INTERSECTION WITH THE NEW CONNECTION. BEND ENDS OF #4 BARS OVER CONNECTION OPENING AS REQUIRED.

D-44


STANDARD DETAILS

MONOLITHIC CATCH BASIN CONNECTION FOR PIPES 12" TO 72"

SEPTEMBER 1984

NOT TO SCALE

COUNTY OF KAUAI
COUNTY OF MAUI
COUNTY OF HAWAII



SECTION A-A

D	L	T
12"	1.0'	4"
18"	1.0'	5"
24"	1.0'	6"
36"	1.5'	8"
48"	1.5'	10"
54"	1.5'	10"
60"	1.75'	11"
66"	1.75'	11"
72"	2.0'	12"

NOTES

1. WHERE PIPES OF DIFFERENT DIAMETERS ARE JOINED WITH A CONCRETE COLLAR, L AND T SHALL BE THOSE OF THE LARGER PIPE $D = D_1$ OR D_2 WHICHEVER IS GREATER.
2. FOR PIPES SIZE NOT LISTED USE NEXT LARGER SIZE.
3. OMIT REINFORCING ON PIPES 24" AND LESS IN DIAMETER AND ON ALL PIPES WHERE ANGLE A IS LESS THAN 10°.
4. JOIN PIPES AT INVERTS.
5. REINFORCEMENT SHALL BE PLACED 1/2" CLEAR FROM OUTSIDE DIAMETER OF PIPE.

COUNTY OF KAUAI
 COUNTY OF MAUI
 COUNTY OF HAWAII

CONCRETE COLLAR DETAILS

STANDARD
 DETAILS

D-45


NOT TO SCALE

SEPTEMBER 1984

SPAN	2'		3'		4'		5'		6'		7'	
	HEIGHT	HEIGHT	HEIGHT	HEIGHT	HEIGHT	HEIGHT	HEIGHT	HEIGHT	HEIGHT	HEIGHT	HEIGHT	
STRENGTH CLASSIFICATION	2	2	3	3	4	4	5	5	6	6	7	7
MAX FILL OVER TOP	10	10	10	10	10	10	10	10	10	10	10	10
Top Slope	1:1	1:1	1:1	1:1	1:1	1:1	1:1	1:1	1:1	1:1	1:1	1:1
Bottom Slope	1:1	1:1	1:1	1:1	1:1	1:1	1:1	1:1	1:1	1:1	1:1	1:1
Side Slope	1:1	1:1	1:1	1:1	1:1	1:1	1:1	1:1	1:1	1:1	1:1	1:1
Size Bar	3/8"	3/8"	3/8"	3/8"	3/8"	3/8"	3/8"	3/8"	3/8"	3/8"	3/8"	3/8"
Spacing	12"	12"	12"	12"	12"	12"	12"	12"	12"	12"	12"	12"
Length	10'	10'	10'	10'	10'	10'	10'	10'	10'	10'	10'	10'
Concrete CY per lin ft	1.7	1.7	1.7	1.7	1.7	1.7	1.7	1.7	1.7	1.7	1.7	1.7
Rebar lbs per lin ft	17	17	17	17	17	17	17	17	17	17	17	17
Area	4	4	4	4	4	4	4	4	4	4	4	4
Hydraulic Radius	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5
Neutral Slope	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5
Head Factor	1	1	1	1	1	1	1	1	1	1	1	1
Entrance Capacity	11	11	11	11	11	11	11	11	11	11	11	11
Design Discharge	10	10	10	10	10	10	10	10	10	10	10	10

Note
For boxes of height less than that shown in table, use next greater table height. Specify wall dimensions and reinforcing steel, and make necessary changes in bar lengths, number of spacers and quantities.

SPAN	3'		4'		5'		6'		7'		8'		10'		12'	
	HEIGHT	HEIGHT	HEIGHT	HEIGHT	HEIGHT	HEIGHT	HEIGHT	HEIGHT	HEIGHT	HEIGHT	HEIGHT	HEIGHT	HEIGHT	HEIGHT	HEIGHT	
STRENGTH CLASSIFICATION	4	4	5	5	6	6	7	7	8	8	9	9	10	10	12	12
MAX FILL OVER TOP	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10
Top Slope	1:1	1:1	1:1	1:1	1:1	1:1	1:1	1:1	1:1	1:1	1:1	1:1	1:1	1:1	1:1	1:1
Bottom Slope	1:1	1:1	1:1	1:1	1:1	1:1	1:1	1:1	1:1	1:1	1:1	1:1	1:1	1:1	1:1	1:1
Side Slope	1:1	1:1	1:1	1:1	1:1	1:1	1:1	1:1	1:1	1:1	1:1	1:1	1:1	1:1	1:1	1:1
Size Bar	3/8"	3/8"	3/8"	3/8"	3/8"	3/8"	3/8"	3/8"	3/8"	3/8"	3/8"	3/8"	3/8"	3/8"	3/8"	3/8"
Spacing	12"	12"	12"	12"	12"	12"	12"	12"	12"	12"	12"	12"	12"	12"	12"	12"
Length	10'	10'	10'	10'	10'	10'	10'	10'	10'	10'	10'	10'	10'	10'	10'	10'
Concrete CY per lin ft	1.7	1.7	1.7	1.7	1.7	1.7	1.7	1.7	1.7	1.7	1.7	1.7	1.7	1.7	1.7	1.7
Rebar lbs per lin ft	17	17	17	17	17	17	17	17	17	17	17	17	17	17	17	17
Area	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4	4
Hydraulic Radius	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5
Neutral Slope	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5	0.5
Head Factor	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1	1
Entrance Capacity	11	11	11	11	11	11	11	11	11	11	11	11	11	11	11	11
Design Discharge	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10	10




SINGLE BOX CULVERTS

SPAN HEIGHT		2'				3'				4'				5'				6'				7'				8'			
STRENGTH CLASSIFICATION BASE FILL OVER TOP		A	B	C	D	A	B	C	D	A	B	C	D	A	B	C	D	A	B	C	D	A	B	C	D	A	B	C	D
Concrete	CY per lin. ft.	0.11	0.12	0.13	0.14	0.15	0.16	0.17	0.18	0.19	0.20	0.21	0.22	0.23	0.24	0.25	0.26	0.27	0.28	0.29	0.30	0.31	0.32	0.33	0.34	0.35	0.36	0.37	0.38
Steel	lbs. per lin. ft.	110	115	120	125	130	135	140	145	150	155	160	165	170	175	180	185	190	195	200	205	210	215	220	225	230	235	240	245
Hydraulic Radius	R	0.84	0.82	0.80	0.78	0.76	0.74	0.72	0.70	0.68	0.66	0.64	0.62	0.60	0.58	0.56	0.54	0.52	0.50	0.48	0.46	0.44	0.42	0.40	0.38	0.36	0.34	0.32	0.30
Channel Slope	S	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04
Channel Factor	K	1.49	1.49	1.49	1.49	1.49	1.49	1.49	1.49	1.49	1.49	1.49	1.49	1.49	1.49	1.49	1.49	1.49	1.49	1.49	1.49	1.49	1.49	1.49	1.49	1.49	1.49	1.49	1.49
Entrance Capacity	cu ft.	110	115	120	125	130	135	140	145	150	155	160	165	170	175	180	185	190	195	200	205	210	215	220	225	230	235	240	245
Design Discharge	cfs	110	115	120	125	130	135	140	145	150	155	160	165	170	175	180	185	190	195	200	205	210	215	220	225	230	235	240	245

SPAN HEIGHT		5'				6'				7'				8'				9'				10'				12'			
STRENGTH CLASSIFICATION BASE FILL OVER TOP		A	B	C	D	A	B	C	D	A	B	C	D	A	B	C	D	A	B	C	D	A	B	C	D	A	B	C	D
Concrete	CY per lin. ft.	0.27	0.28	0.29	0.30	0.31	0.32	0.33	0.34	0.35	0.36	0.37	0.38	0.39	0.40	0.41	0.42	0.43	0.44	0.45	0.46	0.47	0.48	0.49	0.50	0.51	0.52	0.53	0.54
Steel	lbs. per lin. ft.	210	215	220	225	230	235	240	245	250	255	260	265	270	275	280	285	290	295	300	305	310	315	320	325	330	335	340	345
Hydraulic Radius	R	0.44	0.43	0.42	0.41	0.40	0.39	0.38	0.37	0.36	0.35	0.34	0.33	0.32	0.31	0.30	0.29	0.28	0.27	0.26	0.25	0.24	0.23	0.22	0.21	0.20	0.19	0.18	0.17
Channel Slope	S	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04	0.04
Channel Factor	K	1.49	1.49	1.49	1.49	1.49	1.49	1.49	1.49	1.49	1.49	1.49	1.49	1.49	1.49	1.49	1.49	1.49	1.49	1.49	1.49	1.49	1.49	1.49	1.49	1.49	1.49	1.49	1.49
Entrance Capacity	cu ft.	210	215	220	225	230	235	240	245	250	255	260	265	270	275	280	285	290	295	300	305	310	315	320	325	330	335	340	345
Design Discharge	cfs	210	215	220	225	230	235	240	245	250	255	260	265	270	275	280	285	290	295	300	305	310	315	320	325	330	335	340	345

For culverts at grade, extend
"C" bars full length, top slab
only, provide additional spacers
@18" and adjust quantities



TYPICAL SECTION
(Showing reinforcement for interior walls 8" and over)

STANDARD
DETAILS

SEPTEMBER 1984

TRIPLE BOX CULVERTS

NOT TO SCALE


COUNTY OF KAUAI
COUNTY OF MAUI
COUNTY OF HAWAII

SPAN HEIGHT	2'		3'		4'		5'		6'		7'		8'	
	2'	3'	3'	4'	4'	5'	5'	6'	6'	7'	7'	8'	8'	
STRENGTH CLASSIFICATION BASED UPON TOP	[Grid of numbers]													
Design Load	[Grid of numbers]													
Design Pressure	[Grid of numbers]													
Design Factor	[Grid of numbers]													
Design Capacity	[Grid of numbers]													
Design Overload	[Grid of numbers]													


SPAN HEIGHT	10'				12'			
	10'	10'	12'	12'	12'	12'	12'	12'
STRENGTH CLASSIFICATION BASED UPON TOP	[Grid of numbers]							
Design Load	[Grid of numbers]							
Design Pressure	[Grid of numbers]							
Design Factor	[Grid of numbers]							
Design Capacity	[Grid of numbers]							
Design Overload	[Grid of numbers]							

For culverts at grade, extend
"bars full length, provide
additional spacers @ 18" and
adjust quantities


Provide paving match for
culverts at grade where PCC
approach paving is used




TRIPLE BOX CULVERTS




PLAN
TRANSITION TO RECTANGULAR STORM DRAIN



SECTION A-A



PROFILE




SECTION B-B

H	TRANSITION REINFORCEMENT	H.W. REINFORCEMENT
0' - 4"	#4 @ 12" BOTH WAYS CENTERED	#4 @ 18"
OVER 4' - 6"	"A" BARS #5 @ 24" "B" BARS #5 @ 24"	#4 @ 18"
OVER 6' - 6"	"A" BARS #5 @ 12" "B" BARS #5 @ 12"	#5 @ 12"


NOTES

1. PROVIDE A CONSTRUCTION JOINT BETWEEN THE TRANSITION AND THE STORM DRAIN.
2. EXTEND THE LONGITUDINAL REINFORCING STEEL OF THE TRANSITION 2' INTO THE CHANNEL.
3. IN LIEU OF PLACING THE DOWELS BETWEEN THE TRANSITION AND THE RECTANGULAR STORM DRAIN THE LONGITUDINAL REINFORCING STEEL OF THE STORM DRAIN MAY BE EXTENDED 2' INTO THE TRANSITION STRUCTURE.




PLAN


TRANSITION TO CIRCULAR STORM DRAIN



SECTION A-A



PROFILE




SECTION B-B


NOTE

SEE RECTANGULAR TRANSITION FOR GENERAL NOTES & STEEL TABLE

D-50	STANDARD DETAILS	CIRCULAR TRANSITION	COUNTY OF KAUAI COUNTY OF MAUI COUNTY OF HAWAII
		SEPTEMBER 1984	NOT TO SCALE




PARTIAL SECTION




PARTIAL PLAN - SKEWED

PARAPET DETAILS FOR SINGLE SPAN CULVERTS



PARTIAL SECTION




PARTIAL PLAN - SKEWED

PARAPET DETAILS FOR MULTIPLE SPAN CULVERTS


PARAPET "1" BAR NOS.			
SPAN \ SKEW ANGLE	0°	16°	31°
	TO	TO	TO
	15°	30°	45°
3'	#4	#4	#5
4'	#4	#5	#6
5'	#5	#6	#7
6'	#6	#8	#8
8'	#8	#9	#9
10'	#9	#10	#10
12'	#10	#10	#10

"d" BARS SHALL BE AS NOTED IN THE SINGLE, DOUBLE AND TRIPLE BOX CULVERT DETAILS.

CASE - 1
REINFORCED CONCRETE BEAM



CASE - 2
CONCRETE SUPPORT WALL




DIMENSIONS OF REINFORCED CONCRETE BEAMS:

TRENCH WIDTH	DEPTH OF BEAM	BAR SIZE	BEAM LENGTH
4'-0" or 10"	8"	3/8" ϕ	7'-0"
4'-6"	9"	3/4" ϕ	7'-6"
5'-0"	9-1/2"	3/4" ϕ	8'-0"
6'-0"	10-1/2"	3/4" ϕ	9'-0"
7'-0"	12"	7/8" ϕ	10'-0"
8'-0"	13"	7/8" ϕ	11'-0"

1. WIDTH OF BEAMS SHALL BE NOMINAL DIAMETER OF PIPE PLUS 2".
2. LENGTH OF BEAMS SHALL BE THE WIDTH OF TRENCH PLUS 3'-0".
3. REINFORCING STEEL SHALL BE PLACED 1-1/2" CLEAR FROM THE SIDE AND BOTTOM OF BEAMS.
4. IF BEAMS ARE PRECAST, 18" AT ENDS OF BEAMS SHALL BE BEDDED IN CLASS "B" CONCRETE.
5. CLASS "B" MORTAR SHALL BE PLACED BETWEEN TOP OF BEAMS AND BOTTOM OF PIPE TO GIVE BEARING.

1. SUPPORTING WALL SHALL HAVE A FIRM BEARING ON THE SUBGRADE AND AGAINST THE SIDES OF THE EXCAVATION.
2. WALL SHALL BE AT LEAST 2-INCHES FREE AND CLEAR OF ANY GAS OR WATER OR OTHER CONDUIT OR DUCT.
3. EITHER TYPE "A" OR TYPE "B" CROSS SECTION MAY BE USED AT THE CONTRACTOR'S OPTION.
4. WHENEVER SO DIRECTED BY THE ENGINEER, THE CONTRACTOR SHALL PIERCE THE WALL WITH SUITABLE OPENINGS TO PREVENT UNEQUAL PRESSURE RESULTING FROM FLOODING THE BACKFILL. THE VOLUME OF THE PIERCED OPENINGS SHALL NOT EXCEED 1/2 THE VOLUME OF THE SUPPORTING WALL.

CASE - 3
CAST IRON PIPE




INSIDE OF CAST IRON PIPE:

INSIDE DIAMETER	CLASS 150 PIPE			CLASS 200 PIPE		
	6"	8"	10"	6"	8"	10"
MAXIMUM TRENCH WD.	4'-6"	5'-6"	7'-0"	5'-0"	6'-0"	8'-0"


NOTE: PIPE SHALL BE BEDDED IN 18" OF CONCRETE BEYOND EDGE OF TRENCH.

CASE - 4
SPUN REINFORCED CONCRETE PIPE
STORM DRAINS ONLY



1. CLASS 2000-D SPUN REINFORCED CONCRETE PIPE OF THE SAME DIAMETER AS STORM DRAIN MAY BE USED FOR STORM DRAINS ONLY WHERE WIDTH OF TRENCH IS 5'-0" OR LESS.
2. BEARINGS OF THE PIPE ENDS AND JOINT CLOSURE SHALL BE THE SAME AS FOR CASE 3.

METHODS OF SUPPORTING STORM DRAIN AND SEWER PIPES ACROSS TRENCHES




PLAN

OPENING WITHIN SIDEWALK
SCALE: 1/2" = 1'-0"


NOTE

1. Reinf. bars not required where $\left. \begin{matrix} a_1 \\ a_2 \\ a_3 \end{matrix} \right\} > 2'-0''$




OPTIONAL BAR DETAIL

SCALE: 1/2" = 1'-0"



PLAN

OPENING AT EDGE OF SIDEWALK
SCALE: 1/2" = 1'-0"




TYPICAL SECTION

SCALE: 1 1/2" = 1'-0"

SIDEWALK REINFORCEMENT DETAILS
AT UTILITY BOXES OR OPENINGS

Search by Address or TMK



TMK_state: 141030053

TMK: 141030053
Real Property: [More info](#)
Acres: 0.33

[Zoom to](#) ...

100ft
-157.695 21.326 Degrees