

STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION
AIRPORTS

ADDENDUM NO. 2
FOR
FURNISHING AND DELIVERY OF
ONE (1) MULTI-PURPOSE STRUCTURAL FIRE FIGHTING VEHICLE
AT KAHULUI AIRPORT,
KAHULUI, MAUI, HAWAII
AND
ONE (1) MULTI-PURPOSE STRUCTURAL
FIRE FIGHTING VEHICLE AT
DANIEL K. INOUE INTERNATIONAL AIRPORT,
HONOLULU, OAHU, HAWAII
PROJECT NO. FS1219-26

May 15, 2026

The following is provided for information.

A. RESPONSES TO REQUESTS FOR INFORMATION (RFI'S/QUESTIONS)

1. The attached **RESPONSES TO REQUEST FOR INFORMATION** are provided for information.

Please acknowledge receipt of this **ADDENDUM NO. 2** by recording the date of its receipt in the space provided on **PAGE PF-4** of the Proposal.



CURT T. OTAGURO
Deputy Director of Transportation for Airports

**Questions for solicitation: B26002508 FS1219-26 Furnishing & Delivery of
Multi-Purpose Structural Fire Fighting
05/15/2026**

1. Vendor would like to request a 2 week extension, please advise as soon as possible.

Please refer to Addendum No. 1, released on May 12, 2026.

2. Would the State of Hawaii be willing to extend the deadline for questions and the offer due date by two weeks? A two-week extension would allow vendors adequate time to evaluate specifications, submit questions if needed, review any responses or addenda issued, and submit their most responsive bid.

No, please bid accordingly.

3. Section 10 General Specification Page 11-4, Wheelbase The wheelbase for the vehicle shall be 195.00 Question; Clarification the updated wheelbase with the longer body will be 220.00 is this acceptable?

Not acceptable, please bid accordingly.

4. Section 10 General Specification Page 11-4 GVW Rating The gross vehicle weight rating shall be 46,500. Question; Clarification the updated GVW Rating shall be 53,800, is this acceptable?

Not acceptable, please bid accordingly.

5. Section 10 General Specification Page 11-18 Hose Tray Right Side A hose tray shall be placed in the right side of the extended bumper. The tray shall have a capacity of 25' of 5' double jacket cotton-polyester hose. Question; Clarification is 20' of 5" acceptable due to the size of the compartment?

Not acceptable, please bid accordingly.

6. Section 10 General Specification Page 11-71 Hose Bed Hose bed shall accommodate #1 reverse lay 500', 3" x 2.5" #2 LDH Hose 4", 800'-1000' #3 forward Lay 750' 3' x 2.5" #4 Forward lay 400' 1.75" Question; Based on the current configuration, we have calculated the following hose capacity will fit in the hose bed: 1) 500' of 3.00" DJP Hose 2) 950' of 4.00" DJP Hose 3) 750' of 3.00" DJP Hose 4) 350' of 1.75" DJP Hose

Not acceptable, please bid accordingly.

7. Section 10 General Specification Page 11-79 Rear Compartmentation A roll-up door compartment above the rear tailboard shall be provided. The interior dimensions of this compartment shall be 43.50" high. Question; Clarification, due to the upper ladder compartment will a 35.50" high compartment be acceptable.

Not acceptable, please bid accordingly.

8. Section 10 General Specification Page 11-89 Pike pole provided by fire department One 8' pike pole, Fire Hooks Unlimited, Model RH8, 8' long roof hook, with pry end and steel handle shall be provided and located in the right-side long tool storage. Question, Clarification, the 8' pike pole is not required, this will be removed from the file is this acceptable?

Not acceptable, please bid accordingly.