

SPECIFICATIONS AND PROPOSAL

FOR

HONOLULU HARBOR,

PIER 10

SUBSTRUCTURE REPAIRS

OAHU, HAWAII

JOB S10955

**STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION
HARBORS**

NOTICE TO BIDDERS
Hawaii Revised Statutes (HRS),
Chapter 103D

The receiving of bids for **HONOLULU HARBOR, PIER 10, SUBSTRUCTURE REPAIRS, OAHU, HAWAII, JOB S10955**, will begin as of the HiePRO Release Date.

Bidders shall register and submit complete bids through HiePRO only. Refer to the following HiePRO link for important information on Vendor Registration:

<https://hiepro.ehawaii.gov/welcome.html>.

The solicitation plans, specifications, proposal, and additional documents designated or incorporated by reference shall be available in HiePRO.

HiePRO OFFER DUE DATE & TIME is **June 18, 2026, at 2:00 p.m.**, Hawaii Standard Time (HST). **Bidders shall submit and upload the complete proposal to HiePRO prior to the offer due date and time. Proposals received after said due date and time shall not be considered. Any additional support documents explicitly designated as confidential and/or proprietary shall be uploaded as a separate file to HiePRO. Bidders shall not include confidential and/or proprietary documents as part of their proposal. The record of each bidder and their respective proposal shall be open to public inspection. FAILURE TO UPLOAD THE PROPOSAL TO HiePRO SHALL BE GROUNDS FOR REJECTION.**

The scope of work consists of repairing spalls and delaminations on the substructure at Pier 10 at Honolulu Harbor, Oahu, Hawaii. The estimated cost of construction is between \$5,500,000 to \$6,500,000.

To be eligible for award, bidders shall possess a valid State of Hawaii General Engineering Contractor's "A" license **at the time of bidding.**

The Hawaii Department of Transportation, Air and Water Transportation Facilities Division, 2016 GENERAL PROVISIONS FOR CONSTRUCTION PROJECTS, applicable to this project are available on the internet at: <http://hidot.hawaii.gov/administration/con/>.

A virtual pre-bid conference is scheduled for May 27, 2026, at 10:00 a.m., HST. Interested bidders shall contact Branden Sumida, Project Manager, directly at branden.sumida@hawaii.gov, no later than one (1) working days prior to the scheduled pre-bid conference to receive the meeting invitation. All prospective bidders and/or their respective representatives are encouraged to attend, however, attendance is not mandatory. All information presented at the pre-bid conference shall be provided for clarification and information only. Any amendments to the solicitation shall be made by formal addendum and posted in HlePRO.

All Request for Information (RFI) questions and Substitution Requests shall be submitted in HlePRO **no later than June 1, 2026, at 2:00 p.m., HST.** RFI questions received after the stated deadline shall not be addressed. Substitution Requests received after the stated deadline shall not be considered. Verbal RFI(s) shall not receive a response. All responses to RFI questions shall be provided for clarification and information only and issued by formal addendum. Any amendments to the solicitation shall be made by formal addendum and posted in HlePRO.

If there is a conflict between the solicitation and information stated in the pre-bid conference, the meeting minutes, and/or the responses to RFI questions, the solicitation shall govern and control, unless as amended by formal addendum.

Apprenticeship Preference. A five percent bid adjustment for bidders that are parties to apprenticeship agreements pursuant to HRS § 103-55.6 is applicable to this project.

Employment of State Residents on Construction Procurement Contracts. Compliance with HRS §103B-3 is a requirement for this project whereby a minimum of 80 percent of the bidder's work force on this project **must** consist of Hawaii residents.

Campaign Contributions by State and County Contractors. Contractors are hereby notified of the applicability of HRS § 11-355 which states that campaign contributions are prohibited from specified State or County government contractors during the term of the contract if the contractors are paid with funds appropriated by a legislative body. For more information, contact the Campaign Spending Commission at (808) 586-0285.


Protests. Any protest of this solicitation shall be submitted in writing to the Director of Transportation, in accordance with HRS § 103D-701 and Hawaii Administrative Rules § 3-126.

The Equal Employment Opportunity Regulations of the Secretary of Labor implementing Executive Order 11246, as amended, shall be complied with on this project.

The U.S. Department of Transportation Regulation entitled "Nondiscrimination in Federally Assisted Programs of the U.S. Department of Transportation", Title 49, Code of Federal Regulations (CFR), Part 21, is applicable to this project. Bidders are hereby notified that the Department of Transportation shall affirmatively ensure that the contract entered into pursuant to this advertisement shall be awarded to the lowest responsible bidder without discrimination on the grounds of race, color, national origin, or sex (as directed by 23 CFR, Part 200).

For additional information, contact Branden Sumida, Project Manager, by email at branden.sumida@hawaii.gov.

The State reserves the right to reject any or all proposals and to waive any defects in said proposals in the best interest of the public.



DREANALEE K. KALILI
Deputy Director of Transportation for Harbors

HIePRO RELEASE DATE: May 19, 2026

TABLE OF CONTENTS

| | <u>Page</u> | |
|--|---|-------------|
| Instructions for Contractor’s Licensing | | |
| Special Provisions | SP-1 – SP-4 | |
| Wage Rate Schedule (Not Physically Included in the Bid Documents) | | |
| SPECIFICATIONS | | |
| Part I – GENERAL PROVISIONS for CONSTRUCTION PROJECTS 2016 (Not physically included in the Bid Documents) | | |
| Part II – TECHNICAL PROVISIONS | | |
| Article X | Project Description | 10-1 – 10-8 |
| Article XI | Mobilization and Demobilization | 11-1 – 11-2 |
| Article XII | Temporary Water Pollution, Dust, And Erosion Control | 12-1 – 12-9 |
| Article XIII | Concrete Removal Work | 13-1 – 13-3 |
| Article XIV | Concrete Repair Work | 14-1 – 14-6 |
| Article XV | Epoxy Coating System | 15-1 – 15-3 |
| Article XVI | Project Photographs | 16-1 – 16-2 |
| Requirements of Chapter 104, HRS (eH104-3 dated 5/24) | 1 – 2 | |
| Proposal | P-1 – P-6 | |
| Proposal Schedule | P-7 – P-8 | |
| Surety Bid Bond | | |
| Sample Forms | | |
| Sample Contract | | |
| Performance Bond (Surety) | | |
| Performance Bond | | |
| Labor and Material Payment Bond (Surety) | | |
| Labor and Material Payment Bond | | |
| Chapter 104, HRS Compliance Certificate | | |
| Certification of Compliance for Employment of State Residents, Act 192, SLH 2011 | | |

INSTRUCTIONS FOR CONTRACTOR'S LICENSING

"A" general engineering contractors and "B" general building contractors are reminded that due to the Hawaii Supreme Court's January 28, 2002 decision in Okada Trucking Co., Ltd. v. Board of Water Supply, et al., 97 Haw. 450 (2002), they are prohibited from undertaking any work, solely or as part of a larger project, which would require the general contractor to act as a specialty contractor in any area where the general contractor has no license. Although the "A" and "B" contractor may still bid on and act as the "prime" contractor on an "A" or "B" project (*See, HRS § 444-7 for the definitions of an "A" and "B" project.*), respectively, the "A" and "B" contractor may only perform work in the areas in which they have the appropriate contractor's license (*An "A" or "B" contractor obtains "C" specialty contractor's licenses either on its own, or automatically under HAR § 16-77-32.*). The remaining work must be performed by appropriately licensed entities. It is the sole responsibility of the contractor to review the requirements of this project and determine the appropriate licenses that are required to complete the project.

STATE OF HAWAII

DEPARTMENT OF TRANSPORTATION

HONOLULU, HAWAII

SPECIAL PROVISIONS

SPECIAL PROVISIONS

The General Provision is amended as follows:

A. ARTICLE I - TERMS, ABBREVIATIONS, AND DEFINITIONS

1. Section 1.3 Definitions: The definition for “Subcontractor” is amended by deleting it and replacing it with the following:
“Subcontractor – An individual, partnership, firm, corporation, or joint venture, or other legal entity, as licensed or required to be licensed under Chapter 444, Hawaii Revised Statutes, as amended, which enters into an agreement with the Contractor to perform a portion of the work.”
2. Section 1.3 Definitions: The definition for “Proposal (or Bid)” is amended by deleting it and replacing with the following:
“PROPOSAL (OR BID) - The offer of a Bidder, on the prescribed HDOT form, submitted by the Bidder in response to a solicitation request, to perform the work required by the proposed contract documents, for the price quoted and within the time allotted.”
3. Add the following to Section 1.3 Definitions.
“HAWAII ePROCUREMENT SYSTEM (HIePRO) - The State of Hawaii eProcurement System for issuing solicitations, receiving proposals and responses, and issuing notices of award.”

B. ARTICLE II – STANDARD PROVISIONS FOR COMPETITIVE SEALED BIDS AND AWARDS

1. 2.7 Request for Substitution of Specified Materials and Equipment Before Bid Opening is amended as follows:
 - a. The last sentence in the first paragraph (line 147 to 152) be replaced with the following:
“Where a bidder intends to use a material or equipment of an unspecified brand, make, or model, the bidder must submit a request to the Department for review and approval at the earliest date possible. As specified in the Notice to Bidders, all requests shall be posted as a question in HIePRO under the “Question and Answer” tab. Supporting documents for specific request shall be emailed to the Project Manager specified in the Notice to Bidders. Request must be posted in HIePRO and supporting documents received by the Project Manager no later than seventeen (17) calendar days before the bid opening date.”

- b. The first sentence in the second paragraph (line 154 to 156) shall be replaced with the following:

“It shall be the responsibility of the bidder to submit sufficient evidence based upon which a determination can be made by the Department that the alternate brand is a qualified equivalent.”

2. 2.8 Preparation and Delivery of Bid is amended as follows: Last paragraph (line 189 to 192) shall be replaced with the following:

“Bidders shall submit and upload the complete proposal to HIePRO prior to the bid opening date and time. Proposals received after said due date and time shall not be considered. Any additional support documents explicitly designated as confidential and/or proprietary shall be uploaded as a separate file to HIePRO. Do not include confidential and/or proprietary documents with the proposal. The record of each bidder and respective bid shall be open to public inspection. Original (wet ink, hard copy) proposal documents are not required to be submitted. **Contract award shall be based on evaluation of proposals submitted and uploaded to HIePRO.**

FAILURE TO UPLOAD THE COMPLETE PROPOSAL TO HIePRO SHALL BE GROUNDS FOR REJECTION OF THE BID.

If there is a conflict between the specification document and the HIePRO solicitation, the specifications shall govern and control, unless otherwise specified.”

3. 2.11 Bid Security is amended by deleting (a) and replacing it with:

“(a) Unless directed otherwise in the invitation for bids, each bid shall be accompanied by bid security which is intended to protect the Department against the failure or refusal of a bidder to execute the contract for the work bid or to supply the required performance and payment bonds. Bid security shall be in an amount equal to at least five percent of the base bid and additive alternates. Bid security shall be in one of the following forms:

- (1) A deposit of legal tender;
- (2) A valid surety bid bond, underwritten by a company licensed to issue bonds in the State of Hawaii, in the form and composed, substantially, with the same language as provided herewith and signed by both parties;
or
- (3) A certificate of deposit; credit union share certificate; or cashier’s, treasurer’s, teller’s, or official check drawn by or a certified check accepted by a bank, savings institution, or credit union insured by the Federal Deposit Insurance Corporation (FDIC) or the National Credit

Union Administration (NCUA) and payable at sight or unconditionally assigned to the Department. These instruments may be utilized only to a maximum of one hundred thousand dollars (\$100,000.00). If the required amount totals over one hundred thousand dollars (\$100,000.00), more than one instrument not exceeding one hundred thousand dollars (\$100,000.00) each and issued by different financial institutions shall be accepted.

If bidder elects options (1) or (3) above for its bid security, said bid security shall be in its original form and shall be submitted before the bid deadline to the Contract Office, Department of Transportation, Aliiaimoku Hale, 869 Punchbowl Street, Room 103, Honolulu, Hawaii 96813. Original surety bid bonds do not need to be submitted to the Contracts Office. Bidders are reminded that a copy of its surety bid bond shall be included with its bid submitted and uploaded to HiePRO.”

4. 2.12 Pre-Opening Modification or Withdrawal of Bids is amended by deleting 2.12 Pre-Opening Modification or Withdrawal of Bids in its entirety and replacing it with the following:

“2.12 PRE-OPENING MODIFICATION OF WITHDRAWAL OF BIDS. Bids may be modified or withdrawn prior to the bid opening date and time. Withdrawal or revision of proposal shall be completed and submitted and uploaded to HiePRO prior to the bid opening date and time.”

5. 2.14 Public Opening of Bids is amended by deleting 2.14 Public Opening of Bids in its entirety.
6. 2.20 Bid Evaluation and Award is amended by replacing 2.20(a) and 2.20(b) with the following:

“(a) The award shall be made to the lowest, responsive, responsible bidder within 120 days after bid opening and shall be based on the criteria set forth in the invitation for bids. The Department may request the bidders to allow the Department to consider the bids for the issuance of an award beyond the 120 day period. Agreement to such an extension must be made by a bidder in writing. Only bidders who have agreed to such an extension will be eligible for the award. No response to request shall mean bidder shall no longer be eligible for award.

(b) No bid shall be withdrawn or corrected for a period of 120 days after bid opening except for a mistake as described in this article; however, a bidder may withdraw a bid without penalty anytime prior to award of the contract if it finds it is unable to comply with the provisions regarding the employment of State of Hawaii residents as described in Section 7.2 and 103B-3, H.R.S.”

C. ARTICLE VII – LEGAL RELATIONS AND RESPONSIBILITY TO PUBLIC

1. 7.1 Insurance Requirements is amended by deleting paragraph “(b)(4) Builder’s Risk for All Work” in its entirety.

STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION
HONOLULU, HAWAII

SPECIFICATIONS

PART I

GENERAL PROVISIONS

The Hawaii Department of Transportation AIR and WATER Transportation Facilities Division General Provisions for Construction Projects dated 2016 is not physically included in these specifications. The General Provisions are available at

<http://hidot.hawaii.gov/administration/con/>

STATE OF HAWAII

DEPARTMENT OF TRANSPORTATION

HONOLULU, HAWAII

SPECIFICATIONS

PART II

TECHNICAL PROVISIONS

ARTICLE X - PROJECT DESCRIPTION

10.1 GENERAL - The work to be done under this project includes furnishing of all labor, materials and equipment necessary to repair substructure spalls and delaminations at Pier 10 at Honolulu Harbor, Oahu, Hawaii.

Bidders are advised to examine the existing conditions at the project site to familiarize themselves with the nature and extent of work involved. Appointments may be made with the State Harbors Maintenance Engineer for clarification of the work involved and the character and quality of materials specified.

10.2 SCOPE OF WORK - The work to be done includes, but is not necessarily limited to, the following major items of work:

- A. Mobilization and demobilization.
- B. Providing a detailed site specific Best Management Practices (BMP) Plan.
- C. Repair of spalls and delaminations on the concrete substructure.
- D. Coating of concrete repairs on the pier underside with an epoxy coating.

10.3 CONTRACT DRAWINGS – The location and size of the repair areas shown on the plan are approximate and are included for bidding purposes only. All structures and portions of structures shown on the plan are existing unless specifically noted. Existing conditions shown are based on the best available information. No guarantee is given that they are more than approximately correct.

10.4 WORK SCHEDULE - The work schedule and assignment of storage area(s) shall be discussed and coordinated with the Harbors Oahu District Manager and the Construction Engineer and shall be subject to their written approval. The Contractor shall turn in a work schedule two (2) weeks prior to actual construction for approval by the Harbors Oahu District Manager and the Construction Engineer. The Contractor shall be responsible for maintaining the work and storage areas in neat and orderly condition.

Shipping and dock activities by tenants/users will take precedence over the Contractor's activities. Vessels call at various days of the week. An approximate vessel schedule for the project area can be found at hawaii.portcall.com. The exact scheduling of the work and restrictions on the Contractor's activities will be established at the pre-construction meeting.

Bidders shall assume work shall be performed during the cruise vessel off-season approximately between May and September.

Phasing and careful coordination of the work will be required to allow continuous use of the project location and adjacent areas. The Contractor shall be responsible for coordination with all tenants/users of the area and the Harbors District Operations Staff on a daily basis regarding scheduling of all work at no additional cost to the State.

The Contractor shall phase the work to maintain a travel lane at all times through the project site.

The Contractor shall coordinate its work so as to minimize interference with the pier operations. All work shall be scheduled to minimize interference with any operations in the project area. Weekend and night work may be required.

The exact scheduling and sequencing of the work and restrictions on the Contractor's operation while working at the project site will be established at the pre-construction meeting. The Contractor shall attend the pre-construction meeting to coordinate its work with others and shall complete all work within the work schedule.

10.5 LIABILITY AND RESPONSIBILITY - The Contractor shall provide, erect and maintain warning signs, lights, barricades, fences, watchmen and/or other means as necessary to prevent unauthorized persons from wandering onto the job site where they may suffer injury or create a hazard to the construction operations or the work in progress. The Contractor shall also take all reasonable precautions for safety in its operations and to prevent injury to its employees and to others at the job site.

The Contractor shall be responsible for any and all damages to harbor and adjacent facilities caused by its operations and negligence. The Contractor shall, at its own expense, make prompt restitution for damages to the facilities caused by its operations or negligence. The Contractor shall hold the State harmless from all claims for loss or injury.

The Contractor shall remove defective work and replace the required work at no cost to the State.

The Contractor SHALL verify existing conditions in the field prior to ordering any materials. The existing conditions are based on the best available information. The Contractor shall make no claim for extra compensation should actual existing conditions differ from those shown on the plans.

Hawaii One Call. The Contractor shall comply with the Hawaii One Call law, HRS Section 269E-4. This includes, but is not limited to, coordination with the Hawaii One Call Center (HOCC) for any work involving excavation at least five (5) working days but not more than twenty-eight (28) calendar days prior to commencing excavation. The Contractor shall provide to HOCC a description of the excavation site that may include the county, place, address and measurements as needed. HOCC contact information: telephone 811; website <http://www.digsafelyhawaii.com>.

10.6 BEST MANAGEMENT PRACTICES (BMPs) - The Contractor must follow standard best management practices for air pollution, water pollution, noise and solid waste control, as required by Federal, State and County regulations, to protect the environment from the effects of construction activity, including prohibiting any construction debris or other deleterious materials to fall, flow or otherwise enter harbor waters.

The Contractor shall submit a site specific BMP plan to the Harbors Construction Engineer for review and comment before work begins. The plan shall satisfy the requirements of ARTICLE XII – TEMPORARY WATER POLLUTION, DUST, AND EROSION CONTROL. This plan shall describe and detail the methods and procedures to be used to prevent air and water pollution, including preventing any materials, wastes, and debris from entering any adjacent storm drain system and the harbor to the satisfaction of the Harbors Construction Engineer. The Contractor shall revise the BMP plan – at no additional cost to the State - should it be determined by the Harbors Construction Engineer that the plan is insufficient to prevent pollution.

10.7 PERMITS - The Contractor will require permits for all welding and burning operations. The Contractor shall obtain the required work permit from the Harbors Oahu District Manager.

A Building Permit from City and County of Honolulu will not be required for this project.

10.8 SUBMITTALS - The Contractor shall submit for review one (1) copy of the following items in PDF format.

- A. Best Management Practices (BMP) Plan including removal of hazardous material in accordance with Article XII of these Technical Specifications.
- B. Health and Safety Plan
- C. Pre-Construction Survey.
- D. Concrete Repair Work as required by Article XIII of these specifications.
 - 1. Concrete Mix Design for Repairs
 - 2. Patching Compound for Form and Pour Repairs
 - 3. Patching Compound for Vertical Surface and Underside Repairs
 - 4. Reinforcing Steel
 - 5. Reinforcing Steel Anti-Corrosion Coating
 - 6. Epoxy for Grouting of Dowels
 - 7. Curing Compound

10.9 STANDARD SPECIFICATIONS - The term "Standard Specifications" as used in these Technical Specifications, shall mean the Hawaii Standard Specifications for Road and Bridge Construction, State of Hawaii, Department of Transportation, Highways Division, 2005.

10.10 AS BUILT DRAWINGS - The Contractor shall keep one (1) set of drawings at the job site and make all field changes thereon. After completion of the project, a PDF/A format digital file marked up with all the field changes shall be submitted to the Construction Engineer.

10.11 HARBOR SECURITY - The Contractor shall submit required documentation of all Contractor and subcontractor's employees, their representatives, suppliers, manufacturers, and alike, and of all necessary vehicles needing access to the project site to the Harbors Construction Engineer and Oahu District Manager before starting work on the project. The documentation will include the following:

- A. Authorized personnel's first name, middle initial(s), and last name by company name.
- B. Vehicle(s) license plate number(s) by company name.
- C. The Contractor may be directed to use a specified entrance to enter and exit the harbor. Upon every entry, each employee must present and possess a photo identification (ID) card.
- D. All Contractor's and sub-contractor's employees, their representatives, suppliers, manufacturers, and authorized personnel needing access to the project site shall wear their photo ID card at all times.
- E. Contractor's vehicles must be identified with a company logo and will be subject to search. Any employee's personal belongings will also be subject to search.
- F. If the Contractor wishes to remove any fencing or open any locked gates, they shall coordinate with and request approval from the Harbors Construction Engineer and Oahu District Manager. If approval is granted, the Contractor shall then be responsible for securing open fencing or gate(s) immediately after entering, or posting security personnel to monitor ingress and egress. Inspections of vehicles and equipment moving through the access points will be done in accordance with current MARSEC level and directives.
- G. If security personnel are required, the Contractor shall hire the same contract security that provides service to the State of Hawaii, Department of Transportation, Harbors. In the event that the security contract for Harbors changes, Contractor must hire the new security contractor.
- H. By the end of each day, the Contractor shall re-erect and restore all fencing/barrier/perimeter security measures to the satisfaction of the Harbors Construction Engineer and the Oahu District Manager. Electricity and lighting

shall also be restored and in satisfactory working order, to no less than pre-construction conditions, by the end of each day, to the satisfaction of the Harbors Construction Engineer and Oahu District Manager.

- I. Under no circumstances shall perimeter security be compromised. If determined by the State, and solely by the State, that the contractor has left the project site in a condition that compromises security of the harbor, the State reserves the right to make the necessary arrangements to provide and enhance perimeter security, including restoration of electrical power and lighting, at the sole expense of the Contractor.
- J. At times, the maritime security level for the State of Hawaii and/or the general color-coded security level for State of Hawaii may be temporarily elevated. In these events, the contractor may be prohibited to access the project site and may be required to stop work as directed by either the Harbors Construction Engineer or Oahu District Manager. The Department of Transportation, Harbors will consider impacts to the work and schedule as a result of prolonged work stoppages.
- K. Maritime Security Awareness training is mandatory for all personnel entering the Harbor facility. The Contractor shall be responsible to ensure all of its employees, representatives, subcontractors, vendors, and all alike, requiring access to the harbor area for this project, have been trained and possess the required maritime security card before entering the Harbor's property. Prior to starting work on this project, the Contractor shall provide a list of names (full legal name) and birth dates of all employees, representatives, subcontractors, vendors, and all alike, as well as their vehicles license number, year, make, color and model that will be entering the project site, together with a letter attesting that all personnel have received this training to the Harbors Oahu District Manager and Construction Engineer. All employees, representatives, subcontractors, vendors, and all alike, shall wear their respective company's identification card bearing the company's name, the individual's first and last name, and middle initial(s), and a recent photograph of the individual on the front of the identification card at all times while on Harbor's property.

With the possible exception of Item J above, all other requirements indicated shall be considered incidental to the project and shall be provided by the contractor at no cost to the State.

The Contractor's personnel requiring unescorted access to secure areas of maritime facilities will be required to obtain a Transportation Worker Identification Credential (TWIC). No escorting of personnel is allowed. The project area has been deemed to be within a secured area. TWIC was established by Congress through the Maritime Transportation Security Act and is administered by the Transportation Security Administration (TSA) and U.S. Coast Guard. To obtain a TWIC, the applicant must provide biographic and biometric information such as fingerprints, sit for a digital photograph and successfully pass a security threat assessment conducted by TSA. The Contractor will be responsible to obtain and pay for all costs associated in providing their

appropriate employees with TWIC. Information regarding TWIC is available on the TSA website at: <https://www.tsa.gov/for-industry/twic>.

10.12 COMPLETION TIME - All work for this project shall be completed within the specified time period as listed on page P-1 of the Proposal. The number of days shall commence on the issuance of the notice to proceed. The intent of the contract is to provide for the construction final acceptance of the work described by the contract documents at the accepted bid price and within the time established by the contract. The Contractor has the duty to furnish all labor, materials, equipment, tools, transportation, incidentals, and supplies and to determine the means, methods and schedules required to complete the work in accordance with the contract documents.

Unless otherwise directed by the Construction Engineer in writing, the Contractor shall not commence with physical construction without sufficient materials and equipment available at the project site for either continuous construction until completion, or completion of a specified portion of the work.

10.13 PAYMENT - Payment shall be made as specified below. Such payment shall include furnishing all labor, material, equipment and other expenses required to complete each item in accordance with the plans and specifications.

Item 1 – Mobilization (Not to exceed 6% sum of all Items, excluding this Item). Payment shall be made at the lump sum price bid in the Proposal Schedule. Such payment described in Article XI of these Specifications shall include setting up all plant equipment and materials at the job site, providing temporary barricades as required for Harbor operations during construction, and all other incidental work required to complete this item.

Item 2 – Installation, Maintenance, Monitoring, and Removal of BMP. Payment shall be made at the lump sum price bid in the Proposal Schedule. Such payment described in Article XII of these Specifications shall include providing, installing, maintaining, monitoring and removing measures required for BMP's regarding substructure or other work associated with the project as described in Article XII, and all other incidental work required to complete this item.

Item 3 – Additional Noise, Water Pollution, Dust, and Erosion Control. Payment shall be made for additional noise, water pollution, dust, and erosion control measures beyond those described in Article XII, including those to accommodate requests by Aloha Tower tenants and HPU, on a force account basis as described in the Proposal Schedule. Such payment shall include providing, installing, and subsequent removal of additional noise, water pollution, dust, and erosion control measures not described in Article XII, and all other incidental work required to complete this item. The amount may be more or less than the estimated amount shown in the proposal.

Item 4 – Pre-Construction Survey. Payment shall be made at the lump sum price bid in the Proposal Schedule. Such payment shall include sounding all concrete within the project area, delineating all spalled and delaminated areas, numbering the spalled areas per type of repair,

including with the submittals a list of the assessed repairs, and all other incidental work required to complete this item.

Item 5 – Gunite Removal. Payment shall be made at the unit price bid in the Proposal Schedule. Such payment shall include gunite removal and demolition work at all substructure areas not including Item 6, hauling, and all other incidental work required to complete this item. Gunite removal will be performed to identify spalls and delaminations in the concrete substructure beneath that should be repaired in Items 7, 8, and 9. Payment for gunite removal for Item 6 shall be included in that item.

Item 6 – Full Slab Replacement Repair (Type FS). Payment shall be made at the unit price bid per square foot in the Proposal Schedule. Such payment shall include concrete/gunite removal and demolition work, hauling, preparing repair area, cleaning effective reinforcing steel to remain, furnishing and installing reinforcing steel, installing epoxy grouted dowels, applying reinforcing steel coating, installing and removing formwork, placing concrete, patching core holes and holes used to support form work, and all other incidental work required to complete this item.

Item 7 – Slab Spall Repair (Type SR). Payment shall be made at the unit price bid per square foot in the Proposal Schedule. Such payment shall include concrete removal work, preparing repair area, cleaning effective reinforcing steel to remain, applying reinforcing steel coating, installing and removing formwork, placing concrete or patching compound, patching holes used to support form work, and all other incidental work required to complete this item. Payment for reinforcing steel replacement shall be made in accordance with Item 10 below.

Item 8 – Beam Spall Repair (Type B or BR). Payment shall be made at the unit price bid per square foot in the Proposal Schedule. Such payment shall include concrete removal work, preparing repair area, cleaning effective reinforcing steel to remain, applying reinforcing steel coating, installing and removing formwork, placing concrete or repair mortar, patching holes used to support form work, and all other incidental work required to complete this item. Payment for reinforcing steel replacement shall be made in accordance with Item 10 below.

Item 9 – Vertical Spall Repair (Type V or VR). Payment shall be made at the unit price bid per square foot in the Proposal Schedule. Such payment shall include concrete removal work, preparing repair area, cleaning effective reinforcing steel to remain, applying reinforcing steel coating, installing and removing formwork, placing concrete or patching compound, patching holes used to support form work, and all other incidental work required to complete this item. Payment for reinforcing steel replacement shall be made in accordance with Item 10 below.

Item 10 – Reinforcing Steel Replacement. Payment shall be made at the unit price bid per pound in the Proposal Schedule. Such payment shall include furnishing and installing new reinforcing steel to be welded for Items 7, 8, and 9, welding reinforcing steel, and all other incidental work required to complete this item.

Item 11 – Epoxy Coating System. Payment shall be made at the unit price bid per square foot in the Proposal Schedule. Such payment shall include surface preparation, furnishing and coating all repaired concrete surfaces on the substructure as shown on the drawings, and all other incidental work required to complete this item.

Preparation of photographs of repairs will not be paid for directly but shall be considered incidental to the various contract items.

Repair quantities listed in the Proposal Schedule are increased from actual field quantities to account for growth in repair areas and additional repairs not shown in plans. Additional repairs may be present in project limits. No adjustment to the unit prices listed in the Proposal Schedule will be allowed due to difference between actual quantities and bid quantities.

ARTICLE XI - MOBILIZATION AND DEMOBILIZATION

11.1 GENERAL

- A. Related Documents - The General Provision of the contract, including the General Provisions for Construction Projects (2016) and General Requirements of the Specifications, apply to the work specified in this Section.
- B. General Requirements - Section 699 of "*Hawaii Standard Specifications for Road and Bridge Construction, 2005*," are hereby incorporated into and made a part of these specifications by reference unless otherwise modified hereinafter.
- C. Mobilization - The Contractor shall mobilize and transport his construction plant and equipment including materials and supplies for operation to the site of work, construct temporary buildings and facilities as necessary, and assemble the equipment at the site as soon as possible after receipt of Notice to Proceed, subject to the provisions of the General Provisions.
- D. Demobilization - The Contractor shall demobilize and transport his construction plant and equipment including materials, supplies and temporary buildings off the site as soon as possible after construction is completed. Demobilization shall include all cleanup required under this contract and as directed by the Engineer. Demobilization and final cleanup shall be completed prior to final acceptance.

11.2 MATERIALS (Not Applicable)

11.3 EXECUTION (Not Applicable)

11.4 MEASUREMENT AND PAYMENT

- A. Method of Measurement
 - 1. Mobilization shall not be measured for payment. The maximum bid allowed for "Mobilization" is an amount not to exceed six (6) percent of the sum of all items (excluding this item). If the proposal submitted by the bidder indicates an amount in excess of the allowable maximum, the indicated amount or amounts shall be reduced to the allowable maximum; the "Total Amount for Comparison of Bids," in the proposal schedule shall be adjusted to reflect any such reduction. For the purposes of comparing bids and determining the contract price to be inserted in the contract awarded to the bidder, if any is so awarded, the "Total Amount for Comparison of Bids" adjusted in accordance with the foregoing shall be used and the bidder's proposal shall be deemed to have been submitted for the amounts as reduced and adjusted in accordance herewith."
 - 2. Demobilization will not be measured for payment.

B. Basis of Payment

1. Mobilization will be paid for at the contract lump sum price under Mobilization. Partial payment will be made as follows:
 - i. When 2 1/2 percent of the original contract amount is earned, 50 percent of the bid amount will be paid.
 - ii. When 5 percent of the original contract amount is earned, 75 percent of the bid amount will be paid.
 - iii. When 10 percent of the original contract amount is earned, 100 percent of the bid amount will be paid.
 - iv. Nothing herein shall be construed to limit or preclude partial payments otherwise provided by the contract.

C. Payment for Mobilization shall be made as described in Article X of these Specifications.

ARTICLE XII – TEMPORARY WATER POLLUTION, DUST, AND EROSION CONTROL
For Project NOT Subject to NPDES NOI-C Permit

12.1 DESCRIPTION - This section is required for all work, including the Contractor’s storage sites. It describes the following:

- A. A detailed site-specific Best Management Practice (BMP) Plan including diagrams and narratives; constructing, maintaining, and repairing temporary water pollution, dust, and erosion control measures at the project site including local material sources, work areas and access roads; removing and disposing of wastes and hazardous wastes; and control of fugitive dust (defined as uncontrolled emission of solid airborne particulate matter from any source other than combustion). Additionally, all projects at Honolulu, Kalaehoa Barbers Point, and Kahului Harbors are subject to State of Hawaii, Department of Transportation (HDOT) Harbors, Stormwater Management Plan (SWMP) requirements, unless exempted, and are subject to Harbors Stormwater BMP inspections. If any requirement conflicts with those administered by State of Hawaii, Department of Health (HDOH), the Contractor shall follow the more stringent requirement.
- B. Compliance with applicable federal and other state permit conditions.
- C. Work associated with dewatering and hydrotesting activities and compliance with conditions of the NPDES general permit coverage authorizing discharges associated with construction activity dewatering and hydrotesting.

12.2 GENERAL REQUIREMENTS - In order to provide for the control of water pollution, dust, and erosion arising from the construction activities of the Contractor and his subcontractors in the performance of this contract, the work performed shall comply with all applicable federal, state, and local laws and regulations concerning water pollution control including, but not limited to, the following regulations:

- A. State of Hawaii, HDOH, Hawaii Administrative Rules (HAR) Chapter 11-54 – Water Quality Standards and Chapter 11-55 – Water Pollution Control.
- B. For projects at Honolulu, Kalaehoa Barbers Point, and Kahului Harbors ONLY, HDOT Harbors, Stormwater Management Plan.
- C. For projects at Honolulu, Kalaehoa Barbers Point, and Kahului Harbors ONLY, City and County of Honolulu (CCH), Rules Relating to Water Quality.
- D. For projects at Honolulu, Kalaehoa Barbers Point, and Kahului Harbors ONLY, CCH, Storm Water BMP Manual for Construction.
- E. 40 CFR Part 110, Environmental Protection Agency (EPA), Discharge of Oil.

- F. 40 CFR Part 117, EPA, Determination of Reportable Quantities for Hazardous Substances.
- G. 40 CFR Part 261, EPA, Identification and Listing of Hazardous Waste.
- H. 40 CFR Part 302, EPA, Designation, Reportable Quantities, and Notification.
- I. 49 CFR Part 171, U.S. Department of Transportation, Hazardous Materials Regulations.

12.3 MATERIALS - Materials shall conform to the following when applicable:

- A. Slope Drains. Slope drains may be constructed of pipe, fiber, mats, erosion control fabric, geotextiles, rubble, Portland cement concrete, bituminous concrete, plastic sheets, or other materials acceptable to the Construction Engineer.
- B. Grass. Grass shall be quick growing species such as rye grass, Italian grass, or cereal grasses. Grass shall be suitable to the area and provide a temporary cover that will not compete later with permanent cover. Alternative grasses are allowable if acceptable to the Construction Engineer.
- C. Fertilizer and Soil Conditions. Fertilizer and soil conditioners shall be a standard commercial grade acceptable to the Construction Engineer.
- D. Silt Fences. Silt fences shall be synthetic filter fabric mounted on posts and embedded in compacted ground in compliance with American Society for Testing and Materials (ASTM) D6462-03, Standard Practice for Silt Fence Installation.
- E. Berms. Berms shall be gravel or sand wrapped with geotextile material. Alternate materials are allowable if acceptable to the Construction Engineer.
- F. Alternate materials or methods to control, prevent, remove, and dispose of pollution are allowable if acceptable to the Construction Engineer.

12.4 CONSTRUCTION

- A. Preconstruction Requirements.
 - 1. Temporary Stormwater Pollution, Dust, and Erosion Control Meeting. The contractor shall be required to submit a site-specific BMP Plan to the Construction Engineer and address all comments by the Construction Engineer. After the Plan is accepted in writing by the Construction Engineer, the Contractor shall schedule a meeting with the Construction Engineer before the start of construction work to discuss the sequence of work, and plans and proposals for stormwater pollution, dust, and erosion control.

2. Temporary Water Pollution, Dust, and Erosion Control Submittals.
The Contractor shall submit the site-specific BMP Plan to the Construction Engineer prior to the start of work for review of compliance with this Article. A site-specific BMP Plan template is available online at <https://hidot.hawaii.gov/harbors/malamaikeawakai/>, under **HDOT Harbors Construction and Post-Construction Programs – Documents and Forms.**
- a. Written site-specific BMP Plan shall include the following as applicable:
- 1) Identification of potential pollutants and their sources and other factors that may cause water pollution, dust, and erosion.
 - 2) A list of all material and heavy equipment to be used during construction. Vehicles and equipment shall be well maintained and free from any type of fluid leaks.
 - 3) Construction schedule.
 - 4) Name(s) of specific individual(s) designated responsible for water pollution, dust and erosion controls on the project site. Include home, business, and cellular telephone numbers, fax numbers, and e-mail addresses.
 - 5) Descriptions of the methods and devices used to eliminate certain pollutants (e.g., wastewater, fuels, solvents, detergents, toxic or hazardous substances) from discharging into state waters and drainage systems, and provide details of BMP(s) to be installed or utilized. Indicate approximate dates when BMP(s) will be installed and removed.
 - 6) Description of maintenance and subsequent removal of BMP(s).
 - 7) Method(s) of removal and disposal of solid and regulated hazardous wastes encountered or generated during construction. The Contractor is advised to procure regulated hazardous materials on an as-needed basis, as feasible. All excess regulated hazardous materials at the conclusion of this project shall remain the property of the Contractor and shall be removed from HDOT Harbors property upon the completion of the project.
 - 8) Method(s) of removing and disposing concrete and asphalt pavement cutting slurry, concrete curing water, and hydrodemolition water.

- 9) Method(s) of containing, removing and disposing of demolition dust and debris to minimize the discharge of these pollutants into state waters and drainage systems.
- 10) Spill kit contents and location.
- 11) Fugitive dust control, including dust from grinding, sweeping, or brooming off operations or combination thereof.
- 12) Method(s) of storing and handling of regulated hazardous materials (e.g. oils, paints) and other products used for the project. Safety Data Sheets (SDS) for all regulated hazardous materials used during construction activities shall be kept on-site throughout the duration of the project and readily available upon inspection. All containers of regulated hazardous materials should be provided with secondary containment during storage. Regulated hazardous materials not specifically needed in the execution of this project shall not be brought or stored on site. As feasible, the Contractor is encouraged to use products that do not contain any regulated constituents. The use of green products is encouraged.
- 13) Method(s) of concrete washout/waste control.
- 14) Method(s) of managing material stockpiles to minimize erosion and dust.
- 15) Good housekeeping practices.
 - a) Minimize tracking of sediment offsite from project entrances and exits.
 - b) Litter management. The Contractor shall have a comprehensive housekeeping policy and shall actively enforce housekeeping requirements. Housekeeping items include, but are not limited to, cups, cans, bottles and other forms of lightweight litter, unattended containers of hazardous materials, concrete debris (e.g. dust, chips, and other sweepings), and discarded articles of disposable Personal Protective Equipment (e.g., earplugs, dust masks, and gloves). Employees who are specifically tasked with housekeeping duties shall be identified by name.

- c) The Contractor should provide and maintain covered waste receptacles. No construction debris or other refuse that is generated as a result of project activities is to be disposed in HDOT Harbors-owned waste receptacles.
- 16) Provide plan(s)/drawing(s) showing location of followings when applicable:
- a) Boundaries of the property and the locations where construction activities will occur, including:
 - i. Locations where earth-disturbing activities will occur (noting any sequencing of construction activities);
 - ii. Approximate slopes and drainage patterns with flow arrows before and after the construction;
 - iii. Locations where sediment, soil, or other construction materials will be stockpiled;
 - iv. Locations of any contaminated soil or contaminated soil stockpiles;
 - v. Locations of any crossings of state waters;
 - vi. Designated points on the site where vehicle will exit onto paved roads;
 - vii. Locations of structures and other impervious surfaces upon completion of construction; and
 - viii. Locations of construction support activity areas.
 - b) Locations of all state waters, including wetlands and indicate which water bodies are listed as impaired.
 - c) The boundary lines of any natural buffers.
 - d) Topography of the site, existing vegetative cover, and features (e.g., forest, pasture, pavement, structures), and drainage pattern(s) of stormwater

onto, over, and from the site property before and after major grading activities.

- e) Stormwater discharge locations, including locations of any storm drain inlets on-site and in the immediate vicinity of the site to receive stormwater runoff from the project; and locations where stormwater will be discharging to state waters (including wetlands).
 - f) Locations of all potential pollutant-generating activities.
 - g) Locations of stormwater control measures; and
 - h) Locations where chemicals will be used and stored.
- 17) Procedures for notification of appropriate facility personnel, emergency response agencies, and regulatory agencies where a leak, spill, or other release containing a hazardous substance or oil in an amount equal to or in excess of a reportable quantity established under either 40 CFR Parts 110, 117, or 302, occurs during a 24-hour period. Contact information must be in locations that are readily accessible and available.
- 18) The Contractor shall date and sign the site-specific BMP Plan.
- b. The Contractor shall keep the accepted Plan on-site or at an easily accessible location throughout the duration of the project. Revisions to the Plan shall be included with the original plan. The Contractor shall obtain written acceptance from the Construction Engineer before revising BMP. An updated Plan shall be kept on-site throughout the remainder duration of the project.

The Contractor shall follow guidelines in the “*The City and County of Honolulu Storm Water Best Management Practice Manual – Construction*,” (dated November 2011) in developing, installing, and maintaining BMP for the project. Additionally, the Contractor shall follow applicable CCH Rules Relating to Water Quality for all projects at Honolulu, Kalaeloa Barbers Point, and Kahului Harbors, and use respective Soil Erosion Guidelines for other Maui, Kauai and Hawaii County projects. Information can be found at the respective County websites.

B. Construction Requirements are as follows.

1. No work shall be allowed to begin until submittals detailed in Subsection 12.4.A.2 – Temporary Water Pollution, Dust, and Erosion Control Submittals are completed and accepted in writing by the Construction Engineer. The Contractor shall prevent pollutants from entering state waters. These efforts shall address areas such as those that drain to water, are over water, or drain to storm drains in the area of the project site. The Contractor shall design, operate, implement, and maintain the Plan to ensure that storm water discharges associated with construction activities will not cause or contribute to a violation of applicable state water quality standards.
2. All projects at Honolulu, Kalaehoa Barbers Point, and Kahului Harbors are subject to HDOT Harbors SWMP requirements for construction at those harbors unless the project meets a specified exemption class. The requirements include, but are not limited to, construction site BMP initial, recurring (i.e. every two weeks from October through March and every two months otherwise), and final inspections at the frequencies outlined in the SWMP. No grading or land disturbance activities are allowed until the initial BMP inspection is completed and required BMPs are found to be properly installed.
3. Address all comments received from the Construction Engineer.
4. Modify and resubmit plans and construction schedules to correct conditions that develop during construction which were unforeseen during the design and pre-construction stages.
5. Coordinate temporary control provisions with permanent control features throughout the construction and post-construction period.
6. BMP shall be in place and operational until the construction is completed and accepted by Harbors.
7. Install and maintain either or both stabilized construction entrances and wheel washes to minimize tracking of dirt and mud onto roadways. Restrict traffic to stabilized construction areas only. Clean dirt, mud, or other material tracked onto the road immediately. Modify stabilized construction entrances to prevent mud from being tracked onto roadways.
8. Chemicals may be used as soil stabilizers for either or both erosion and dust control if acceptable to the Construction Engineer.
9. Cover exposed surface of materials completely with tarpaulin or similar device when transporting aggregate, soil, excavated material or material that may be a source of fugitive dust.

10. Clean up and remove any pollutant that can be attributed to the Contractor.
11. Install or modify BMP due to change in the Contractor's means and methods, or for omitted condition that should have been allowed for in the accepted site-specific BMP Plan or a BMP that replaces an accepted site-specific BMP that is not satisfactorily performing.
12. Properly maintain BMP.
13. Remove, replace or relocate any BMP that must be removed, replaced or relocated due to potential or actual flooding, or potential danger or damage to the project or public.
14. The Contractor's designated representative specified in Subsection 12.4.A.2.a.4 shall address any BMP concerns brought up by the Construction Engineer within 24 hours of notification, including weekends and holidays. Should the Contractor fail to satisfactorily address these concerns, the Construction Engineer reserves the right to employ outside assistance or use the Construction Engineer's own labor forces to provide necessary corrective measures. The Construction Engineer will charge the Contractor such incurred costs plus any associated project engineering costs. The Construction Engineer will make appropriate deductions from the Contractor's monthly progress estimate. Failure to apply BMP shall result in either or both the establishment and increase in the amount of retainage due to unsatisfactory progress or withholding of monthly progress payment. Continued failure to apply BMP may result in one or more of the following: The Contractor being fully responsible for all additional costs incurred by HDOT Harbors including any fines levied by HDOH, suspension of the Contract, or cancellation of the Contract.

- C. Hydrotesting Activities. If work includes removing, relocation or installing waterlines, and the Contractor elects to flush waterline or discharge hydrotesting effluent into state waters or drainage systems, obtain a Notice of General Permit Coverage (NGPC) authorizing discharges associated with hydrotesting waters from the HDOH Clean Water Branch (CWB). If a permit is required, prepare and submit permit application (CWB-Notice of Intent (NOI) Form F) to the HDOH CWB.

Do not begin hydrotesting activities until the HDOH CWB has issued a NGPC. Hydrotesting operations shall be in accordance with conditions in the NGPC. Submit a copy of the NPDES Hydrotesting Waters Application and Permit to the Construction Engineer.

- D. Dewatering Activities. If excavation or backfilling operations requires dewatering, and the Contractor elects to discharge dewatering effluent into state waters or existing drainage systems, obtain an NGPC authorizing discharges associated with construction activity dewatering from the HDOH CWB. If a

permit is required, prepare and submit permit application (CWB-NOI Form G) to the HDOH CWB.

Do not begin dewatering activities until the HDOH-CWB has issued an NGPC. Conduct dewatering operations in accordance with the conditions in the NGPC. Submit a copy of the NPDES Dewatering Application and Permit to the Construction Engineer.

12.5 MEASUREMENT

- A. Installation, maintenance, monitoring, and removal of the BMP will be paid on a lump sum basis. Measurement for payment will not apply.
- B. The Construction Engineer will only measure additional water pollution, dust and erosion control required and requested by the Construction Engineer on a force account basis in accordance with Subsection 109.06 - Force Account Provisions and Compensation of the "*Hawaii Standard Specification for Road and Bridge Construction, 2005.*"

12.6 PAYMENT – Payment for installation, maintenance, monitoring, and removal of BMP shall be made as specified in Article X of these Specifications.

No progress payment will be authorized until the Construction Engineer accepts in writing the site-specific BMP Plan or when the Contractor fails to maintain the project site in accordance with the accepted BMP Plan.

The Contractor shall reimburse the State of Hawaii within 30-day for the full amount of all outstanding costs incurred by the State of Hawaii for all citations or fines received as a result of the Contractor's non-compliance with regulations.

ARTICLE XIII – CONCRETE REMOVAL WORK

13.1 GENERAL

- A. The work to be done under this Article includes, but is not necessarily limited to, demolition and removal work at full slab replacement and spall repairs at select locations as indicated on the plans. All material resulting from removal work shall become property of the Contractor except as indicated or otherwise specified and shall be removed from the project site.
- B. In general, the work includes but is not limited to the following:
 - 1. Cutting, chipping and removing concrete/gunite at full slab replacement and beam spall repair areas designated on the drawings.
 - 2. Cutting, chipping and removing concrete/gunite at all other various substructure surfaces including slabs, beams, girders, piles, and bulkhead walls.
 - 3. Cutting, chipping and removing concrete at spall repair areas.
- C. All work shall be in accordance with the following sections of the Standard Specifications except as modified or supplemented herein:

Section 201 Clearing and Grubbing

Section 202 Removal of Structures and Obstructions

13.2 GENERAL REQUIREMENTS

- A. The provisions of Section 201 “Clearing and Grubbing” of the Standard Specifications shall apply except as hereinafter modified.
- B. The provisions of Section 202 “Removal of Structures and Obstructions” of the Standard Specifications shall apply except as hereinafter modified.
- C. Reference to “highway” in this section means “harbor facilities”.

13.3 SUBMITTALS

- A. Submit proposed demolition and removal procedures to the Harbors Construction Engineer before work is started. Procedures shall provide for coordination with other work in progress, a detailed description of methods and equipment to be used for each operation, and sequence of operations.

13.4 CONSTRUCTION METHODS

- A. Phasing of Work – The Contractor shall phase the work to minimize shutdown of existing mooring bollards and maintaining a travel lane. An existing cleat shall not be used when concrete repair work is performed in the bays adjacent to the bollard. Cleats shall not be put back into use until the repair concrete has been allowed to cure for 7 days.
- B. Existing Facilities to be Removed. All work shall be executed in an orderly and careful manner with due consideration for all items to remain. All work shall be indicated and as required to complete the removal work.
- C. Dust Control. Take appropriate action to check the spread of dust and to avoid the creation of nuisance in the surrounding area. Provide barriers, dust screens, tarpaulins or similar action to prevent damage to and dust from entering the shed. Comply with all dust regulations imposed by local air pollution agencies.
- D. Use of explosives will not be permitted.
- E. Where pedestrian and driver safety is endangered in the area of removal work, use traffic barricades with flashing lights.
- F. The Contractor shall take precautions to prevent damage to items indicated to remain. The Contractor shall repair any damage to items indicated to remain at no cost to the State.
- G. Contractor shall maintain all existing utilities in service and protect them against damage during demolition operations.

13.5 DUST AND DEBRIS CONTROL

- A. Prevent the spread of dust and debris and avoid the creation of a nuisance of hazard in the surrounding area. Do not use water if it results in hazardous or objective conditions such as, but not limited to, flooding or pollution.

13.6 DISPOSITION OF MATERIAL

- A. Title of Materials – Title to all materials and equipment to be removed, except as specified otherwise, is vested in the Contractor upon approval by the Director of the Contractor’s demolition and removal procedures, and authorization by the Director to begin demolition. The State will not be responsible for the condition or loss of, or damage to, such property after notice to proceed.
- B. Unsalvageable Materials – Noncombustible and combustible materials shall be disposed of outside the limits of the project site at the Contractor’s responsibility and expense.

- C. Removed material shall be disposed of away from the project site in a lawful manner at no cost to the State. The Contractor will not be allowed to deposit removed material into State waters.
- D. Survey for Hazardous Areas – The Contractor shall survey the entire area around the project site to ensure that no hazardous vapors are present. The Contractor shall certify in writing that the project site shall be safe for hot work and free of hazardous vapor. No open flame, hot cutting, welding or other hot work will be permitted without the certification.

13.7 CLEANUP

- A. Debris and Rubbish – Remove and transport debris and rubbish in a manner that will prevent spillage on pavements, streets or adjacent areas.
- B. Comply with Federal, State, and local hauling and disposal regulations.

13.8 PAYMENT - Payment for concrete removal work shall not be made separately but shall be considered incidental to the items described in Article X of the Specifications.

ARTICLE XIV – CONCRETE REPAIR WORK

14.1 GENERAL

- A. Work under this Article includes furnishing all labor, materials and equipment necessary to repair spalled concrete on the pier substructure in the project area. Work shall be performed in phases to always maintain a travel way at Pier 10.
- B. In general, the work includes, but is not necessarily limited to the following:
 - 1. Sounding concrete to determine extent of concrete spall repairs.
 - 2. Removal of concrete surrounding reinforcing steel in repair areas.
 - 3. Preparing concrete repair area.
 - 4. Replacing severely corroded reinforcing steel with replacement reinforcing steel at spall repairs.
 - 5. Installing new reinforcing steel.
 - 6. Cleaning reinforcing steel and applying reinforcing steel coating.
 - 7. Installing and removing formwork.
 - 8. Placing concrete or patching compound.
- C. All work shall be in accordance with the following sections of the Standard Specifications except as modified or supplemented herein:

Section 503 Concrete Structures
Section 601 Structural Concrete
Section 602 Reinforcing Steel
Section 711 Concrete Curing Materials and Admixtures

Sections on Materials referenced in the above sections are hereby incorporated.

14.2 MATERIALS

- A. Concrete
 - 1. Concrete shall be Class $f'c = 5,000$ psi.
 - 2. Maximum aggregate size shall be 3/8 inches and shall be coordinated with concrete preparation procedures for spall repairs.

- B. Admixture - Admixture to be used in the concrete shall be approved by the Construction Engineer. Contractor shall strictly adhere to the manufacturer's recommendations regarding the use of admixtures including storage, transportation and method of mixing.

CORTEC MCI 2005NS migrating corrosion inhibiting admixture manufactured by Cortec Corporation, or approved equal, shall be added at the following rate and as recommended by the manufacturer.

CORTEC MCI 2005NS: 1.5 pints per cubic yard of concrete

To combat climate change and reduce the concrete carbon footprint, supplementary cementitious material(s) shall be used to reduce the cement content in the concrete for this project. The following supplementary cementitious material shall be substituted for cement by weight at the following rate and as recommended by the concrete supplier.

Fly Ash: 20% of cement by weight

The maximum water to cementitious materials ratio shall be 0.40 and the mix water shall be reduced as necessary to account for the admixture.

- C. Reinforcing Steel for Weld Splicing - Reinforcing steel for weld splicing shall be ASTM A706 Grade 60.
- D. Reinforcing Steel - Reinforcing not to be weld spliced shall be ASTM A615 Grade 60 or ASTM A706 Grade 60.
- E. Welds - Welding electrodes shall be low hydrogen E70.
- F. Reinforcing Steel Anti-Corrosion Coating - Anti-corrosion coating with a minimum 7 day open time for reinforcing steel shall be Sika Armatec 110 Epocem by Sika, or approved equal.
- G. Epoxy Grout - Epoxy for grouting of dowels shall be SET 3G by Simpson Strong-Tie, or approved equal.
- H. Patching Compound for form and pour repairs shall be Sikacrete 211 SCC Plus by Sika, or approved equal.
- I. Patching Compound for repairing vertical and overhead repairs in lifts shall be Sikaquick VOH with Later R by Sika, or approved equal.
- J. Curing Compound for concrete repairs shall be acceptable to the Harbors Construction Engineer.
- K. Forms shall conform to Section 503.03.C "Forms" of the Standard Specifications.

- L. Snap ties and inserts shall be plastic or stainless steel. All reinforcing steel shall be secured with ties at all intersections with adjacent reinforcing steel.

14.3 CONSTRUCTION METHODS

- A. Concrete construction shall conform to the American Concrete Institute (ACI) ACI 318R and ACI 546R.
- B. Pre-Construction Survey - The Contractor shall clearly identify the bents under the pier, sound all the concrete within the project area and delineate all the spalled areas, numbering the spalled areas per type of repair. A list with the assessed repairs shall be included with the submittals.
- C. Surface preparation for spall repair work shall follow the International Concrete Repair Institute (ICRI) Guideline No. 310.1R-2008. The sizes, locations and types of repair work specified on the drawings are intended to be approximate only. The actual amount and type of repair work to be done shall be determined after completion of the removal work. Removal and surface preparation shall be performed in the order listed below.
 - 1. All visible loose and deteriorated concrete shall be removed with suitable pneumatic or hand tools until only sound concrete remains.
 - 2. Such chipped areas and adjoining areas shall be further sounded by tapping with a light hammer. Areas emitting a hollow sound indicating unsound and delaminated concrete with voids shall be further chipped to sound concrete and beyond the extent of the corroded reinforcing.
 - 3. Partially exposed reinforcing steel or steel exposed during the concrete chipping process shall be fully exposed throughout their length within the repair area. There shall be a minimum of 3/4 inch of clear distance between the reinforcing steel and the chipped surface of the existing concrete for placing patching compound or concrete.
 - 4. The edges of the repair shall be saw-cut and chipped as necessary to attain a minimum repair material depth of 3/4 inch and to prevent featheredge conditions.
 - 5. The existing concrete in the repair areas shall be chipped to approximate rectangular dimensions to facilitate the repair work.
 - 6. The patch area shall be cleaned of all dust and debris just prior to patching with high pressure, oil-free compressed air with appropriate PPE's and containment.
- D. Live Load Limitation

1. Any element being repaired shall not be subjected to live loads during the period starting from the removal of existing concrete until the repair concrete has been allowed to cure for 7 days or obtained a minimum compressive strength of $f'_c=4,000$ psi.
 2. Mooring cleats shall be shut down when spall repair work is performed in the vicinity of the bollards. Only one cleat will be allowed to be taken out of service at one time.
 3. The repair area shall remain barricaded with barriers visible at night from traffic during this period. The Contractor shall provide shoring for severely spalled areas as necessary to prevent damage or collapse.
- E. Cleaning Reinforcing Steel - All exposed concrete and reinforcing steel in the repair area shall be needle gunned to remove all scale, loose rust, debris and other bond-inhibiting materials. Any areas not patched more than 48 hours after cleaning shall be recleaned.
- F. Replacing Reinforcing Steel - All existing reinforcing bars with less than 80% of their cross-section remaining after cleaning shall be supplemented with welded reinforcing as shown on the plans. Replacement reinforcing steel will be measured by the pound, complete in place. The theoretical unit weight of each size of reinforcing bar used will be based upon Table 602.04-1 of the Standard Specifications.
- G. Welding Reinforcing Steel - All welding shall conform to AWS D1.4. All existing bars to be welded with a carbon equivalent (C.E.) above 0.55 percent shall be preheated according to the requirements set forth in AWS D1.4. If the C.E. is unknown, maximum preheat requirements for an assumed C.E. greater than 0.75 percent shall be used.

The Contractor shall survey the entire area around the project site to ensure that no hazardous vapors are present. The Contractor shall certify in writing that the project site shall be safe for hot work and free of hazardous vapor. No open flame, hot cutting, welding or other hot work will be permitted without the certification.

- H. Reinforcing Steel Coating - All exposed steel shall be liberally coated with anti-corrosion coating per manufacturer's recommendations.
- I. Epoxy Grouting - Blow holes completely clean of all concrete debris to allow for adequate bonding of the epoxy. The holes shall be filled with epoxy gel before inserting and turning the supplemental reinforcement to displace the grout.
- J. Photographs – The Contractor shall provide digital photographs of underside spall repairs to the Harbors Construction Engineer for their review. Photos shall be in color and taken with a digital camera having a 6.0 mega pixel resolution or

higher. Each photo shall be identified with the time, date, and location referenced to the plans.

The Contractor shall provide one set of photos per 200 square feet of spall repairs. A set of photos shall contain at least two photos for each of the procedures listed below.

1. Existing condition of concrete repair.
2. After all removal of existing concrete has been completed, including spalled and delaminated concrete, concrete surrounding reinforcing steel in repair areas, and sawcut and chipped out concrete at the perimeter of the repair.
3. After cleaning of the reinforcing steel.
4. After replacing severely corroded steel with weld spliced reinforcing steel.
5. After installing replacement reinforcing steel.
6. After applying reinforcing steel coating.
7. After formwork has been installed.
8. After forms have been removed, or concrete has cured for at least 3 days.

The photos shall be taken on the same day that the procedure has been completed and shall clearly represent typical details of the completed procedure. The photos shall also be emailed to the Harbors Construction Engineer on the same day that the photos were taken. Additionally, one set of 4" x 6" sized prints shall be delivered to the Construction Engineer at the completion of the project.

- K. Formwork - The exact method of formwork requires the Construction Engineer's approval. Forms shall be designed to provide a minimum of three (3) inches of concrete cover over all reinforcing steel, unless noted otherwise. All edges of concrete repairs shall be chamfered and existing joints shall be maintained.
- L. Placing Concrete - Concrete shall be placed in accordance with Section 503.03 - "Construction" of the Standard Specifications. All repair surfaces including forms shall be thoroughly washed with clean water and remain in a saturated surface dry condition prior to placing concrete. Surfaces shall be clean and free of loose and other bond-inhibiting materials. Surface-applied migrating corrosion inhibitor shall be applied to repair surfaces as per manufacturer's recommendations prior to placing repair concrete. The repair concrete shall be vibrated, rodded or tamped during placement to consolidate the pour and fill all corners of the patch or form and beneath the reinforcing. As an alternate self-consolidating concrete may be used. There shall be no cold joints in the field of the repair.

- M. Patching Compound - Patching compound shall be used only to fill minor spalls and voids and to fill minor depressions such as those caused by the installation of expansion anchors used for formwork support. The Contractor shall follow the manufacturer's recommendations for mixing and placing patching compound, including application of a slurry coat to prime the substrate and application of the repair material in lifts.
- N. Finish - Concrete finish shall be Class I - Ordinary Surface Finish. Provide smooth finish on pier decks for all holes patched. Cementitious compound used to patch holes shall be finished to the level of the concrete surface to match existing elevation and composition.
- O. Formwork Removal - Formwork for all repairs shall not be removed for a minimum of 24 hours and until concrete has obtained a minimum compressive strength of $f'c = 4,000$ psi.
- P. Concrete Curing - Concrete repairs on the underside of the pier shall be cured a minimum 7 days by leaving the forms in place or covering the surface with a curing compound approved by and acceptable to the Harbors Construction Engineer.
- Q. Identifying Repairs - Identify all repair work with paint. The color and marking for identification shall be a minimum 6 inch in height and black stenciling unless otherwise directed by the Harbors Construction Engineer.
- R. Defective Work - After forms have been removed, the repaired area shall be tested by tapping with a hammer. Any "hollow" sound emitted shall indicate the presence of voids and shall be sufficient cause for removal of repair work and reconstruction. The method of repairing defects shall be subject to the approval of the Construction Engineer. All defects shall be corrected by the Contractor at no additional cost to the State.

14.4 PAYMENT - Payment for concrete repair work shall be made as described in Article X of these Specifications.

ARTICLE XV – EPOXY COATING SYSTEM

15.1 GENERAL

- A. Work to be done under this Article includes coating the repaired areas and surfaces of the concrete slabs, beams, girders, and piles of Pier 10 as shown on the plans in the project location, with an epoxy coating system.
- B. **Work included in this Article must be completed by a valid State of Hawaii Specialty Contractor licensed “C-33” Painting and Decorating Contractor. The “C-33” Painting and Decorating Contractor must be listed on page P-4 of the Proposal at the time of bidding.**

15.2 MATERIALS

- A. Product shall be delivered to the site in manufacturer’s sealed containers until ready for application. Store and dispose of solvent-based materials, and materials used with solvent-based materials, in accordance with requirements of local authorities having jurisdictions. The coating shall be the following:
 - 1. High Solids Epoxy Coating – High Solids Epoxy Coating shall be Amerlock 400 manufactured by PPG Protective and Marine Coatings or approved equal. Color shall be off white/gray and submitted to the Harbors Construction Engineer for approval.

15.3 SURFACE PREPARATION

- A. Project Conditions - Maintain environmental conditions (temperature, humidity, and ventilation) within limits recommended by manufacturer for optimum results. Do not install products under environmental conditions outside manufacturer's absolute limits.
- B. Surfaces to be coated shall include all repaired concrete slabs, beams, girders, pile caps and piles down to and including the beam and girder haunch soffits on the underside of the pier.
- C. Preparation - Clean surfaces thoroughly prior to installation. Prepare surfaces similar to SSPC-SP-2 or SSPC-SP-3 or using the methods recommended by the manufacturer for achieving the best result for the substrate under the project conditions. The surface should be dry, sound, clean and free of all dirt, oil, grease efflorescence, dust, sax, soaps, powdery residue, form release agents, curing compounds, laitance and other foreign matter and be structurally sound. Cleaning may be done by steam cleaning, water blasting, sandblasting or other methods as necessary.

- D. All surfaces to be coated shall be properly prepared prior to coating and shall be inspected for approval by the Harbors Construction Engineer before coating will be allowed. In addition, a technical representative of the coating manufacturer shall be present to verify the surface preparation, application and dry film thickness of the coatings.

15.4 SURFACE APPLICATION

- A. Allow repair concrete to cure a minimum of 14 days or per manufacturer's recommendation.
- B. Apply two (2) coats of Amerlock 400 at a dry film thickness of 4-6 mils per coat for a total dry film thickness of 10 mils. Coating shall be applied in a method to ensure the material does not enter the water.
- C. The prime coat shall be applied on the same day that the surface is prepared. It may take more than a single application to obtain the required thickness. If a coat requires more than a single application, it shall be done no later than the following day.
- D. The time interval between each coat shall be no more than 24 hours or as recommended by the manufacturer. For intervals exceeding 24 hours, all surfaces shall be rinsed with fresh water or tested for acceptable chloride levels by the technical representative of the product manufacturer. Each coat shall be of a lighter color than the later coat to be coated upon it.
- E. Finish work shall be uniform and of approved color. The finish shall completely cover, be smooth and be free from runs, sags, drips, waves, laps or brush marks. Edges of coating adjoining other surfaces of materials shall be sharp and clean without overlapping.
- F. Coating shall be allowed to cure completely. Any marred surfaces or damages to the coating finish shall be corrected by proper preparation and recoating.
- G. All methods and procedures shall comply with OSHA and HIOSH requirements and be acceptable to the Harbors Construction Engineer.

15.5 CLEAN-UP

- A. All coating, oil, etc. shall be cleaned off fenders, chains, or any portion of the pier beyond the coating area. The Contractor shall take precautions to prevent the coating from being applied on equipment, vehicles, or cargo in the project area.
- B. All unused rags, waste and empty containers shall be removed from the work area at the end of each work day and precautions shall be taken to avoid the danger of fire.

- C. The Contractor shall maintain the job site in a neat and orderly condition during the progress of the work. Upon completion, the Contractor shall remove all surplus material, debris, equipment, tools, etc. belonging to it and leave the premises in a neat and orderly condition.

15.6 PAYMENT - Payment for the epoxy coating system shall be made as specified in Article X of these specifications.

ARTICLE XVI – PROJECT PHOTOGRAPHS



Photo 1: Typical Pier Substructure at Pier 10



Photo 2: Typical Slab Spall at Pier 10



Photo 3: Typical Beam Spall at Pier 10



Photo 4: Typical Girder Spall at Pier 10

Requirements of Chapter 104, HRS Wages and Hours of Employees on Public Works Law

Chapter 104, HRS, applies to every public works construction project over \$2,000, regardless of the method of procurement or financing (purchase order, voucher, bid, contract, lease arrangement, warranty, SPRB).

Rate of Wages for Laborers and Mechanics

- Minimum prevailing wages (basic hourly rate plus fringe benefits), as determined by the Director of Labor and Industrial Relations and published in wage rate schedules, shall be paid to the various classes of laborers and mechanics working on the job site. [§104-2(a), (b), Hawaii Revised Statutes (HRS)]
- If the Director of Labor determines that prevailing wages have increased during the performance of a public works contract, the rate of pay of laborers and mechanics shall be raised accordingly. [§104-2(a) and (b), HRS; §12-22-3(d) Hawaii Administrative Rules (HAR)]

Overtime

- Laborers and mechanics working on a Saturday, Sunday, or a legal holiday of the State or more than eight hours a day on any other day shall be paid overtime compensation at not less than one and one-half times the basic hourly rate plus the cost of fringe benefits for all hours worked. If the Director of Labor determines that a prevailing wage is defined by a collective bargaining agreement, the overtime compensation shall be at the rates set by the applicable collective bargaining agreement [§§104-1, 104-2(c), HRS; §12-22-4.1, HAR]

Weekly Pay

- Laborers and mechanics employed on the job site shall be paid their full wages at least once a week, without deduction or rebate, except for legal deductions, within five working days after the cutoff date. [§104-2(d), HRS]

Posting of Wage Rate Schedules

- Wage rate schedules with the notes for prevailing wages and special overtime rates, shall be posted by the contractor in a prominent and easily accessible place at the job site. A copy of the entire wage rate schedule shall be given to each laborer and mechanic employed under the contract, except when the employee is covered by a collective bargaining agreement. [§104-2(d), HRS]

Withholding of Accrued Payments

- If necessary, the contracting agency may withhold accrued payments to the contractor to pay to laborers and mechanics employed by the contractor or subcontractor on the job site any difference between the wages required by the public works contract or specifications and the wages received. [§104-2(e), HRS]

Certified Weekly Payrolls and Payroll Records

- A certified copy of all payrolls shall be submitted weekly to the contracting agency. [§104-3(a), HRS; §12-22-10, HAR]
- The contractor is responsible for the submission of certified copies of the payrolls of all subcontractors. The certification shall affirm that the payrolls are correct and complete, that the wage rates listed are not less than the applicable rates contained in the applicable wage rate schedule, and that the classifications for each laborer or mechanic conform with the work the laborer or mechanic performed. [§104-3(a), HRS; §12-22-10, HAR]
- Payroll records shall be maintained by the contractor and subcontractors for three years after completion of construction. The records shall contain: [§104-3(b), HRS; §12-22-10, HAR]
 - the name and home address of each employee
 - the last four digits of social security number
 - a copy of the apprentice's registration with DLIR
 - the employee's correct classification
 - rate of pay (basic hourly rate + fringe benefits)
 - itemized list of fringe benefits paid
 - daily and weekly hours worked
 - weekly straight time and overtime earnings
 - amount and type of deductions
 - total net wages paid
 - date of payment
- Records shall be made available for examination by the contracting agency, the Department of Labor and Industrial Relations (DLIR), or any of its authorized representatives, who may also interview employees during working hours on the job. [§§104-3(c), 104-22(a), HRS; §12-22-10, HAR]

Termination of Work on Failure to Pay Wages

- If the contracting agency finds that any laborer or mechanic employed on the job site by the contractor or any subcontractor has not been paid prevailing wages or overtime, the contracting agency may, by written notice to the contractor, terminate the contractor's or subcontractor's right to proceed with the work or with the part of the work in which the required wages or overtime compensation have not been paid. The contracting agency may complete this work by contract or otherwise, and the contractor or contractor's sureties shall be liable to the contracting agency for any excess costs incurred. [§104-4, HRS]

Apprentices

- Apprentice wage rates apply to contractors who are a party to a bona fide apprenticeship program which has been registered with the DLIR. In order to be paid apprentice rates, apprentices must be parties to an agreement either registered with or recognized as a USDOL nationally approved apprenticeship program by the DLIR, Workforce Development Division, (808) 586-8877, and the apprentice must be individually registered by name with the DLIR. [§12-22-6(1) and (2), HAR]
- The number of apprentices on any public work in relation to the number of journeyworkers in the same craft classification as the apprentices employed by the same employer on the same public work may not exceed the ratio allowed under the apprenticeship standards registered with or recognized by the DLIR. A registered or recognized apprentice receiving the journeyworker rate will not be considered a journeyworker for the purpose of meeting the ratio requirement. [§12-22-6(3), HAR]

Enforcement

- To ensure compliance with the law, DLIR and the contracting agency will conduct investigations of contractors and subcontractors. If a contractor or subcontractor violates the law, the penalties are: [§104-24, HRS]
 - First Violation Equal to 25% of back wages found due or \$250 per offense up to \$2,500, whichever is greater.
 - Second Violation Equal to amount of back wages found due or \$500 for each offense up to \$5,000, whichever is greater.
 - Third Violation Equal to two times the amount of back wages found due or \$1,000 for each offense up to \$10,000, whichever is greater; and
Suspension from doing any new work on any public work of a governmental contracting agency for three years.
- A violation would be deemed a second violation if it occurs within two years of the **first notification of violation**, and a third violation if it occurs within three years of **the second notification of violation**. [§104-24, HRS; §12-22-25(b), HAR]
- **Suspension:** For a first or second violation, the department shall immediately suspend a contractor who fails to pay wages or penalties until all wages and penalties are paid in full. For a third violation, the department shall penalize and suspend the contractor as described above, **except that if the contractor continues to violate the law, then the department shall immediately suspend the contractor for a mandatory three years. The contractor shall remain suspended until all wages and penalties are paid in full.** [§§104-24, 104-25, HRS]
- **Suspension:** Any contractor who fails to make payroll records accessible or provide requested information within 10 days, or fails to keep or falsifies any required record, shall be assessed a penalty including suspension as provided in Section 104-22(b) and 104-25(a)(3), HRS. [§104-3(c), HRS; §12-22-26, HAR]
- If any contractor interferes with or delays any investigation, the contracting agency shall withhold further payments until the delay has ceased. Interference or delay includes failure to provide requested records or information within ten days, failure to allow employees to be interviewed during working hours on the job, and falsification of payroll records. The department shall assess a penalty of \$10,000 per project, and \$1,000 per day thereafter, for interference or delay. [§104-22(b), HRS; §12-22-26, HAR]
- Failure by the contracting agency to include in the provisions of the contract or specifications the requirements of Chapter 104, HRS, relating to coverage and the payment of prevailing wages and overtime, is not a defense of the contractor or subcontractor for noncompliance with the requirements of this chapter. [§104-2(f), HRS]



For additional information, visit the department's website at <http://labor.hawaii.gov/wsd> or contact any of the following DLIR offices:

Oahu (Wage Standards Division)(808) 586-8777
Hawaii Island.....(808) 974-6464
Maui and Kauai(808) 243-5322

STATE OF HAWAII

DEPARTMENT OF TRANSPORTATION

HONOLULU, HAWAII

PROPOSAL

PROPOSAL TO THE STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION
HARBORS

PROJECT: HONOLULU HARBOR, PIER 10, SUBSTRUCTURE
REPAIRS, OAHU, HAWAII.

PROJECT NO.: S10955

COMPLETION TIME: THREE HUNDRED SIXTY (360) CALENDAR DAYS
from the date indicated in the Notice to Proceed from
the Department.

LIQUIDATED DAMAGES: FOUR HUNDRED, FIFTY DOLLARS (\$450.00) for
each and every calendar day which the Contractor has
delayed the completion of this project.

DESIGN PROJECT MANAGER: MR. BRANDEN SUMIDA
DEPARTMENT OF TRANSPORTATION
HARBORS
HALE AWA MOKU
79 S. NIMITZ HIGHWAY
HONOLULU, HAWAII 96813
PHONE: (808) 587-1873
EMAIL: branden.sumida@hawaii.gov

ELECTRONIC SUBMITTAL: **Bidders shall submit and upload the complete proposal to HiePRO prior to the bid opening date and time. Any additional support documents explicitly designated as confidential and/or proprietary shall be uploaded as a separate file to HiePRO. Bidders shall refer to SPECIAL PROVISIONS 2.8 PREPARATION AND DELIVERY OF BID for complete details. FAILURE TO UPLOAD THE COMPLETE PROPOSAL TO HiePRO SHALL BE GROUNDS FOR REJECTION OF THE BID.**

Director of Transportation
869 Punchbowl Street
Honolulu, Hawaii 96813

Dear Sir:

The undersigned Bidder declares the following:

1. It has not, either directly or indirectly, entered into any agreement, participated in any collusion, or otherwise taken any action in restraint of free competitive bidding in connection with this proposal.
2. It has not been assisted or represented on this matter by any individual who has, in a State capacity, been involved in the subject matter of this contract within the past two years.
3. It has not and will not, either directly or indirectly offered or given a gratuity (i.e. an entertainment or gift) to any State or County employee to obtain a contract or favorable treatment under a contract.

The undersigned Bidder further agrees to the following:

1. If this proposal is accepted, it shall execute a contract with the Department to provide all necessary labor, machinery, tools, equipment, apparatus and any other means of construction, to do all the work and to furnish all the materials specified in the contract in the manner and within the time therein prescribed in the contract, and that it shall accept in full payment therefore the sum of the unit and/or lump sum prices as set forth in the attached proposal schedule for the actual quantities of work performed and materials furnished and furnish satisfactory security in accordance with Section 103D-324, Hawaii Revised Statutes, within 10 days after the award of the contract or within such time as the Director of Transportation may allow after the undersigned has received the contract documents for execution, and is fully aware that non-compliance with the aforementioned terms will result in the forfeiture of the full amount of the bid guarantee required under Section 103D-323, Hawaii Revised Statutes.
2. That the quantities given in the attached proposal schedule are approximate only and are intended principally to serve as a guide in determining and comparing the bids.
3. That the Department does not either expressly or by implication, agree that the actual amount of work will correspond therewith, but reserves the right to increase or decrease the amount of any class or portion of the work, or to omit portions of the work, as may be deemed necessary or advisable by the Director of Transportation, and that all increased or decreased quantities of work shall be performed at the unit prices set forth in the attached proposal schedule except as provided for in the specifications.

4. In case of a discrepancy between unit prices and the totals in said Proposal Schedule, the unit prices shall prevail.
5. Agrees to begin work within 10 working days after the date of notification to commence with the work, which date is in the notice to proceed, and shall finish the entire project within the time prescribed.
6. The Director of Transportation reserves the right to reject any or all bids and to waive any defects when in the Director's opinion such rejections or waiver will be for the best interest of the public.
7. The undersigned Bidder further agrees to the following: Pursuant to HAR §3-122-13(e), any contractor (including consultants) paid for services to develop or prepare specifications or work statements shall be precluded from submitting an offer or receiving a contract for that particular solicitation. This includes the preparation of reports relied upon by HDOT in the development of the project scope.

The Bidder acknowledges receipt of and certifies that it has completely examined the following listed items: the Hawaii Department of Transportation, Air and Water Transportation Facilities Division General Provisions for Construction Projects dated 2016, the Notice to Bidders, the Special Provisions, if any, the Technical Provisions, the Proposal, the Contract and Bond Forms, and the Project Plans.

In accordance with Section 103D-323, Hawaii Revised Statutes, this proposal is accompanied with a bid security in the amount of 5% of the total amount bid, in the form checked below. (Check applicable bid security submitted with bid.)

Surety Bid Bond (Use standard form),

Cash,

Cashier's Check,

Certified Check, or

(Fill in other acceptable security.)

The undersigned Bidder acknowledges receipt of any addendum issued by the Department by recording in the space below the date of receipt.

Addendum No. 1 _____

Addendum No. 3 _____

Addendum No. 2 _____

Addendum No. 4 _____

In accordance with Section 103D-302, Hawaii Revised Statutes, the undersigned as Bidder, has listed the name of each person or firm, who will be engaged by the Bidder on the project as a Subcontractor or Joint Contractor and the nature of work to be done by each. **The Bidder must adequately and unambiguously disclose the unique nature and scope of the work to be performed by each Subcontractor or Joint Contractor.** For each listed firm, the Bidder declares the respective firm is a Subcontractor or Joint Contractor and is subject to evaluation as a Subcontractor or Joint Contractor. It is understood that failure to comply with the aforementioned requirements may be cause for rejection of the bid submitted.

| <u>Name of Subcontractor</u> | <u>Nature and Scope of Work</u> |
|------------------------------|---------------------------------|
| 1. _____ | _____ |
| 2. _____ | _____ |
| 3. _____ | _____ |
| 4. _____ | _____ |
| 5. _____ | _____ |
| 6. _____ | _____ |
| 7. _____ | _____ |
| 8. _____ | _____ |

| <u>Name of Joint Contractor</u> | <u>Nature and Scope of Work</u> |
|---------------------------------|---------------------------------|
| 1. _____ | _____ |
| 2. _____ | _____ |
| 3. _____ | _____ |

NOTES:

"None" or if left blank indicates no Subcontractor or Joint Contractor.

If more space is needed, attach additional sheets.

The undersigned hereby certifies that the bid prices contained in the attached proposal schedule have been carefully checked and are submitted as correct and final.

This declaration is made with the understanding that the undersigned is subject to the penalty of perjury under the laws of the United States and is in violation of the Hawaii Penal Code, Section 710-1063, unsworn falsification to authorities, of the Hawaii Revised Statutes, for knowingly rendering a false declaration.

Bidder (Company Name)

By _____
Authorized Signature

Print Name and Title

Business Address

Business Telephone

Date

Contact Person (If different from above)

Phone: _____ Email: _____

NOTE:

If Bidder is a CORPORATION, the legal name of the corporation shall be set forth above, the corporate seal affixed, together with the signature(s) of the officer(s) authorized to sign contracts for the corporation. Please attach to this page current (not more than six months old) evidence of the authority of the officer(s) to sign for the corporation.

If Bidder is a PARTNERSHIP, the true name of the partnership shall be set forth above, with the signature(s) of the general partner(s). Please attach to this page current (not more than six months old) evidence of the authority of the partner authorized to sign for the partnership.

If Bidder is an INDIVIDUAL, the bidder's signature shall be placed above.

If signature is by an agent, other than an officer of a corporation or a partner of a partnership, a POWER OF ATTORNEY must be on file with the Department before opening bids or submitted with the bid. Otherwise, the Department may reject the bid as irregular and unauthorized.

PREFERENCES

Bidders agree that preferences shall be taken into consideration to determine the low bidder in accordance with said Sections and the rules promulgated, however, the award of contract will be in the amount of the bid offered exclusive of any preferences.

A. HAWAII PRODUCTS PREFERENCE

In accordance with ACT 174, SLH 2022, effective June 27, 2022, Hawaii Products Preference shall not apply to solicitations for public works construction. Therefore, the Hawaii Products Preference shall not apply to this project.

B. APPRENTICESHIP PROGRAMS PREFERENCE

In accordance with ACT 17, SLH 2009 – Apprenticeship Program, a 5% bid adjustment for bidders that are parties to apprenticeship agreements pursuant to Hawaii Revised Statutes (HRS) Section 103-55.6 may be applied to the bidder's price for evaluation purposes.

Any bidder seeking this preference must be a party to an apprenticeship agreement registered with the Department of Labor and Industrial Relations at the time the offer is made for each apprenticeable trade the bidder will employ to construct the public works projects for which the offer is being made.

The bidder is responsible for complying with all submission requirements for registration of its apprenticeship program before requesting the preference.

Yes, I wish to be considered for the Apprenticeship Programs Preference. I have included Certification Form(s) 1 with my bid.

C. RECYCLED PRODUCT PREFERENCE

Recycled product preference shall not apply to this proposal.

HONOLULU HARBOR
PIER 10
SUBSTRUCTURE REPAIRS
OAHU, HAWAII
JOB S10955
PROPOSAL SCHEDULE

| Item No. | Item Description | Approximate Quantity (a) | Unit | Unit Price (b) | Amount Bid (a x b) |
|----------|---|--|------|----------------|--------------------|
| 1 | Mobilization (Not to exceed 6% sum of all Items, excluding this Item) | L.S. | L.S. | L.S. | \$ _____ |
| 2 | Installation, Maintenance, Monitoring, and Removal of BMP | L.S. | L.S. | L.S. | \$ _____ |
| 3 | Additional Noise, Water Pollution, Dust, and Erosion Control | F.A. | F.A. | F.A. | \$ 15,000 |
| 4 | Pre-Construction Survey | L.S. | L.S. | L.S. | \$ _____ |
| 5 | Gunite Removal | 12,000 | S.F. | \$ _____ | \$ _____ |
| 6 | Full Slab Replacement Repair (Type FS) | 6,500 | S.F. | \$ _____ | \$ _____ |
| 7 | Slab Spall Repair (Type S or SR) | 500 | S.F. | \$ _____ | \$ _____ |
| 8 | Beam Spall Repair (Type B or BR) | 8,000 | S.F. | \$ _____ | \$ _____ |
| 9 | Vertical Spall Repair (Type V or VR) | 500 | S.F. | \$ _____ | \$ _____ |
| 10 | Reinforcing Steel Replacement | 8,000 | LBS | \$ _____ | \$ _____ |
| 11 | Epoxy Coating System | 18,500 | S.F. | \$ _____ | \$ _____ |
| | | TOTAL AMOUNT FOR COMPARISON OF BIDS \$ _____ | | | |

NOTES:

1. Bidders shall submit and upload the complete proposal to HiePRO prior to the bid opening date and time. Proposals received after said due date and time shall not be considered. Any additional support documents explicitly designated as confidential and/or proprietary shall be uploaded as a separate file to HiePRO. Bidders shall not include confidential and/or proprietary documents with the proposal. The record of each bidder and respective bid shall be open to public inspection. Original (wet ink, hard copy) proposal documents are not required to be submitted. Contract award shall be based on evaluation of proposals submitted and uploaded to HiePRO.

FAILURE TO UPLOAD THE COMPLETE PROPOSAL TO HiePRO SHALL BE GROUNDS FOR REJECTION OF THE BID.

If there is a conflict between the specification document and the HiePRO solicitation, the specifications shall govern and control, unless otherwise specified.

2. Bid shall include all Federal, State, County and other applicable taxes and fees.
3. The TOTAL AMOUNT FOR COMPARISON OF BIDS shall be used to determine the lowest responsible bidder.
4. Bidders shall complete all unit prices and amounts. Failure to do so shall be grounds for rejection of bid.
5. If a discrepancy occurs between unit bid price and the bid price, the unit bid price shall govern.
6. If the lowest TOTAL AMOUNT FOR COMPARISON OF BIDS exceeds the funds available for this project, the State reserves the right to negotiate with the lowest responsible bidder as permitted under Section 103D-302, Hawaii Revised Statutes, as amended, to reduce the scope of work and award a contract.
7. Submission of Proposal is a warranty that the bidder has made an examination of the project site and is fully aware of all conditions to be encountered in performing the work and the requirements of the plans and specifications.
8. No additional compensation will be paid by the State for losses, including overhead and profit, resulting from reduced scope of work.
9. Contract time shall remain the same whether or not the overall scope of work is decreased.

SURETY BID BOND

Bond No. _____

KNOW TO ALL BY THESE PRESENTS:

That we, _____
(full name or legal title of offerer)

as Offeror, hereinafter called the Principal, and

(name of bonding company)

as Surety, hereinafter called Surety, a corporation authorized to transact business as a Surety in the State of Hawaii, are held and firmly bound unto

(State/county entity)

as Owner, hereinafter called Owner, in the penal sum of

(required amount of bid security)

Dollars(\$ _____), lawful money of the United States of America, for the payment of which sum well and truly to be made, the said Principal and the said Surety bind ourselves, our heirs, executors, administrators, successors and assigns, jointly and severally, firmly by these presents.

WHEREAS:

The Principal has submitted an offer for

(project by number and brief description)

NOW, THEREFORE:

The condition of this obligation is such that if the Owner shall reject said offer, or in the alternate, accept the offer of the Principal and the Principal shall enter into a contract with the Owner in accordance with the terms of such offer, and give such bond or bonds as may be specified in the solicitation or Contract Documents with good and sufficient surety for the faithful performance of such Contract and for the prompt payment of labor and material furnished in the prosecution thereof as specified in the solicitation then this obligation shall be null and void, otherwise to remain in full force and effect.

Signed this _____ day of _____

Name of Principal (Offeror) (Seal)

Signature

Title

Name of Surety (Seal)

Signature

Title

STATE OF HAWAII
DEPARTMENT OF TRANSPORTATION
HONOLULU, HAWAII

SAMPLE FORMS

Contents:

Sample Contract
Performance Bond (Surety)
Performance Bond
Labor and Material Payment Bond (Surety)
Labor and Material Payment Bond
Chapter 104, HRS Compliance Certificate
Certification of Compliance for Employment of State Residents, Act 192, SLH 2011

CONTRACT

THIS AGREEMENT, made this day of _____, by and between the STATE OF HAWAII, by its Director of Transportation, hereinafter referred to as "STATE", and «CONTRACTOR», «STATE_OF_INCORPORATON», whose business/post office address is «ADDRESS», hereinafter referred to as CONTRACTOR";

WITNESSETH: That for and in consideration of the payments hereinafter mentioned, the CONTRACTOR hereby covenants and agrees with the STATE to complete in place, furnish and pay for all labor and materials necessary for "«PROJECT_NAME_AND_NO»", or such a part thereof as shall be required by the STATE, the total amount of which labor, material and construction shall be computed at the unit and/or lump sum prices set forth in the attached proposal schedule and shall be the sum of «BASIC»----DOLLARS (\$«BASIC_NUMERIC») as follows:

TOTAL AMOUNT FOR COMPARISON OF BIDS.....\$«BASIC_NUMERIC»

which sum shall be provided from State funds, all in accordance with the specifications, the special provisions, if any, the notice to bidders, the instructions to bidders, the proposal and plans for «PROJECT_NO_ONLY», and any supplements thereto, on file in the office of the Director of Transportation. These documents, together with all alterations, amendments, and additions thereto and deductions therefrom, are attached hereto or incorporated herein by reference and made a part of this contract.

The CONTRACTOR hereby covenants and agrees to complete such construction within «WORKING_DAYS» from the date indicated in the Notice to Proceed from the State subject, however, to such extensions as may be provided for in writing under the specifications.

For and in consideration of the covenants, undertakings and agreements of the CONTRACTOR herein set forth and upon the full and faithful performance thereof by the CONTRACTOR, the STATE hereby agrees to pay the CONTRACTOR the sum of «BASIC»---DOLLARS (\$«BASIC_NUMERIC») in lawful money, but not more than such part of the same as is actually earned according to the STATE's determination of the actual quantities of work performed and materials furnished by the CONTRACTOR at the unit or lump sum prices set forth in the attached proposal schedule. Such payment, including any extras, shall be made, subject to such additions or deductions hereto or hereafter made in the manner and at the time prescribed in the specifications and this contract.

An additional sum of «EXTRAS»-----DOLLARS (\$«EXTRA_NUMERIC») is hereby provided for extra work.

All words used herein in the singular shall extend to and include the plural. All words used in the plural shall extend to and include the singular. The use of any gender shall extend to and include all genders.

IN WITNESS WHEREOF, the parties hereto have caused this instrument to be duly executed the day and year first above written.

STATE OF HAWAII

Director of Transportation

«CONTRACTOR»

(Seal)

Signature

Print name

Print Title

Date

PERFORMANCE BOND (SURETY)
(6/21/07)

KNOW TO ALL BY THESE PRESENTS:

That _____,
(Full Legal Name and Street Address of Contractor)

as Contractor, hereinafter called Principal, and _____

(Name and Street Address of Bonding Company)

as Surety, hereinafter called Surety, a corporation(s) authorized to transact business as a
surety in the State of Hawaii, are held and firmly bound unto the _____,
(State/County Entity)

its successors and assigns, hereinafter called Obligee, in the amount of _____

_____ DOLLARS (\$ _____), to which payment Principal and Surety bind themselves,
their heirs, executors, administrators, successors and assigns, jointly and severally, firmly by
these presents.

WHEREAS, the above-bound Principal has signed a Contract with Obligee on
_____, for the following project: _____

hereinafter called Contract, which Contract is incorporated herein by reference and made a part
hereof.

NOW THEREFORE, the condition of this obligation is such that:

If the Principal shall promptly and faithfully perform, and fully complete the Contract in
strict accordance with the terms of the Contract as said Contract may be modified or amended
from time to time; then this obligation shall be void; otherwise to remain in full force and effect.

Surety to this Bond hereby stipulates and agrees that no changes, extensions of time, alterations, or additions to the terms of the Contract, including the work to be performed thereunder, and the specifications or drawings accompanying same, shall in any way affect its obligation on this bond, and it does hereby waive notice of any such changes, extensions of time, alterations, or additions, and agrees that they shall become part of the Contract.

In the event of Default by the Principal, of the obligations under the Contract, then after written Notice of Default from the Oblige to the Surety and the Principal and subject to the limitation of the penal sum of this bond, Surety shall remedy the Default, or take over the work to be performed under the Contract and complete such work, or pay moneys to the Oblige in satisfaction of the surety's performance obligation on this bond.

Signed this _____ day of _____, _____.

(Seal)

Name of Principal (Contractor)

*

Signature

Title

(Seal)

Name of Surety

*

Signature

Title

***ALL SIGNATURES MUST BE ACKNOWLEDGED
BY A NOTARY PUBLIC**

PERFORMANCE BOND

KNOW TO ALL BY THESE PRESENTS:

That we, _____
(full legal name and street address of Contractor)

as Contractor, hereinafter called Contractor, is held and firmly bound unto the

_____ *(State/County entity)*

its successors and assigns, as Obligee, hereinafter called Obligee, in the amount

_____ DOLLARS \$ _____),
(Dollar amount of Contract)

lawful money of the United States of America, for the payment of which to the said Obligee, well and truly to be made, Contractor binds itself, its heir, executors, administrators, successors and assigns, firmly by these presents. Said amount is evidenced by:

- Legal Tender;**
- Share Certificate** unconditionally assigned to or made payable at sight to
Description: _____;
- Certificate of Deposit**, No. _____, dated _____ issued
by _____ drawn on _____ a bank, savings
institution or credit union insured by the Federal Deposit Insurance Corporation or the
National Credit Union Administration, payable at sight or unconditionally assigned to
_____;
- Cashier's Check** No. _____, dated _____
drawn on _____ a
bank, savings institution or credit union insured by the Federal Deposit Insurance
Corporation or the National Credit Union Administration, payable at sight or
unconditionally assigned to _____;
- Teller's Check** No. _____, dated _____
drawn on _____ a
bank, savings institution or credit union insured by the Federal Deposit Insurance
Corporation or the National Credit Union Administration, payable at sight or
unconditionally assigned to _____;
- Treasurer's Check** No. _____, dated _____
drawn on _____ a
bank, savings institution or credit union insured by the Federal Deposit Insurance
Corporation or the National Credit Union Administration, payable at sight or
unconditionally assigned to _____;
- Official Check** No. _____, dated _____
drawn on _____ a
bank, savings institution or credit union insured by the Federal Deposit Insurance
Corporation or the National Credit Union Administration, payable at sight or
unconditionally assigned to _____;
- Certified Check** No. _____, dated _____
accepted by a bank, savings institution or credit union insured by the Federal Deposit
Insurance Corporation or the National Credit Union Administration, payable at sight or
unconditionally assigned to _____;

WHEREAS:

The Contractor has by written agreement dated _____ entered into a contract with Obligee for the following Project: _____

hereinafter called Contract, which Contract is incorporated herein by reference and made a part hereof.

NOW THEREFORE,

The Condition of this obligation is such that, if Contractor shall promptly and faithfully perform the Contract in accordance with, in all respects, the stipulations, agreements, covenants and conditions of the Contract as it now exists or may be modified according to its terms, and shall deliver the Project to the Obligee, or to its successors or assigns, fully completed as in the Contract specified and free from all liens and claims and without further cost, expense or charge to the Obligee, its officers, agents, successors or assigns, free and harmless from all suits or actions of every nature and kind which may be brought for or on account of any injury or damage, direct or indirect, arising or growing out of the doing of said work or the repair or maintenance thereof or the manner of doing the same or the neglect of the Contractor or its agents or servants or the improper performance of the Contract by the Contractor or its agents or servants or from any other cause, then this obligation shall be void; otherwise it shall be and remain in full force and effect.

AND IT IS HEREBY STIPULATED AND AGREED that suit on this bond may be brought before a court of competent jurisdiction without a jury, and that the sum or sums specified in the said Contract as liquidated damages, if any, shall be forfeited to the Obligee, its successors or assigns, in the event of a breach of any, or all, or any part of, covenants, agreements, conditions, or stipulations contained in the Contract or in this bond in accordance with the terms thereof.

The amount of this bond may be reduced by and to the extent of any payment or payments made in good faith hereunder.

Signed and sealed this _____ day of _____, _____.

(Seal) _____

Name of Contractor

Signature*

Title

*ALL SIGNATURES MUST BE ACKNOWLEDGED
BY A NOTARY PUBLIC

LABOR AND MATERIAL PAYMENT BOND (SURETY)
(6/21/07)

KNOW TO ALL BY THESE PRESENTS:

That _____,
(Full Legal Name and Street Address of Contractor)

as Contractor, hereinafter called Principal, and _____

_____,
(Name and Street Address of Bonding Company)

as Surety, hereinafter called Surety, a corporation(s) authorized to transact business as a surety in the State of Hawaii, are held and firmly bound unto the _____,
(State/County Entity)

its successors and assigns, hereinafter called Obligee, in the amount of _____

_____ Dollars (\$ _____), to which payment Principal and Surety bind themselves, their heirs, executors, administrators, successors and assigns, jointly and severally, firmly by these presents.

WHEREAS, the above-bound Principal has signed Contract with the Obligee on _____ for the following project: _____

_____ hereinafter called Contract, which Contract is incorporated herein by reference and made a part hereof.

NOW THEREFORE, the condition of this obligation is such that if the Principal shall promptly make payment to any Claimant, as hereinafter defined, for all labor and materials supplied to the Principal for use in the performance of the Contract, then this obligation shall be void; otherwise to remain in full force and effect.

1. Surety to this Bond hereby stipulates and agrees that no changes, extensions of time, alterations, or additions to the terms of the Contract, including the work to be performed thereunder, and the specifications or drawings accompanying same, shall in any way affect its obligation on this bond, and it does hereby waive notice of any such changes, extensions of time, alterations, or additions, and agrees that they shall become part of the Contract.

2. A "Claimant" shall be defined herein as any person who has furnished labor or materials to the Principal for the work provided in the Contract.

Every Claimant who has not been paid amounts due for labor and materials furnished for work provided in the Contract may institute an action against the Principal and its Surety on this bond at the time and in the manner prescribed in Section 103D-324, Hawaii Revised Statutes, and have the rights and claims adjudicated in the action, and judgment rendered thereon; subject to the Obligee's priority on this bond. If the full amount of the liability of the Surety on this bond is insufficient to pay the full amount of the claims, then after paying the full amount due the Obligee, the remainder shall be distributed pro rata among the claimants.

Signed this _____ day of _____, _____.

(Seal)

Name of Principal (Contractor)

*

Signature

Title

(Seal)

Name of Surety

*

Signature

Title

***ALL SIGNATURES MUST BE ACKNOWLEDGED
BY A NOTARY PUBLIC**

LABOR AND MATERIAL PAYMENT BOND

KNOW TO ALL BY THESE PRESENTS:

That we, _____
(full legal name and street address of Contractor)

as Contractor, hereinafter called Contractor, is held and firmly bound unto _____
(State/County entity)

its successors and assigns, as Obligee, hereinafter called Obligee, in the amount
_____ DOLLARS (\$ _____)
(Dollar amount of Contract)

lawful money of the United States of America, for the payment of which to the said Obligee, well and truly to be made, Contractor binds itself, its heir, executors, administrators, successors and assigns, firmly by these presents. Said amount is evidenced by:

- Legal Tender;
- Share Certificate unconditionally assigned to or made payable at sight to _____
Description: _____
- Certificate of Deposit, No. _____, dated _____ issued by _____ drawn on _____ a bank, savings institution or credit union insured by the Federal Deposit Insurance Corporation or the National Credit Union Administration, payable at sight or unconditionally assigned to _____;
- Cashier's Check No. _____, dated _____ drawn on _____ a bank, savings institution or credit union insured by the Federal Deposit Insurance Corporation or the National Credit Union Administration, payable at sight or unconditionally assigned to _____;
- Teller's Check No. _____, dated _____ drawn on _____ a bank, savings institution or credit union insured by the Federal Deposit Insurance Corporation or the National Credit Union Administration, payable at sight or unconditionally assigned to _____;
- Treasurer's Check No. _____, dated _____ drawn on _____ a bank, savings institution or credit union insured by the Federal Deposit Insurance Corporation or the National Credit Union Administration, payable at sight or unconditionally assigned to _____;
- Official Check No. _____, dated _____ drawn on _____ a bank, savings institution or credit union insured by the Federal Deposit Insurance Corporation or the National Credit Union Administration, payable at sight or unconditionally assigned to _____;
- Certified Check No. _____, dated _____ accepted by a bank, savings institution or credit union insured by the Federal Deposit Insurance Corporation or the National Credit Union Administration, payable at sight or unconditionally assigned to _____;

WHEREAS:

The Contractor has by written agreement dated _____ entered into a contract with Obligee for the following Project: _____

hereinafter called Contract, which Contract is incorporated herein by reference and made a part hereof.

NOW THEREFORE,

The condition of this obligation is such that, if Contractor shall promptly and faithfully perform the Contract in accordance with, in all respects, the stipulations, agreements, covenants and conditions of the Contract as it now exists or may be modified according to its terms, free from all liens and claims and without further cost, expense or charge to the Obligee, its officers, agents, successors or assigns, free and harmless from all suits or actions of every nature and kind which may be brought for or on account of any injury or damage, direct or indirect, arising or growing out of the doing of said work or the repair or maintenance thereof or the manner of doing the same or the neglect of the Contractor or its agents or servants or the improper performance of the Contract by the Contractor or its agents or servants or from any other cause, then this obligation shall be void; otherwise it shall be and remain in full force and effect.

AND IT IS HEREBY STIPULATED AND AGREED that suit on this bond may be brought before a court of competent jurisdiction without a jury, and that the sum or sums specified in the said Contract as liquidated damages, if any, shall be forfeited to the Obligee, its successors or assigns, in the event of a breach of any, or all, or any part of, covenants, agreements, conditions, or stipulations contained in the Contract or in this bond in accordance with the terms thereof.

AND IT IS HEREBY STIPULATED AND AGREED that this bond shall inure to the benefit of any and all persons entitled to file claims for labor performed or materials furnished in said work so as to give any and all such persons a right of action as contemplated by Sections 103D-324(d) and 103D-324(e), Hawaii Revised Statutes.

The amount of this bond may be reduced by and to the extent of any payment or payments made in good faith hereunder, inclusive of the payments of mechanics' liens which may be filed of record against the Project, whether or not claim for the amount of such lien be presented under and against this bond..

Signed this _____ day of _____, _____.

(Seal) _____

Name of Contractor

Signature*

Title

ALL SIGNATURES MUST BE ACKNOWLEDGED BY A NOTARY PUBLIC

CHAPTER 104, HRS COMPLIANCE CERTIFICATE

The undersigned bidder does hereby certify to the following:

1. Individuals engaged in the performance of the contract on the job site shall be paid:
 - A. Not less than the wages that the director of labor and industrial relations shall have determined to be prevailing for corresponding classes of laborers and mechanics employed on public works projects; and
 - B. Overtime compensation at one and one-half times the basic hourly rate plus fringe benefits for hours worked on Saturday, Sunday, or a legal holiday of the State or in excess of eight hours on any other day.
2. All applicable laws of the federal and state governments relating to workers' compensation, unemployment compensation, payment of wages, and safety shall be fully complied with.

DATED at Honolulu, Hawaii, this _____ day of _____, 20__.

«CONTRACTOR»
Name of Corporation, Partnership, or Individual

Signature and Title of Signer

Notary Seal
NOTARY ACKNOWLEDGEMENT

Subscribed and sworn before me this _____ day of _____
Notary signature _____
Notary public, State of _____
My Commission Expires: _____

Notary Seal
NOTARY CERTIFICATION

Doc. Date: _____ #Pages: _____
Notary Name: _____ Circuit _____
Doc. Description: _____

Notary signature _____
Date _____

**PROVISIONS TO BE INCLUDED IN
CONSTRUCTION PROCUREMENT SOLICITATIONS**

1. Definitions for terms used in HRS Chapter 103B as amended by Act 192, SLH 2011:
 - a. "Contract" means contracts for construction under 103D, HRS.
 - b. "Contractor" has the same meaning as in Section 103D-104, HRS, provided that "contractor" includes a subcontractor where applicable.
 - c. "Construction" has the same meaning as in Section 103D-104, HRS.
 - d. "General Contractor" means any person having a construction contract with a governmental body.
 - e. "Procurement Officer" has the same meaning as in Section 103D-104, HRS.
 - f. "Resident" means a person who is physically present in the State of Hawai'i at the time the person claims to have established the person's domicile in the State of Hawai'i and shows the person's intent is to make Hawai'i the person's primary residence.
 - g. "Shortage trade" means a construction trade in which there is a shortage of Hawai'i residents qualified to work in the trade as determined by the Department of Labor and Industrial Relations.

2. HRS Chapter 103B as amended by Act 192, SLH 2011--Employment of State Residents Requirements:
 - a. A Contractor awarded a contract shall ensure that Hawai'i residents comprise not less than 80% of the workforce employed to perform the contract work on the project. The 80% requirement shall be determined by dividing the total number of hours worked on the contract by Hawai'i residents, by the total number of hours worked on the contract by all employees of the Contractor in the performance of the contract. The hours worked by any Subcontractor of the Contractor shall count towards the calculation for this section. The hours worked by employees within shortage trades, as determined by the Department of Labor and Industrial Relations (DLIR), shall not be included in the calculation for this section.

- b. Prior to award of a contract, an Offeror/Bidder may withdraw an offer/bid without penalty if the Offeror/Bidder finds that it is unable to comply with HRS Chapter 103B as amended by Act 192, SLH 2011.
- c. Prior to starting any construction work, the Contractor shall submit the subcontract dollar amount for each of its Subcontractors.
- d. The requirements of this section shall apply to any subcontract of \$50,000 or more in connection with the Contractor; that is, such Subcontractors must also ensure that Hawai'i residents comprise not less than 80% of the Subcontractor's workforce used to perform the subcontract.
- e. The Contractor and any Subcontractor whose subcontract is \$50,000 or more shall comply with the requirements of HRS Chapter 103B as amended by Act 192, SLH 2011.
 - 1) Certification of compliance shall be made in writing under oath by an officer of the General Contractor and applicable Subcontractors and submitted with the final payment request.
 - 2) The certification of compliance shall be made under oath by an officer of the company by completing a "Certification of Compliance for Employment of State Residents" form and executing the Certificate before a licensed notary public.
 - 3) In addition to the certification of compliance as indicated above, the Contractor and Subcontractors shall maintain records such as certified payrolls for laborers and mechanics who performed work at the site and time sheets for all other employees who performed work on the project. These records shall include the names, addresses and number of hours worked on the project by all employees of the Contractor and Subcontractor who performed work on the project to validate compliance with HRS Chapter 103B as amended by Act 192, SLH 2011. The Contractor and Subcontractors shall retain these records and provide access to the State for a minimum period of four (4) years after the final payment, except that if any litigation, claim, negotiation, investigation, audit or other action involving the records has been started before the expiration of the four-year period, the Contractor and Subcontractors shall retain the records until completion of the action and resolution of all issues that arise from it, or until the end of the four-year period, whichever occurs later. Furthermore, it shall be the Contractor's responsibility to enforce compliance with this provision by any Subcontractor.

- f. A General Contractor or applicable Subcontractor who fails to comply with this section shall be subject to any of the following sanctions:
- 1) With respect to the General Contractor, withholding of payment on the contract until the Contractor or its Subcontractor complies with HRS Chapter 103B as amended by Act 192, SLH 2011.
 - 2) Proceedings for debarment or suspension of the Contractor or Subcontractor under Hawai'i Revised Statutes §103D-702.
3. Conflict with Federal Law: This section shall not apply if the application of this section is in conflict with any federal law, or if the application of this section will disqualify the State from receiving Federal funds or aid.

**CERTIFICATION OF COMPLIANCE
FOR
EMPLOYMENT OF STATE RESIDENTS
HRS CHAPTER 103B, AS AMENDED BY ACT 192, SLH 2011**

Project Title: _____

Agency Project No: _____

Contract No.: _____

As required by Hawai'i Revised Statutes Chapter 103B, as amended by Act 192, Session Laws of Hawaii 2011—Employment of State Residents on Construction Procurement Contracts, I hereby certify under oath, that I am an officer of _____ and
(Name of Contractor or Subcontractor Company)
for the Project Contract indicated above, _____ was in
(Name of Contractor or Subcontractor Company)
compliance with HRS Chapter 103B, as amended by Act 192, SLH 2011, by employing a workforce of which not less than eighty percent are Hawai'i residents, as calculated according to the formula in the solicitation, to perform this Contract.

I am an officer of the **Contractor** for this contract.

I am an officer of a **Subcontractor** for this contract.

CORPORATE SEAL

(Name of Company)

(Signature)

(Print Name)

(Print Title)

Subscribed and sworn to me before this
____ day of _____, 2011.

Doc. Date: _____ # of Pages _____ 1st Circuit

Notary Name: _____

Doc. Description: _____

Notary Public, 1st Circuit, State of Hawai'i
My commission expires: _____

Notary Signature

Date

NOTARY CERTIFICATION