

**Specifications Contact Information:**

Jason Misaki

[jason.c.misaki@hawaii.gov](mailto:jason.c.misaki@hawaii.gov)

- 1. New 2026 or Latest Production Model, Amphibious Marsh Master, w/Trailer, delivered FOB State of Hawaii, DLNR, Division of Forestry & Wildlife, 743 Ulukahiki St Kailua, HI 96734. Vendor must be an Authorized Marsh Master Dealer and be able to provide repair and maintenance services.**

Minimum Specifications Below

<b><u>Category</u></b>	<b><u>Specifications</u></b>
<ul style="list-style-type: none"><li>• Make:</li><li>• Model:</li></ul>	<p>Marsh Master MM-2MX-KC</p>
<ul style="list-style-type: none"><li>• <b>All-Welded High-Strength Body:</b></li><li>• <b>Amphibious Capability:</b></li><li>• <b>High Ground Clearance &amp; Stability:</b></li><li>• <b>Rear Hydraulic Three-Point Hitch:</b></li><li>• <b>Overhead Cargo Rack:</b></li><li>• <b>Advanced Diesel Power System:</b></li><li>• <b>Maintenance-Free Emissions System:</b></li><li>• <b>Efficient Cooling System:</b></li></ul>	<p>Constructed with 3/16" high-strength pontoon bottoms, delivering durability and structural integrity in demanding environments.</p> <p>Operates at speeds up to 7 mph on land and 1 mph in water, with a floating load capacity of 1,800 lbs for versatile terrain access.</p> <p>Provides 38.5" of ground clearance and a full-width walking deck across the tracks for improved accessibility and operator safety.</p> <p>Equipped with a quick-tach system for fast and efficient implement installation and removal, increasing overall machine versatility.</p> <p>Standard bolt-on rack supports up to 100 lb of gear, with optional deck inserts and railing systems available for expanded cargo configurations.</p> <p>Powered by a 74 HP Tier 4 Rehlko KDI2504TCR diesel engine paired with twin hydrostatic transmissions for reliable performance and smooth operation.</p> <p>DOC-only system eliminates the need for DEF, DPF, and regeneration, reducing downtime and simplifying maintenance.</p> <p>Features a thermostatically controlled hydraulic-driven fan with reversing capability, along with a side-by-side radiator and oil cooler for optimal performance.</p>

- **Hydraulic Auxiliary Circuits:** Includes both low-flow (6 GPM @ 2000 PSI) and high-flow (30 GPM @ 3500 PSI) circuits to support a wide range of attachments.
- **Heavy-Duty Track System:** Utilizes 28" wide cleats with low-stretch rubber belts, urethane drive lugs, and UHMW sprockets to ensure traction, durability, and smooth operation.
- **Sealed Bogie Wheel System:** Oil bath lubricated and fully sealed bogie axle assemblies eliminate external greasing, with 500-hour service intervals and easy bolt-on replacement.
- **Corrosion-Resistant Construction:** Stainless-steel fasteners and track hardware, along with anodized aluminum bearing housings, provide long-term durability in harsh and saltwater environments.
- **Hydraulic Winch System:** Front-mounted 10,000 lb hydraulic winch with 130 ft of 3/8" cable and porthole window for improved operator visibility during operation.
- **Integrated Camera System:** Dual rearview cameras with in-cab display enhance visibility and operational safety.
- **Operator Convenience & Electrical System:** Includes a Murphy Powerview® multifunction display, LED front and rear light bars, 12V auxiliary outlets, enclosed battery compartment, and in-cab battery cut-off switch.
- **Accessible Fuel System:** Features a 29-gallon secured aluminum fuel tank mounted in the rear bed for easy access and servicing.

## Marsh Master Extra Long Trailer

### Category

### Specifications

- Make: Marsh Master Extra Long Trailer
- Model: MM-2 TRLR XLG-L
- **Tilt Deck Design:** Features an 8'4" × 20' tilt deck with a 15-degree tilt angle, allowing for efficient loading and unloading of equipment.
- **Fixed Front Deck:** Includes an 8'2" × 48" fixed deck with four integrated D-ring tie-downs for additional cargo support and securement.
- **Gravity Tilt System with Hydraulic Dampener:** Utilizes a gravity tilt system with a hydraulic dampener and adjustable orifice, providing controlled and smooth deck operation.
- **Durable Wood Decking:** Constructed with 2 × 10 #1 treated pine decking for long-lasting performance and load support.

- **Integrated Guide System:** Equipped with a bolt-on, center-mounted guide hump to assist with proper equipment alignment during loading.
- **Convenient Deck Access:** Includes a steel step on the driver's side of the fixed deck and a bolt-on galvanized access ladder for safe and easy access.
- **Heavy-Duty Axle System:** Built with two 7,000 lb Dexter TorFlex torsion axles featuring high-profile top mounts, cambered design, and trailing arm positioning at 45 degrees for improved ride quality.
- **Maintenance-Free Hubs:** Equipped with Dexter Nev-R-Lube hubs to reduce maintenance and increase reliability.
- **Commercial-Grade Tire Package:** Outfitted with four 235/80R16 14-ply commercial trailer tires, along with a matching spare tire for added reliability.
- **High Load Capacity:** Rated with a GVWR of 14,000 lb, supporting heavy equipment transport needs.
- **Electric Brake System:** Includes electric brakes with in-cab gain control and a breakaway actuator system for enhanced safety.
- **Adjustable Coupler System:** Features a 2 5/16" auto-latching coupler with adjustable height (24"–28") and an 8,000 lb tongue jack for easy hookup and leveling.
- **Heavy-Duty Frame Construction:** Constructed from steel channel and I-beam, with a durable black polymeric finish (optional hot-dip galvanizing available) for long-term durability.
- **Integrated Safety Features:** Includes rear underride protection guard and dual 3/8" safety chains for secure transport.
- **DOT-Compliant Lighting System:** Equipped with LED stop/taillights, amber and red clearance lights, reflectors, and reflective tape to meet DOT standards.
- **7-Pin Electrical Connector:** Standard 7-pin round plug ensures compatibility with most towing vehicles.

**2. New 2026 or Latest Production Model, Rotary Cutter attachment for Marsh Master MM-2MX delivered FOB State of Hawaii, DLNR, Division of Forestry & Wildlife, 743 Ulukahiki St Kailua, HI 96734. Vendor must be an Authorized Marsh Master Dealer and be able to provide repair and maintenance services.**

Minimum Specifications Below

<u>Category</u>	<u>Specifications</u>
• Make:	Marsh Master
• Model:	MM-2MX CUTTER
• <b>Wide Cutting Capability:</b>	Features an 84” cutting width with a 98” overall width, allowing for efficient clearing over large areas.
• <b>Dual Cutting Head Design:</b>	Equipped with two 38” diameter cutting heads to maximize cutting efficiency and coverage.
• <b>High-Performance Blade System:</b>	Each cutting head utilizes two heat-treated steel blades (1/2” x 3” x 11 1/2”), designed for durability and effective material processing.
• <b>3” Cutting Capacity:</b>	Capable of cutting soft wood material up to 3 inches in diameter, making it suitable for vegetation management and land clearing.
• <b>Optimized Blade Speed:</b>	Operates at approximately 1600 spindle RPM with blade tip speeds reaching 18,000 feet per minute for efficient cutting performance.
• <b>Independent Hydraulic Drive Motors:</b>	Two hydraulic motors (one per cutting head), each rated up to 50 HP, deliver reliable and consistent power.
• <b>Heavy-Duty Spindle Assembly:</b>	Features extra heavy-duty spindles with Timken tapered roller bearings, grease-lubricated and protected seals to prevent debris wrap-up.
• <b>Durable Aluminum Deck Construction:</b>	Built with a 1/4” thick 5086 aluminum deck and reinforced with 3/8” thick 6061-T6 aluminum pivot mounts and bolt-on steel bosses for added strength.
• <b>Adjustable Skid System:</b>	Heavy-duty, height-adjustable skis support the cutter deck and include replaceable wear pads for extended service life.
• <b>Rear Hydraulic Tilt &amp; Lift System:</b>	Utilizes a rear-mounted 3-point hitch with hydraulic operation and mechanical controls for precise positioning and adjustment.
• <b>Integrated Safety System:</b>	Includes a foot switch that must be engaged for cutter operation, a push/pull dash-mounted engagement switch, and a hydraulic blade brake to stop blade rotation after shutdown.
• <b>Lightweight Design:</b>	Weighs approximately 840 lbs, balancing durability with efficient machine performance.

**3. New 2026 or Latest Production Model, Roller Chopper attachment for Marsh Master MM-2MX delivered FOB State of Hawaii, DLNR, Division of Forestry & Wildlife, 743 Ulukahiki St Kailua, HI 96734. Vendor must be an Authorized Marsh Master Dealer and be able to provide repair and maintenance services.**

Minimum Specifications Below

<u>Category</u>	<u>Specifications</u>
<ul style="list-style-type: none"> <li>• Make:</li> <li>• Model:</li> </ul>	<p>Marsh Master MM-2LX ROLLER CHOP.</p>
<ul style="list-style-type: none"> <li>• <b>Durable Mechanical Drum Design:</b></li> <li>• <b>Heavy-Duty 16" Drum:</b></li> <li>• <b>Chevron-Patterned Flat Bars:</b></li> <li>• <b>Vegetation Management Performance:</b></li> <li>• <b>Wide Coverage Efficiency:</b></li> <li>• <b>Water-Ready Operation:</b></li> <li>• <b>Optimized Dimensions:</b></li> <li>• <b>Easy Attachment:</b></li> <li>• <b>Substantial Unit Weight:</b></li> </ul>	<p>Built with greaseable bearings on both ends of the roller for long-lasting performance and easy maintenance.</p> <p>Includes a drain plug, allowing the drum to be filled for additional weight when needed.</p> <p>Equipped with 4" flat bars welded in a chevron pattern to improve effectiveness and coverage.</p> <p>Rolls and flattens grasses while tracking which is ideal for invasive cattail control and creating open water areas for improved waterfowl habitat.</p> <p>Creates an 8-foot open swath with each pass for faster, more efficient operation.</p> <p>Effective in standing water up to 3 feet deep, making it well-suited for wetland environments.</p> <p>Drum Width: 86" Overall Width: 96"</p> <p>Quickly and securely attaches to the three-point hitch system and is marsh master compatible.</p> <p>Total weight of 775 lbs ensures stability and effective operation.</p>

**4. New 2026 or Latest Production Model, Disc Harrows attachment for Marsh Master MM-2MX delivered FOB State of Hawaii, DLNR, Division of Forestry & Wildlife, 743 Ulukahiki St Kailua, HI 96734. Vendor must be an Authorized Marsh Master Dealer and be able to provide repair and maintenance services.**

Minimum Specifications Below

**Category**

**Specifications**

- Make: Marsh Master
- Model: MM-2LX DISK HARROW
  
- **Effective Soil Turning:** Designed to turn and condition soil efficiently, making it ideal for land preparation and habitat management.
- **Food Plot Preparation:** Perfect for creating and maintaining food plots to support healthy waterfowl populations.
- **Corrosion-Resistant Construction:** Fully galvanized design helps prevent rust, extending the life of the equipment in wet and harsh environments.
- **Efficient Cutting Performance:** 66" cutting width provides consistent, productive coverage across a variety of terrain.
- **Deep Cutting Capability:** Achieves a maximum cutting depth of up to 6", allowing for effective soil penetration.
- **Optimized Disc Configuration:** Features 16 discs with 7.5" spacing to ensure even and thorough ground engagement.
- **Durable 18" Disc Blades:** Large-diameter blades enhance cutting efficiency and performance in tough conditions.
- **Heavy-Duty Galvanized Frame:** Constructed with 3" square tubing for strength, durability, and long-term reliability.
- **Maintenance-Free Operation:** Sealed bearings eliminate the need for routine maintenance and reduce downtime.

**5. New 2026 or Latest Production Model, Slick Sled attachment, with trailer for Marsh Master MM-2MX delivered FOB State of Hawaii, DLNR, Division of Forestry & Wildlife, 743 Ulukahiki St Kailua, HI 96734. Vendor must be an Authorized Marsh Master Dealer and be able to provide repair and maintenance services.**

Minimum Specifications Below

<u>Category</u>	<u>Specifications</u>
• Make:	Marsh Master
• Model:	MM-2LX SLICK SLED-A
• <b>Pivoting Hitch System:</b>	Equipped with a pivoting hitch and steel A-frame tow bar with rotating pintle eye, allowing quick and secure coupling to the Marsh Master while improving maneuverability over rough terrain.
• <b>High Hauling Capacity:</b>	Capable of safely transporting up to 4,000 lb of personnel and materials across land or water, with a rated hauling capacity of 3,500 lb.
• <b>Amphibious Transport Capability:</b>	Designed for both land and water operation, providing a stable platform for transporting equipment and crew in challenging environments.
• <b>Spacious Flat-Deck Design:</b>	Wide 7’6” × 24’ platform with a flat bottom distributes weight efficiently, reducing strain on the tow vehicle while delivering a stable and comfortable ride.
• <b>Landing Craft-Style Loading System:</b>	Fold-down rear transom allows easy loading and unloading of rolling stock, improving jobsite efficiency.
• <b>Personnel Transport Options:</b>	Optional seating configuration accommodates up to 8 personnel for safe crew transport.
• <b>Heavy-Duty Construction:</b>	Constructed from 3/16” 5052 aluminum for strength and durability in harsh operating conditions.
• <b>UHMW Polymer Bottom Protection:</b>	Features a bolt-on 1/2” ultra-tough UHMW polymer sheet on the bottom to reduce wear and extend service life.
• <b>Low Ground Pressure:</b>	Exerts minimal ground pressure (0.66 PSI fully loaded), making it ideal for soft or sensitive terrain.
• <b>Enhanced Terrain Transition:</b>	Front and rear angled rakes with 26” sides allow smooth crossing of ditches and seamless transition between land and water.
• <b>Secure Load Management:</b>	Includes six D-ring tie-down points and additional floor-mounted D-rings for effective cargo securement.

- **Non-Skid Flooring:** Provides improved traction and safety for both personnel and equipment during operation.
- **Integrated Drainage System:** Dual drain plugs allow for quick and efficient water removal.

Minimum Specifications Below

<u>Category</u>	<u>Specifications</u>
<ul style="list-style-type: none"> <li>• Make:</li> <li>• Model:</li> </ul>	<p>Marsh Master SLICK SLED Trailer MM-2 TRLR SSG-L</p>
<ul style="list-style-type: none"> <li>• Tilt Deck: 8' wide x 23' long</li> <li>• Deck Height: 21"</li> <li>• Overall Length: 28'</li> <li>• Deck Material: 2 X 10 #1 Treated Pine</li> <li>• Axles: (1) 6,000 lb. torsion axles</li> <li>• Tires: (2) 235 / 80 R 16 — Load range E</li> <li>• Spare: (1) 235 / 80 R 16 — Load range E Brakes: Electric Brakes on both axles</li> <li>• GVWR: 7200 lbs.</li> <li>• Coupler: Electric brake actuator with breakaway and Auto Latch 2 5/16" adjustable coupler</li> <li>• Coupler Height: 24" – 28" adjustable</li> <li>• Tongue Jack: 5,000 lb</li> <li>• Tilt Control: Power Tilt/Hydraulic</li> <li>• Frame: Painted (polymeric black) OR Hot Dip Galvanized steel channel</li> <li>• Lights: LED reflectors, Four (4) 2" Red and Two (2) 2" Amber and reflective tape on the side and rear per DOT standards.</li> <li>• Light Connector: 7 Pin Round Plug</li> </ul>	

**6. New 2026 or Latest Production Model, Deck Liner accessory for Marsh Master MM-2MX delivered FOB State of Hawaii, DLNR, Division of Forestry & Wildlife, 743 Ulukahiki St Kailua, HI 96734. Vendor must be an Authorized Marsh Master Dealer and be able to provide repair and maintenance services.**

Minimum Specifications Below

**Category**

**Specifications**

- Make: Marsh Master
- Model: DECK LINER
  
- **Advanced Polymer Protection:** Specially formulated polymers permanently bond to your Marsh Master® vehicle's operating surfaces for long-lasting durability.
- **Extreme Environment Defense:** Provides comprehensive protection against harsh conditions, shielding your Marsh Master® amphibious vehicle from both operational wear and environmental elements.
- **All-Condition Durability:** Engineered to withstand damage from debris, moisture, and demanding terrain encountered in the field.
- **Proven Global Performance:** Utilized worldwide across commercial, industrial, agricultural, military, and custom applications.