

Contractor Requirements: Due to the technical complexity of the build the Contractor shall be a Whelen Engineering WEVT certified distributor (certification will be verified with the Whelen RSM) with a permanent physical location in Hawaii. The vehicle(s) shall be available for inspection by DLE OIC (officer in charge) project manager during the build process. The contractor shall have drive-up warranty service available during normal business hours and be available for off-hours service if the need arises. The warranty period shall, at minimum, match the manufacturer's warranty for the provided product(s); and the contractor shall guarantee the integrity of the installation for the service life of the vehicle.

The contractor shall furnish and install a Whelen C399SH CORE-S with CCT5 Handheld controller, SA315 speaker, Howler low frequency speaker, and correct brackets. Whelen FST WeCanX DUO (5) head red/white on driver's side & (5) head blue/white on passenger's side. Whelen RST WeCanX DUO (8) head tray consisting of (4) red/amber on the driver's side & (4) blue/amber on the passenger's side shall be mounted.

The contractor is responsible for selection of the Whelen mounts that most closely match the GOV. Modification to the included brackets and/or fabrication of new brackets will be necessary. Metal shall be cut/bent/welded as needed. Metal shall be coated to prevent corrosion. Completed installation of the Inner Edge assemblies in each vehicle shall be "as intended" by the manufacturer with minimal to no lighting "flashback" to the vehicle occupants.

Lower level lighting shall include (1) WXIONR & (1) WXIONB smoked IONs installed in the front grille area forward facing. Whelen T-ION light heads shall be installed behind the rear quarter windows – side facing – red on the driver's side, blue on the passenger side. Whelen T-ION light heads shall be installed on the lower portion of the liftgate trim – rear facing when opened – red on the driver's side, blue on the passenger side.

Rear OEM LED taillights shall be integrated into the system to flash in response mode - patterns shall be synched to the rest of the warning lights. The contractor

shall properly isolate the lights away from the BCM to eliminate OEM issues. Whelen 3SRCCDCR duo red/white compartment lights, (2) two shall be mounted on the rear inside trim panel – downward facing when open – to provide selectable day/night work lights in the cargo area.

An on-off-on rocker shall be mounted in the rear cargo area for this purpose.

The contractor shall install the department provided Motorola APX8500 mobile radio and antenna.

Final acceptance will be at the discretion of the officer in charge. Any damage to the vehicle by the contractor during the installation shall be repaired at the expense of the contractor.