

WET/DRY VACUUM WITH SUMP PUMP SINGLE MOTOR W/ KIT PUMP

Core Specifications www.nacecare.com +2

- **Motor:** 1,200 W (1.6 HP) bypass motor, rated for 1,100 hours of operation
- **Airflow:** 95 cfm
- **Water Lift:** 100"
- **Capacity:** 12 US gallons
- **Tank Construction:** Structural foam (rustproof) with **10-year warranty** on tank and head
- **Filtration:** 0.5-micron HEPA filter, 98.60% efficiency for improved indoor air quality
- **Noise Level:** 64 dB(A)
- **Weight:** 44 lbs
- **Power Cord:** 42'
- **Dimensions (package):** 34.65" H × 24.61" L × 21.06" W
- **Motor Warranty:** 2 years
- **Tank Warranty:** 10 years

Key Features www.nacecare.com +2

- **Ball float wet shut-off assembly** prevents water from reaching the motor; vapor barriers can be added to eliminate moisture completely.
- **Unique tip-and-pour emptying system** allows draining without a floor drain; dump tube for in-place floor drain emptying.
- **Optional 29" front-mounted squeegee** for wide-area wet floor coverage in a single pass.
- **BB8 standard kit** included; also available with wet/dry, wet only, and combo kits.
- Suitable for schools, large commercial facilities, and industrial maintenance departments where liquid spills and debris are common.



WET/DRY VACUUM W/ DUAL MOTOR

Specifications

- Motor – 1200W
- Water Lift – 100”
- Airflow – 95 cfm
- Noise level – 64 dB(A)
- Motor Life – 1100 hours
- Capacity – 12 gal
- Tank Construction – Structural foam
- Power Cord – 42’
- Weight – 44 lbs.



UPRIGHT 12” DUAL MOTOR VACUUM WITH VACUUM BAG

Airflow Hi	106 cfm
Airflow Lo	100 cfm
Capacity	1.0 US gal
Cleaning Width	12 "
Noise Level	67 dB(A)
Power Cord	40 '
Vacuum Motor	1200 W
Voltage	120 V
Weight	15 lbs



20" BURNISHER 1500 RPM W/ DC MOTOR

Specifications:

- Pad size – 20"
- Speed/RPM – 1500
- Amp Draw – 13.8
- dB rating – 69 dB
- Weight - 90 lbs.
- Motor – 66 frame, rectified DC motor
- Power – 120v – 50/60 Hz power (230v available)
- Power Cord – 50 ft (12-3) Industrial power cord with lock
- Drive – Multi-V belt drive



20" BURNISHER 2000 RPM W/ DC MOTOR

Specifications

Power

- 1.5 HP, 66 frame, DC rectified motor
- 11 SV, 60 Hz power. 50 ft., (14-3) SJT cord with molded plug

Drive System

- Multi V-Belt drives pads at 1500, 1800 or 2000 RPM

Engineered Design

- Built with welded, heavy gauge industrial powder coated steel
- Variable position handle with vinyl grips
- Thumb operated safety switch. Negative pressure on/off switch.
- Dual steel operating triggers.
- 1" x S" non-marking ball bearing wheels
- Includes flexible pad holder with pad centering clamp
- Optional splash guard, dust filter, polishing and burnishing pads

Safety Features

- Quiet operation - 69 dB (Standard), 62 dB (Dust Control)
- Meets GS42 standard



13" FLOOR MACHINE WITH TELESCOPING WAND 1.5 HP

Pad Driver Size	13 inch
Pad Size	12 inch
Speed	175 RPM
Amp Draw	5.5 Amp
Weight	87 lbs
Motor	1.5 HP, 66 frame, dual capacitor AC
Drive System	Triple-planetary XHD 11:1 helical-cut industrial gears
Power Source	115-230V, 50/60 Hz
Power Cord	50 ft. 12-3 SJT power cord w/ molded plug
dB Rating	66 dB – Meets GS42 standard



17" FLOOR MACHINE 1.5 HP

Specifications

- Machine Size – 17"
- Pad size – 16"
- Pad speed – 175 RPM
- Amp Draw – 5.9 Amp
- Weight – 94 lbs
- Motor – 1.5 HP 66 frame, dual capacitor AC
- Drive System – Triple planetary 10:1 helical-cut industrial gears
- Power Source – 115-230V 60 Hz (50 Hz optional)
- Power Cord – 50 ft. 12-3 industrial w/ molded plug
- dB rating – 66 dB – Meets GS42 standard



DOODLE SCRUB DELUXE WITH SKATE CORDED

Specifications

- Weight – 21 lbs
- 30ft power cord
- 4,100 rpm
- 5.25 x 10 pad size

Includes:

2 – Tile & Gout pads	1 – Red Driver pad
2 – Blue Driver pads	1 – Melamine pad
1 – SHO pad	1 – Titan pad
1 - White Driver pad	1 – White pad
1 – SQP pad	



SQUARE SCRUB WITH VACUUM KIT

Specifications

- Pivoting Head Adjusts to Uneven Floors
- Perfect Weight Distribution = Longer Pad Life
- 3450 rpm - 1.5 HP Motor
- Vibration Reducing Handle
- Includes Dust Containment Kit
- Removable Weights
- 50 ft Power Cord
- Stone Care Capable



PRESSURE WASHER 4000 PSI WITH ELECTRIC START

Engine knags32een-4ec00b.com +1

- **Model:** Honda GX390
- **Type:** Air-cooled, 4-stroke OHV
- **Displacement:** 389 cc
- **Fuel:** 86 octane, up to 10% ethanol
- **Oil:** SAE 10W30
- **Battery:** 12V (HW4013HC) or 55Ah marine (HW4013HG)
- **Ignition:** 12V Beckett/Becker burner, adjustable thermostat (max 93°C / 200°F)
- **Heating coil:** 1/2" cold-rolled steel, ignited by burner

Pump images.killer-motors.com (101x1)

- **Model:** Comet ZWD4040G or General EZ4040G triplex
- **Oil type:** 30W non-detergent
- **Adjustable injector**
- **Fuel capacity:** 10 gallons diesel
- **External unloader with 3/6" hose**

Performance knags32een-4ec00b.com +1

- **Pressure:** 4000 psi
- **Flow rate:** 4.0 GPM
- **Hose:** 50 ft, 3/8" double-wire braid
- **Nozzles:** 0°, 15°, 25°, 40°, soaper
- **Gun wand:** 36" insulated
- **Fittings:** Quick connect



AIR MOVER WITH EXTENDABLE HANDLE AND WHEELS 1500 RPM, 1.5 HP

Shipping Weight	21.9 lb.
Length	16 7/8 Inches
Width	15 3/4 Inches
Height	16 1/2 Inches
Power Cord Length	20 Feet
Amps	5 Amps
Hertz	60 Hz
Voltage	115 Volts
Color	Blue
Flow Rate	2,800 CFM
Horsepower	1/2 hp
Material	Polypropylene
Plug Type	NEMA 5-15P
Speeds	3 Speed
Type	Air Movers



AIR MOVER WITH EXTENDABLE HANDLE AND WHEELS

1,550 RPM,1 HP

Frame Type **Fixed Frame**

Extendable Handle Included? **Yes**

Airflow Direction **Variable** ?

Maximum Airflow **3,600 cfm** ?

Number of Speeds **3** ?

Nameplate Voltage **115V AC** ?

Motor Horsepower **1 hp** ?

Current **8.5 A**

Frequency **60 Hz**

Daisy Chain Capability **No** ?

Power Outlets on Unit **0**

GFCI Protected **No**

NEMA Plug Configuration **5-15P**

Power Cord Length **20 ft**

Blower Wheel Diameter **9-3/4 in**

Overall Height **18-11/16 in**

Overall Width **18-11/16 in**

Overall Length **15-7/8 in**

Includes **Wheels**

Standards **CETL; ETL**

Manufacturer Part Number **P-830H-Blue**

Dimensions **18-11/16 in H x 15-7/8 in L x 18-11/16 in W**

Application **Commercial; Home and Office**

Blade Material **Polypropylene**

Housing Material **Polypropylene**

Speed **1,550 RPM**

Nominal Voltage **115V AC**

Country of Origin **China (subject to change)**



JANITOR CART W/ 32 GAL BAG

- **MOBILITY:** Durable 8" wheels and 4" casters provide smooth maneuverability.
- **SLEEK AND MULTI-PURPOSE FUNCTIONAL PLATFORM DESIGN:** Front platform holds WaveBreak mop bucket or up to a 32-gallon BRUTE trash can container.
- **ERGONOMIC TRASH PICK UP COLLECTION:** Front-access zippered bag allows user to easily remove collected waste with no need to lift through the top.
- **EASY ACCESS TO MULTIPLE STICK GOODS AND SAFETY SIGNS:** 11 tool hooks make room for all your cleaning needs, such as brooms, mops, dustpans, dusters, and safety signs.
- **DURABLE COMMERCIAL GRADE CONSTRUCTION:** Water and chemical resistant finish provides easy maintenance and molded-in color for long-lasting use and good looks.

- **Large capacity:** 3 shelves, hooks and holders for all cleaning equipment.
- **Ease of use:** 8" non-marking rear wheels, 4" swivel wheels in front.
- **Bottom shelf** easily accommodates [Bucket/Wringer](#) or [32 Gallon Uline Trash Can](#).
- [Replacement Bag](#) available.



CARPET EXTRACTOR

Voltage (V)	110-120
Frequency (HZ)	50-60
Rated power (W)	-
Brush motor (W)	0.5 HP
Vacuum motor power (W)	1.6 HP
Vacuum (MMH2O)	4.7
Sound pressure level (dB(A))	68+/- 3
Solution flow rate gpm (l/min.)	0.7 gal/min
Handle vibration level m/s2	<0.09
Working width (MM)	18 inch
Cleaning width (MM)	16 inch
Cable length (M)	50 ft
Solution tank (L)	9 gal
Recovery tank (L)	6 gal
Brush speed (RPM)	1400
Dimensions l x w x h (MM)	46x20x35 inch
Gross weight (GVW) (KG)	176 lbs
Net weight (KG)	121 lbs
Shipping weight (KG)	143 lbs

Current draw, rated (A)	14.6
Body height	29 inch
Floor tool	10 inch
Upholstery tool	4.7 inch
Packaging dimensions	35.5x24x36.5 inch



HEATED CARPET EXTRACTOR

W/ WAND, SOLUTION, VAC HOSE, HOSE CUFF, ADAPTER

Body	• Roto-molded polyethylene housing • 10" (25.4 cm) foam-filled rear wheels • 4" (10 cm) locking front casters
Solution Tank	10 gallon (37.9 L) capacity
Vacuum Tank	• 10 gallon (37.9 L) capacity
Vacuum	Dual 3-Stage Vacuum Motors • 5.6" diameter • 200 CFM • 130" water lift
Pump	Diaphragm Demand Pump • 220 PSI • 1.35 GPM
Heater	
Heater	REAL HEAT™ system – 2,000W – 210° maximum
Power Cord	Dual 50' (15.2 m) twist-lock 12/3
Amp Draw (115V 60Hz)	Cord One: 20 amps Cord Two: 18 amps
Amp Draw (230V 50Hz)	Cord One: 10 amps Cord Two: 9 amps
Net Weight	110 lbs. (51.7 kg)
Machine Dimensions	28" x 18.5" x 39" (71 cm x 47 cm x 99 cm)



BACKPACK VACUUM W/ TELESCOPING WAND

CFM Rating	153	Inches Lift	91
Wattage	1296	Amperage	10.8
Voltage	120	Decibel (dBA)	67.9
Capacity (Quarts)	6	Cleaning Path Width (in)	14
Drain Port	No	Power Cord (ft)	50
Power Cord Replacement	101678	Filtration sq in	ProLevel Filtration w/ Four Levels of Filtration:1054 sq. in. total area
ProLevel Filtration System	ProLevel Filtration System with HEPA Media captures 99.8% at 0.3-0.5 microns per ASTM F3150	HEPA Filter	No
Filters Associated	107314, 834072, 510183, 844488	Tool Kit	107100

Tool	Dust Brush, Crevice, Upholstery, Multi-Surface	Wand	Telescoping Coupling
Application	Carpet, Detail Cleaning, Hard Surface	Industry	Education, Commercial Buildings, Healthcare, Hospitality, Transportation
Warranty	3 year warranty on motor, labor and parts. Limited lifetime warranty on molded body parts.	Certifications	UL Listed, CRI Seal of Approval

Accessory Size	1.5 Inch	Hose Diameter (in)	1.5
Hose Length (ft)	4	Product Weight (lb)	12 lb
Product Weight (kg)	5.44 kg	Product Depth (in)	8.13
Product Width (in)	11.94	Product Height (in)	18.35

