

FORKLIFT SPECIFICATIONS - NEW

All specifications listed below are based on a Hyster H90FT forklift. Offers submitted should be for equipment with specifications that are equal to or better than those listed. If the specifications for your equipment does not meet or exceed any of the following criteria, your proposal will not be accepted.

Brand New – not greater than 25 Hours

Gas or diesel engine (no propane)

Rated Capacity 9000 lbs

Load Center, Distance 24"

Side shift-carriage

Fork positioner

Lift Height, Top of Fork (TOF) 200"

Lift speed 121" ft/min

Standard Carriage Width 48"

Forks, Thickness x Width x Length 2" X 5" X 48"

Fork Spread, Outside Dimensions 43.5"

Mast Tilt Angles, Forward/Backward degrees 6/10

TIRES & WHEELS

Tire Size, Front 250 x 15 - 20 Ply

Tire Size, Rear 7.00 x 12 - 14 Ply

Wheelbase 72"

POWERTRAIN

74hp @ 2200RPM 45

Number of Cylinders 4

Hydraulic Tank - capacity (drain & refill) 13.5gal

Fuel Tank Capacity Diesel 20.9"

Auxiliary Hydraulic Pressure Relief for Attachments 2250 psi

WARRANTY

1 year machine, 2 years power train

DELIVERY

Equipment will be on the Young Brothers barge departing Honolulu on Friday, July 28 to Kalaupapa, Molokai. Include cost of delivery to Young Brothers.